PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

ACCEPTED 25 NOV 1981 CAUTION: HARMFUL IF SWAL 1706-159 NALCO

LOWED. Avoid breathing vapors Avoid contact with skin, eyes, or clothing

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Keep out of lakes. streams, or ponds. Permits may be required for discharges containing this pesticide into lakes. streams, ponds, or public water. For guidance, contact the regional office of the Environmental Protection Agency.

STORAGE AND DISPOSAL

Keep container closed when not in use. Do not contaminate water, food, or feed by storage. disposal or cleaning of equipment. Rinsate that cannot be used or reprocessed should be disposed of in a landfill approved for pesticides or buried in a safe price away from water supplies. Open dumping is prohibited.

METAL CONTAINERS: Triple rinse and offer for recycling, reconditioning, or disposal in an approved landfill or bury in a safe place.

PLASTIC CONTAINERS: Do not reuse empty container. Triple rinse and incinerate or dispose of in an approved landfill or bury in a safe place.

> EPA Reg. No. 1706-159 EPA Est. 1706-11-1

1WT-865

MICROORGANISM CONTROL CHEMICAL

ACTIVE INGREDIENTS:

Poly|oxyethylene (dimethyliminio) ethylene (dimethyliminio) ethylene dichloridel....

INERT INGREDIENTS:

This product contains 1.74 lb of active ingredient per gallon and weighs 8.69 lb per gallon

20.09

R() ()

100 0%

KEEP OUT OF REACH OF CHILDREN **CAUTION:**

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED: Drink promptly a large quantity of milk, egg whites, gelatin solution, or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately

DIRECTIONS FOR USE **GENERAL CLASSIFICATION**

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling

NALCO IW1 565 is used to control algae, bacteria. and runge in repreculating commercial and industrial water cooping towers. Prior to its use, systems must be cleaned to re nove algal growth, microbiological slime. and other deposits. An initial slug addition of 2.9 to 7.3. fluid ounces of NALCO 1WT 865 per 1000 gallons of water to provide a concentration of 24 to 60 parts per million of NALCO 1WT-865, based on the total weight of water in the system, is recommended. Repeat initial dosage until control is evident.

Subsequent slug additions of 0.73 to 7.3 fluid ounces of NALCO 1WT-865 per 1000 gallons of water (6 to 60 parts per million of NALCO IWT-865) should be employed every 2 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

NALCO 1WT-865 is used to control bacteria in industrial air-washing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 11.1 to 18.3 fluid ounces of NALCO 1WT-865 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 7.5 to 18.3 fluid ounces of NALCO 1WT-865 per 1000 gailons of water should be employed each 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slugadditions may be made to the sump or to the water collection trays of the airwash system.

SEE SIDE PANEL AT LEFT FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

NALCO CHE COMPANY

6216 WEST 66TH PLACE

NºT CONTENTS SHOWN ELSEWHERE ON CONTAINER

CHICAGO, ILLINOIS 60638