

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER, CORROSIVE. CAUSES IRREVERSIBLE EYE DAMAGE OR SKIN BURNS. HARMFUL IF INHALED, SWALLOWED OR ABSORBED THROUGH SKIN. Do not get in eyes, on skin or on clothing. Prolonged or frequently repeated skin contact may cause allergic reaction in some individuals. Mixers, loaders, and others exposed to this product must wear: long-sleeved shirt and long pants; chemical resistant gloves such as nitrile or butyl rubber; shoes plus socks; goggles and face shield; and chemical resistant apron. Discard clothing or other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry. Users should wash hands before eating, drinking, chewing gum, using tobacco or using the toilet. Users should remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users should remove PPE immediately after handling the product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly. Do not apply this product in a way that will contact workers or other persons.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to aquatic plants, fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL AND CHEMICAL HAZARDS

This product is corrosive to mild steel. Do not store or transport in unlined metal containers.

STORAGE AND DISPOSAL

STORAGE: Do not contaminate water, food, or feed by storage, disposal or cleaning of equipment.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

METAL CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

PLASTIC CONTAINERS: Do not reuse empty container. Triple rinse (or equivalent). Then puncture and dispose of in a sanitary landfill, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.



NALCON® 7678

PAPERMILL SLICICIDE

ACTIVE INGREDIENTS:

5-Chloro-2-methyl-4-isothiazolin-3-one.....	3.11%
2-Methyl-4-isothiazolin-3-one.....	0.94%
INERT INGREDIENTS:	95.95%
Total	100.0%

**KEEP OUT OF REACH OF CHILDREN
DANGER PELIGRO**

FIRST AID

- **IF IN EYES:** Hold eyes open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call a poison control center or doctor for treatment advise.
- **IF SWALLOWED:** Call a poison control center or doctor immediately for treatment advise. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told by a poison control center or doctor.
- **IF ON SKIN:** Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advise.
- **IF INHALED:** Move person to fresh air. If person is not breathing, call 911 or ambulances, then give artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for treatment advise
- **NOTE TO PHYSICIAN:** Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

EPA Reg. No. 1706-170 EPA Est. No. 1706-LA-1 (GV)
 EPA Est. No. 1706-CN-1 (BU) EPA Est. No. 10445-PA-1 (E)
 Letter in () that matches first letter in batch number identifies the establishment number.

ONDEO Nalco Company
 ONDEO Nalco Center
 60563
 (800) 462-5378

ACCEPTED

NET CONTENTS SHOWN ELSEWHERE ON CONTAINER

JUN 21 2001

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 1706-170

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

PAPERMILL WATERS

NALCON 7678 is recommended for the control of bacterial and fungal slime in the production of paper.

POINT OF ADDITION: NALCON 7650 should be added to a point in the system to insure uniform mixing such as the Beater, Hydropulper, or Fan or Broke Storage Pumps.

DOSAGE: Apply 0.17 - 0.56 lbs (2.6 - 8.6 fluid oz) of NALCON 7678 per ton (dry basis) of pulp or paper produced as a slug dose. If needed repeat daily. Badly fouled systems should be cleaned before initial treatment.

POLYMER LATEX PRESERVATION

NALCON 7678 is recommended for the control of bacteria and fungi in the manufacture and storage of synthetic and natural polymer latices including: acrylic; styrene/butadiene; carboxylated styrene/butadiene; ethylene/vinyl acetate; and biopolymers intended for industrial use, such as xanthan gum, gum arabic, guar gum, protein-derived polymers, starches, and casein-derived polymers.

Add 0.16 - 1.22 lbs of NALCON 7678 (72 g - 0.56 kg) to each 1,000 lbs (453.6 Kg) of emulsion to provide 157 to 1240 ppm product (6.25 - 50 ppm active isothiazolones).

NOTE: To insure uniform mixing, add NALCON 7678 to latex or solutions slowly with agitation. The actual concentrations required will depend upon such factors as the specific substance to be treated, frequency of repeated microbial contamination expected, and level of protection required.

COATING PRESERVATION

NALCON 7678 is recommended as an in-container preservative for the control of bacteria and fungi in water-based coatings such as paper coatings.

Add 0.16 - 0.61 lbs of NALCON 7678 (72-278 g) to each 1,000 lbs (453Kg) of fluid to provide 157-620 ppm product (6.25 to 25 ppm active isothiazolones).

DISPERSED PIGMENT PRESERVATION

NALCON 7678 is recommended for the control of bacteria and fungi in the manufacture and storage of dispersed pigments such as kaolin clay, montmorillite clay, titanium dioxide, calcium carbonate, calcium sulfate, barium sulfate, magnesium silicate, and kieselsguhr used in paper production.

Add 0.16 - 0.61 lbs of NALCON 7678 (72-278 g) to each 1,000 lbs (453 Kg) of fluid to provide 157-620 ppm product (6.25-25 ppm active isothiazolones).

SVEZ

1706-170

6-21-2001

11