PRECAUTIONARY STATEMENTS: HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER, CORROSIVE, CAUSES IRREVERSIBLE EYE DAMAGE OR SKIN BURNS, HARMFUL IF INHALED, SWALLOWED OR ABSORBED THROUGH SKIN. Do not get in eyes, on skin or on clothing. Prolonged or frequently repeated skin contact may cause allergic reaction in some individuals. Mixers, loaders, and others exposed to this product must wear: long-sleeved shirt and long pants; chemical resistant gloves such as nitrile or butyl rubber; shoes plus socks; goggles and face shield; and chemical resistant apron. Discard clothing or other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry. Users should wash hands before eating, drinking, chewing gum, using tobacco or using the toilet. Users should remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users should remove PPE immediately after handling the product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly. Do not apply this product in a way that will contact workers or other persons.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to aquatic plants, fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL AND CHEMICAL HAZARDS

This product is corrosive to mild steel. Do not store or transport in unlined metal containers.

STORAGE AND DISPOSAL

STORAGE: Do not contaminate water, food, or feed by storage, disposal or cleaning of equipment.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Immental Control Agency, or the Hazardous Waste representative a. nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

METAL CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities. PLASTIC CONTAINERS: Do not reuse empty container. Triple rinse (or equivalent). Then puncture and dispose of in a sanitary landfill, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

Revised: 6/23/2005



PermaClean®PC-56

AN ANTIMICROBIAL FOR THE TREATMENT OF ULTRA FILTRATION UNITS AND NON-MEDICAL/NON-POTABLE REVERSE OSMOSIS MEMBRANES AND PERIPHERAL SYSTEMS

ACTIVE INGREDIENTS:

5-Chloro-2-methyl-4-isothiazolin-3-one	1.11%
2-Methl-4 isothiazolin-3-one	0.39%
INERT INGREDIENTS:	98.50%
TOTAL	100.00%

This product contains the active ingredients at 0.127 pounds per gallon

KEEP OUT OF REACH OF CHILDREN **DANGER PELIGRO**

FIRST AID

If swallowed:

- · Call a poison control center or a doctor immediately for treatment advice.
- · DO NOT INDUCE VOMITING.
- · Do not give anything to drink.

f in eyes:

- · Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- After at least 15 minutes of rinsing or after it is judged that nearly all of the contamination has been removed. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing.
- Call a poison control center or a doctor immediately for treatment advice.

If on skin or clothing:

- · Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- · Call a poison control center or a doctor for treatment advice.

If inhaled:

- · Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, and then give artificial respiration, preferably mouth-to-mouth if possible.
- · Call a poison control center or a doctor for further treatment advice. NOTE TO PHYSICIAN:

Aspiration may cause lung damage. Probable mucosal damage may contraindicate the use of gastric lavage.

Have the MSDS and, if available, the product container or label with you when calling a poison control center or a doctor, or going for treatment.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

EPA REG. NO. 1706- 183

EPA EST. NO.: 1706-PA-01 EPA EST. NO.: 1706-WA-01

Letter in () that matches first letter in batch number identifies the establishment number.

Corrosive Liquid, Acidic, Organic, N.O.S. (Isothiazolinone Microbiocide), 8, UN 3265, II

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

BADLY FOULED SYSTEMS MUST BE CLEANED BEFORE TREATMENT IS BEGUN.

For controlling bacterial fouling of ultra-filtration units, nonmedical or non-potable reverse osmosis membranes and peripheral systems, where approved for compatibility by the membrane manufacturer or demonstrated by other means to be compatible, add this product to the system inlet water or before any other contaminated area ahead of the Reverse Osmosis or Ultra-filtration unit. Addition should be made with a metering pump on a continuous basis depending on the severity of contamination when treatment is begun, and the guidelines specified by the membrane manufacturer or demonstrated by other means to be compatible. During use of this product for ultra-filtration units and reverse osmosis membranes, both permeate and reject water should be directed to the drain. Once treatment has been completed, rinsing with feedwater should be continued until conductivity values in the permeate are at or below values before O treatment with this product.


FOR CONTROL OF BACTERIAL FOULING

When the system is noticeably fouled, add 2.75-16.5 fluid ounces PermaClean®PC-56 per 1000 gallons of feedwater (20-130 ppm). Product should be fed continuously for a time period of 1 to 24 hours 7 days each week depending on the severity of the problem. For off-line cleaning, PermaClean®PC-56 shoulæ be added to provide a level of 100-400 ppm (13.75-55 fluid ounces per 1000 gallons in the soak tank.)

Nalco Company 1601 West Diehl Road

Naperville, IL 60563-1198 EMERGENCY PHONE NO. (800) 424-9300

NET CONTESTED OFFICE OF CONTESTED ON CONTESTED



1706-183