PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CORROSIVE. CAUSES EYE DAMAGE AND SKIN IRRITATION. MAY BE FATAL IF SWALLOWED. Do not get in eyes, on skin, on clothing. Wear goggles or face shield, rubber gloves and rubber apron when handling. Wash thoroughly after handling. Do not breathe vapor or spray mist.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

STORAGE AND DISPOSAL

PROHIBITIONS: Do not contaminate water, food, or feed by storage or disposal. Keep container tightly closed.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State pesticide or environmental control agency, or the hazardous waste representative at the nearest EPA regional office for guidance.

PLASTIC CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or by incineration or, if allowed by State and Local authorities, by burning. If burned, stay out of smoke.

NET CONTENTS SHOWN ELSEWHERE ON CONTAINER



JUN 0 5 2003

Under the Federal Insecticide, Fungicide, and Rudenticide Act as unrended, for the pesticide, registered under EPA Reg. No. / 706 - / 93

ာ္တို္င္လိ**ONDEO** Nalco

NALCON® D3T-A

INHIBITS AND CONTROLS GROWTH OF SLIME-FORMING BACTERIA AND FUNGI IN PULP AND PAPER MILLS AND IN CASEIN, EMULSIONS, SIZINGS, PASTES AND GLUE SOLUTIONS

ACTIVE INGREDIENT:

DANGER

FIRST AID

- IF IN EYES: Hold eyes open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call a poison control center or doctor for treatment advice.
- IF SWALLOWED: Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told by a poison control center or doctor.
- IF ON SKIN: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.
- IF INHALED: Move person to fresh air. If person is not breathing, call 911 or ambulances, then give artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for treatment advice

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed. Have the MSDS with you when calling a poison control center or a doctor, or going for treatment.

EPA Reg. No. 1706-193

EPA Est. No. 9386-GA-03

Ondeo Nalco Company
Ondeo Nalco Center
Naperville, IL 50563-198
EMERGENCY PHONE NO. (800) 424-9300

manner inconsistent with its labeling.

Nalcon D3T-A should be added at a point in processing where

Nalcon D3T-A should be added at a point in processing where there is sufficient agitation and mixing time to achieve good dispersion.

For bacterial and Fungal Slime Control in Pulp and Paper Mill Systems:

Laboratory tests show that Nalcon D3T-A will inhibit the growth of slime-forming bacteria and fungi in pulp and paper mill systems. Each mill system varies considerably with respect to the composition of the furnish, white water temperatures, the extent of good housekeeping and types of equipment in use. The amount of Nalcon D3T-A required to minimize bacterial and fungal slime is best determined by actual test in the system, and falls in the range of 5-36 fluid ounces per ton of finished product.

Nalcon D3T-A can be added directly from the drums to points in the wet end of the mill system by means of pumps or gravity feed. Good agitation is required for rapid dispersion. Continuous addition is the preferred method to insure adequate concentrations. This may be accomplished by use of metering pumps. Shock dosage is to be avoided. Badly fouled systems must be precleaned before treatment is begun.

For Preservation of Clay Slurries, Adhesives, Coatings, and High Viscosity Suspensions:

Test data show that Nalcon D3T-A is effective as a preservative at use levels of 0.3-0.5% based on formulation in slurries of starch, clay, calcium carbonate or titanium dioxide; paper coatings; high viscosity suspensions (e. g. polymers or silicapolymer combinations); polyvinyl alcohol/polyvinyl acetate-based adhesives and starch-based adhesives. Effectiveness in dextrin adhesives has been shown to be as low as 0.2%. The exact amount will depend on the components, storage time, and temperature, etc., and can best be determined by actual test.

For preservation of slurries and high viscosity suspensions, the material should be added at a point in the processing where there will be sufficient time and agitation for good dispersion.

z>ez

Rev.: 4/14/2003