UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, DC 20460

OFFICE OF PREVENTION, PESTICIDES AND TOXIC SUBSTANCES

FEB - 2 2010

Juli Mann
Paralegal Specialist
1330 Connecticut Avenue, NW
Washington, DC 20036-1795

Subject:

AG-451

EPA Registration Number: 1706-231 Notification Date: January 15, 2010 EPA Receipt Date: January 15, 2010

Dear Ms. Mann:

This will acknowledge receipt of your notification, submitted under the provisions of PR Notice 2007-4.

Proposed Notification:

- Updating Container Disposal statements
- Editorial correction of a typographical error
- Addition of statement to aid in identification of the proper establishment number

General Comment:

Based on a review of the submitted materials, your notification to update the Container Disposal statements, correct a typographical error, and to add a statement to aid in the identification of the proper establishment number is acceptable and a part of the records on file.

Should you have any questions concerning this letter, please contact Heather Garvie at (703) 308-0034 or by email address at garvie.heather@epa.gov.

Sincerely,

Jacqueline McFarlane

(Acting) Product Manager (34) Regulatory Management Branch II Antimicrobials Division (7510P)

1 teuse reau mon menon	on reverse bejore comple					ODD Harristan Number	
p.//	l l	United States		`	Registration	•	
EPA Environmental Protection			0 •		Amendmen	t	
	Wash	ington, DC 2			Other		
Application for Pesticide – Section I							
1. Company/Product Nu	umber			Product Manager		3. Proposed Classification	
1706-231 4. Company/Product (Name)			ShaRon Carlisle PM#			None Restricted	
AG-451			34				
	f Applicant (Include ZIP)	Code)		dited Review. Ir	accordance v	with FIFRA Section 3(c)(3)	
Nalco Company			(b)(i), my product is similar or identical in composition and				
1601 West Diehl Road			labeling to:				
Naperville, IL 60563			EPA Reg. No				
Check if this is a new address			Product Name				
Section - II							
Amendment – Exp.			L	Final printed label	-		
Resubmission in re	esponse to Agency letter d	ated	Agency letter dated				
Notification – Expl	lain Below.	"Me Too" Application					
		Other – Explain Below.					
Explanation: Use additional page(s) if necessary. (For Section I and Section II.)							
Notification of label changes to incorporate revised container handling statements per PR Notice 2007-4 and an additional							
minor label revision and typographical correction per PR Notice 98-10. This notification is consistent with the guidance in PR Notice 2007-4 and PR Notice 98-10 and the requirements of EPA's regulations at							
40 CFR §§ 152.46, 15	66.10, 156.140, 156.144	l, 156.146, ai	nd 156.156. No othe	er changes have b	een made to tl	he labeling or the	
40 CFR §§ 152.46, 156.10, 156.140, 156.144, 156.146, and 156.156. No other changes have been made to the labeling or the Confidential Statement of Formula for this product. I understand that it is a violation of 18 U.S.C. Sec. 1001 to willfully make any false							
statement to EPA. I further understand that if the amended label is not consistent with the requirements of 40 CFR §§ 152.46, 156.10, 156.140, 156.144, 156.146, and 156.156, this product may be in violation of FIFRA and I may be subject to enforcement action and							
	5.146, and 156.156, this ins 12 and 14 of FIFRA.		y be in violation of r	IFHA and i may b	e subject to er	nforcement action and	
•	ESPONDENCE for th		Juli Mann. Stepto	e & Johnson LL	P. 1330 Conne	ecticut Ave., NW,	
Washington, D.C. 20		10 40::	Jun 1, 200-1-1		.,		
			Section - III				
1. Material This Produ	ıct Will Be Packaged In:						
Child-Resistant	Unit Packaging		Water Soluble Packaging 2. 7			f Container	
Packaging	Yes		Yes		Metal	Metal	
Yes	│		□ No			c	
No					Glass		
* Certification		No. per	If "Yes"	No. per	Paper		
must be submitted	Unit Packaging wgt.	Container	Packaging wgt.	Container		(Specify)	
3. Location of Net Cont	- Information	4 Si-a(a) Da	t-il Container				
3. LOCATION OF INCL COM-	ents information	4. Size(s) Ref	-			of Label Directions	
Label			On Lab				
	Container		~			peling accompanying product	
6. Manner in Which Lab	oel is Affixed to Product	Lithogra	-	Oth	er		
		Paper G				0000	
Stencil			led			0 0000	
			Section - IV			0 0	
1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application)							
Name Title Code)							
Juli Mann			Paralegal Specialist	, Steptoe & Johns	son 202-4		
Certification 6.0 Dates Application							
I certify that the statements I have made on this form and all attachments thereto are true, accurate and completes 4							
acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both (Stamped)							
CCCCC							
2. Signature	has	1	Paralegal Specialist, Agent for Nalco Company			occc	
Juli Mann							
4. Typed Mame			5. Date				
Juli Mann /		January 15, 2010					



WRITER'S DIRECT DIAL 202.429.3095

1330 Connecticut Avenue, NW Washington, DC 20036-1795 Tel 202.429.3000 Fax 202.429.3902 steptoe.com

000000

600000

0 0 0 0

ζοιιίι

o c

January 15, 2010

Via Hand Delivery

ShaRon Carlisle, Acting Product Manager 34 Antimicrobials Division (AD) c/o Document Processing Desk (NOTIF) Office of Pesticide Programs (7510P) U.S. Environmental Protection Agency Room S-4900, One Potomac Yard 2777 South Crystal Drive Arlington, VA 22202-4501

Re: Notification to update label per PR Notice 2007-4 and PR Notice 98-10

Product: AG-451 (EPA Reg. No. 1706-231)

Dear Ms. Carlisle:

Please find enclosed a notification to update the container handling statements per PR Notice 2007-4. Additionally, the following minor label revisions were incorporated:

- A statement to to aid in identification of the proper establishment number.
- A correction of a typographic error in the last sentence of the Personal Protective Equipment paragraph: "PE" was changed to "PPE."

The revised and updated language is highlighted in yellow on the enclosed label.

Documents included with this submission include an Application Form (EPA Form 8570-1) and one copy of the updated label.

Correspondence for this matter should be sent to me at the Washington, D.C. address identified above. If you require any further information please contact me at (202) 429-3095. Thank you for your attention to this matter.

Sincerely,

Juli Mann

Paralegal Specialist



INDUSTRIAL MICROBIOCIDE

Date Reviewed By:

......<u>95%</u>

Weight: 9.6 lbs/gal. (1.15 kg/liter)

KEEP OUT OF REACH OF CHILDREN DANGER

FIRST AID

- IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove
 contact lenses, if present, after the first 5 minutes, then continue rinsing. Call a poison control
 center or dector for testiment advice.
- IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible. Call a poison control center or doctor for further treatment advice.
- IF SWALLOWED: Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told by a poison control center or doctor. Do not give anything to an unconscious person
- IF ON SKIN: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

NOTE TO PHYSICIAN: Probable mucosal dumage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed. Have the product container or label with you when calling a poison control center or doctor or going to

For emergency information on AG-451 call the National Pesticides Information Center at 1-800-858-7378, 6:30 AM to 4:30 PM Pacific time (PT), seven days a week. During other times, call the poison control center 1-800-222-1222.

PERSONAL PROTECTIVE EQUIPMENT

Applicators and other handlers must wear: coveralls over long-sleeved shirt and long pants, socks and chemicalresistant footwear, goggles or face shield, and chemical resistant gloves (such as barrier laminate or butyl nitrile/heopener nubber, PVC, or viton).

Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables, use detergent and hot water. Keep and wash PPE separately from other laundry.

User Safety Recommendations

Users must wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet. Users must remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users must remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing.

Application Restrictions:

Do not apply this product in a way that will contact workers or other persons, either directly or through drift. Only protected handlers may be in the area during application.

Engineering Controls:

When handlers use closed metering systems the handler requirements may be reduced or modified to long-sleeve shirt, long pants, shoes and socks.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER. CORROSIVE: Causes irreversible eye damage. May be fatal if inhaled or swallowed. Causes skin irritation. Do not get in eyes, on skin or on clothing. Do not breathe dust. When loading or handling wear protective eyewear (goggles or face shield), long-sleeved shirt and long pants, socks, shoes, chemically resistant gloves and a NIOSH approved respirator. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, or using tobacco. Remove and wash contaminated clothing separated from other before reuse.

ENVIRONMENTAL HAZARDS

Revised: 1/15/10

ACTIVE INGREDIENT

TOTAL

INERT INGREDIENTS.....

2,2-Dibromo-3-nitrilopropionamid

This pesticide is toxic to fish and invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Secondary biological treatment of DBNPA effluent is required for all uses except for use in secondary oil recovery systems. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

DIRECTION FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Controls bacteria, (ungi, and algae in industrial recirculating water cooling tower systems, and in once-through fresh and seawater industrial cooling water systems; controls slime-forming bacteria and fungi, and yeasts in paper mills, metalworking fluids containing water, and enhanced oil recovery systems.

NOTE: Add AG-451 separately to the system.* Do not mix it with other additives, in order to avoid decomposition of AG-451 due to the high pH of many additive formulations.

IN RECIRCULATING WATER SYSTEMS

AG-451 aids in the control of bacterial, fungal, and algal slimes in evaporative condensers, commercial and industrial cooling towers, industrial water scrubbing systems, and brewery pasteurizers. For opinnum performance, add AG-451 at a point of uniform mixing. Addition may be continuous or intermittent (slug) depending on the severity of contamination when treatment is begun. When a metering pump is not used for addition, care should be exercised in handling. Refer to precautionary statements.

Badly fouled systems must be cleaned before treatment is begun.

FOR THE CONTROL OF BACTERIA

INTERMITTENT (SLUG) METHIOD – INITIAL DOSE: When the system is noticeably fouled, add 2.4 – 4.9 fluid ounces of AG-451 per 1000 gallon of water in the system (22-44 ppm). Repeat until control is achieved. SUBSEQUENT DOSE: When control is evident, add 1.2 – 4.8 fluid ounces of AG-451 per 1000 gallons of water in the system (11 – 44 ppm) every four days or as needed to niaintain control.

CONTINUOUS FEED METHOD - INITIAL DOSE: When the system is noticeably fouled, 2.4 - 4.9 fluid ounces of AG-451 per 1000 gallon of water in the system (22-44 ppm).

SUBSEQUENT DOSE: Maintain this level by pumping a continuous feed of 0.5 – 2.4 fluid ounces of AG-451 per 1000 gallon of water (4 – 22 ppm) lost from the system by bleedoff.

FOR CONTROL OF FUNGIAND ALGAE

INTERMITTENT OR SLUG METHOD – INITIAL DOSE: When the system is noticeably fouled, add 25 – 49 fluid ounces of AG-451 per 1000 gallon of water in the system (221-438 ppm). Repeat until control is achieved. SUBSEQUENT DOSE: When microbial control is evident, add 15 - 49 fluid ounces of AG-451 per 1000 gallon of water in the system (135-438 ppm) daily, or as needed to maintain control.

CONTINUOUS FEED METHOD - INITIAL DOSE: [When the system is noticeably fouled add 25 - 49 fluid ounces of AG-451 per 1000 gallon of water in the system (221-438 ppm).

SUBSEQUENT DOSE: Maintain treatment level by pumping a continuous feed of 15 – 49 fluid ounces of AG-451 per 1000 gallon of water in the system (135-438 ppm) per day. Badly fouled systems must be cleaned before treatment is beginn

IN PAPER MILLS

For control of bacterial, fungal, and yeast growths in pulp, paper and paperboard mills, add AG-451 at the rate of 7.7 – 19.2 fluid ounces per ton of pulp or paper (dry basis). Addition may be continuous or intermittent, depending upon the type of system and the severity of the contamination. It should be made with a metering pump at location that will ensure uniform distribution of AG-451 in the mass of fiber and water, such as the beaters, jordan inlet or discharge, broke chest, furnish chests, save-alls, and white-water tanks.

ascarage, took chest, turnish chests, save-aits, and white-water tanks. Heavly foulded systems should be boiled out, then treated with 7.7 – 19.2 fluid ounces of AG-451 per ton of paper (dry basis), as necessary for control. Moderately fouled systems should be treated continuously with 19.2 – 25.9 fluid ounces of AG-451 per ton of paper (dry basis) until the stime accumulation is controlled. Additional rates then be reduced to 7.7 – 19.2 fluid ounces of AG-451 per ton of paper on a continuous or intermittent basis, as needed for control. Dislodged stime may cause breaks in the paper and a clean up of the paper machine may be advisable. Slightly fouled systems should be treated continuously with 7.7 – 19.2 fluid ounces of AG-451 per ton of paper (dry basis) until the stime is controlled, then added on an intermittent basis to maintain control and the stime is controlled, then added on an intermittent basis to maintain control.

IN AIR WASHER SYSTEMS

- Add 1 –32 fluid ounces of AG-451 per 1000 gallons of water in the system (9-285 ppm), depending on the severity of the contamination to control slime-forming bacteria and fungi in the industrial air washing system. NOTE: For use only in industrial air washer systems that maintain effective mist eliminating components. Badly fouled systems must be cleaned before treatment is been.

be cleaned before treatment is oegun.

INTERMITTENT (SLUE) METHOD – BNTIAL DOSE: When the system is noticeably fouled, add 20 – 32 fluid ounces of AG-451 per 1000 gallon of water in the system (176-285 ppm). Repeat until control is achieved. SUBSEQUENT DOSE: When microbial control is exident, add 4 – 10 fluid ounces of AG-451 per 1000 gallon of

water in the system (9-142 ppm) every 2 days or as needed to maintain control. CONTINUOUS FEED NATHOD - INITIAL DOSE: When the system is noticeably Youled add 20 - 32 fluid owness of AG-451 per 1300 gallon of water in the system (178-285 ppm).

SUBSEQUENT DOSE: Maintain treatment level by pumping a continuous feed of 1 - 16 fluid ounces of AG-451 per 1000 gallon of wair in the system (9-142 ppm) per day.

IN METALWORKING FLUIDS CONTAINING WATER This product is effective in resulvorking fluid concentrates which have been diluted yelly years at ratios of 1: 100 –

1.4. For controlling (of inhibiting) the growth of bacteria, fungi, and yeasts that may deteriorate metals of the fluid collection tank. Additions should be made with semetring pump. INTPL-10-98 SUIG DOSE: When the system is noticeably fouled, add 1.0 gallon of 64-55 per 1000 gylory, of metalworking fluid to the system. Repeat until control is achieved. SUBSEQUENT DOSE: When microbial control is evident, add 0.4 = 0.8 gallons of AG-451 per 1000 gallons of metalworking fluid per day, or as needed to maintain control. Additions carbe and so continuously or intermittently. Slug the system as recurrence or an action of the system as recurrence or the system as recurrenc

GNCE-THROUGH INDUSTRIAL COOLING WATER SYSTEMS

For controlling bacteria; 'fangi, and algae in once-through and closed-cycle fresh and sex; water cooling systems, cooling ponds, canals & lagoons, add AG-451 to the system inlet water or before other contaminated areas in the system. Addition should be made with a metering pump. It may be continuous or intermittent depending on severity of contamination when treatment is begun, and retention time in system.

FOR CONTROL OF BACTERIA

TERMITTENT METHOD - INITIAL DOSE: Where stem is noticeably fouled, add 24-48 ppm AG-451 infimum treatment intervals should be 15 minutes. Repet il control is achieved. SUBSEQUENT DOSE: Wher microbial control is evident, add 12-48 ppm AG-451 intermit antly as needed to maintain control.

CONTINUOUS FEED METHOD - INTIAL DOSE: When the system is noticeably fouled, add 24-48 ppm AG-450 continuously to the system. SUBSEQUENT DOSE: When microbial control is evident, pump a continuous feed of 4-24 ppm AG-451 continuously to the system. Baully fouled systems must be cleaned before treatment is begun.

FOR CONTROL OF FUNGI AND ALGAE

INTERMITTENT METHOD – INITIAL DOSE: When the system is noticeably fouled add 240-472 ppm AG-451 to the system. The minimum treatment interval should be 15 minutes. Repeat until control is achieved SUBSEQUENT DOSE: When microbial control is evident, add 144-472 ppm AG-451 to the system dily, or as needed to maintain control. The minimum treatment interval should be 15 minutes. Badly fouled systems must be cleaned before treatment is begun.

CONTINUOUS FEED METHOD - INITIAL DOSE: When the system is noticeably fouled add 240-472 ppm AG-451 to the system. SUBSEQUENT DOSE: When microbial control is evident, pump a continuous feed of 144-47; ppm AG-451 to the system. Badly fouled systems must be cleaned before treatment is beeun.

IN ENHANCED OIL-RECOVERY SYSTEMS

For controlling slime-forming bacteria, yeasts and fungi in oil field water, polymer or mycellar floods, water disposa systems, or other oil field water systems, add 0.4 – 25 gallons of AG-451 per 2400 barrels of water, depending on the severity of contamination. Additions should be made with a metering pump either continuously or intermittently. CONTINUOUS FEED METHOD: When the system is noticeably fouled, add 3.2 – 25 gallons of AG-451 per 2400 barrels of water continuously until the desired degree of control is achieved. Subsequently treat with 0.4 – 4.8 gallons of AG-451 per 2400 barrels of water continuously or an exceled to maintain control.

INTERNITIENT (SLUG) METHOD: When the system is noticeably fouled, or to maintain control of the system add 3.2 – 25 gallons of AG-451 per 2400 barrels of water intermittently for 4.8 hours per day or as needed depending on the severity of contamination. Addition of AG-451 may be made at the free water knockouts, before or after the injection pumps and injection well headers. NOTE: For control of bacteria, yeast and fungi in aqueous solutions of biopolymer used in flooding operations, add 4.8 – 25 gallons of AG-451 on the per 2400 barrels of water. Additions of AG-451 should be made with a metering pump immediately after the preparation of the aqueous biopolymer solution to prevent loss of viscosity.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

PESTICIDE STORAGE: To maintain product quality, store at temperatures below 60° C. Keep container tightly closed when not in use.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance. (Instructions for refillable containers:)

CONTAINER HANDLING: Refillable container. Refill this container with pesticide only. Do not reuse this container for any other purpose. Cleaning the container fore final disposal is the responsibility of the person disposing of the container. To clean the container before final disposal, empty the remaining contents from this container into application equipment or mix tank. Fill the container about 10 percent full with water. Agitate vigorously or recirculate water with the pump for 2 minutes. Pour or pump rineste into application equipment or rinsate collection system. Repeat this rinsing procedure two more times. Then offer for recycling, if available, or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedure approved by state and local nuthorities.

(Instructions for non-refillable containers greater than 5 gallons:)

CONTAINER HANDLING: Non-refliable container. Do not reuse or refill this container. Triple rinse (or equivalent) container promptly after emptying. Triple rinse as follows: Empty remaining contents into application equipment or a mix tank. Fill the container of 4 full with water. Replace and tighten closures. Tip container on its side and roll it back, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinstet into application equipment or a mix tank or stope rinstet for later use or disposal. Repeat this procedure two more times. Then offer for recycling, if available, or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedure approved by state and local authorities.

(Instructions for non-refillable containers 5 gallons or less:)

CONTAINER HANDLING: Non-refillable container. Do not reuse or refill this container. Triple rinse (or equivalent) container promptly after emptying. Triple rinse as follows: Empty remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container 4 full with water and recap. Shake for 10 seconds. Pour rinsule into application equipment or a mix tank or store rinsule for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times. Then offer for recycling, if available, or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedure approved by state and local authorities.

NET CONTENTS SHOWN ELSEWHERE ON CONTAINER

EPA REG. NO. 1706-231

EPA EST. NO. 1706-PA-1

EPA EST. NO. 1706-OH-I

Letters in () that match the prefix in batch number identify the establishment number

Nalco Company 1601 West Diehl Road Naperville, IL 60563-1198 Emergency Phone No.: (800) 424-9300

[Batch/Lot Number: Note to EPA Reviewer: Batch/Lot number may or may not appear on the label