



MOBILE PAINTS

Active Ingredient	
Copper Naphthenate	20.0%
Inert Ingredient	80.0%
Total	100.0%
Copper as Metal	2.0%

COP-R-TOX contains 2% copper as metal. U.S. Dept. of Commerce Commercial Standard CS152-48 requires only 1% copper as metal.

PROTECTS WOOD
COP-R-TOX soaks into wood, filling the pores with copper, giving it protection against mold, termites, and fungus.

MARINE USE
PROTECTS CANVAS, ROPES, NETS & SEINES.
COP-R-TOX saturates the fibre with protection against rot, mildew, and fungus. Its waterproofing qualities make it exceptionally valuable in the preservation of these materials adding long life and strength.

FOR WOOD BOATS
COP-R-TOX affords protection against mold, rot, and fungus in interior bilge and unpainted surface as well as exteriors which are to be painted. When used on bare wood below waterline, before using copper paint, COP-R-TOX gives 30 to 60 days protection in the event the anti-fouling paint is scraped off by contact with pilings or grounded.

DIRECTIONS
COP-R-TOX is a 20% active solution and each gallon may be thinned with 1 gallon of mineral thinner to equal a 10% active solution.

COP-R-TOX preserves and protects all types of unpainted wood surfaces, lumber, timbers, fish nets, rope or twine. The formula of COP-R-TOX was tested in the Tropics by U.S. Government Agencies and found to be highly efficient in all Tropical and Semi-Tropical climates.

COP-R-TOX may be applied by brushing freely, spray, or dipping in a tank or trough. COP-R-TOX is most effective on unpainted dry, clean lumber as COP-R-TOX penetrates the pores and wood cells filling them with copper, preventing termites, decay fungus, mildew. COP-R-TOX may be painted over in 24 hours as it contains no epoxy or tar products.

A green cast may be noted in the first priming coat of paint over COP-R-TOX, caused by picking up copper deposit on the surface, but this is not bleeding and will not show in succeeding coats of paint or enamel.

All wood which is to be in contact with the earth should receive 2 flowing coats by brush or spraying or be dipped for at least 5 minutes. Other wood surfaces require only 1 coat. This material is harmful if taken internally.

COP-R-TOX covers 300 square feet per gallon one coat.

CAUTION!

HARMFUL OR FATAL IF SWALLOWED

CONTAINS PETROLEUM DISTILLATE. If swallowed, CALL PHYSICIAN IMMEDIATELY. COMBUSTIBLE. Keep away from heat and open flame. Avoid contact with skin and breathing of vapor or spray mist. Do not transfer contents to bottles or other unlabeled containers. Close container after each use. Do not take internally. Do not reuse empty container. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

USE WITH ADEQUATE VENTILATION
KEEP OUT OF REACH OF CHILDREN

USDA REG. NO. 1719-2

COP-R-TOX

REGISTERED U.S. PATENT OFFICE

PENETRATING LIQUID COPPER

PROTECTS AGAINST

WOOD ROT : TERMITES : FUNGUS

FOR MARINE USE

Copper Content Meets Requirements of
Military Spec. 906-B and Navy Spec. 52-W-5-A

CAUTION!

HARMFUL OR FATAL IF SWALLOWED
KEEP OUT OF REACH OF CHILDREN

ACCEPTED

See other cautions on back panel

JUL 21 1971

UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGISTRATION
ED UNDER NO. 1719-2

MOBILE PAINT MANUFACTURING COMPANY
MOBILE, ALABAMA

ONE GALLON

1719-2

7-21-1971

11