

**PRECAUTIONARY STATEMENTS
CONTAINS PETROLEUM
DISTILLATES**

**HAZARD TO HUMANS AND
DOMESTIC ANIMALS. CAUTION!**

May be harmful or fatal if inhaled or swallowed. Avoid breathing of vapors or spray mist. Avoid contact with skin, eyes, or clothing. Wash thoroughly with soap and water after handling.

**STATEMENT OF PRACTICAL
TREATMENT**

In case of contact with skin or eyes, flush with plenty of water. Get medical attention if irritation persists. If inhaled, remove victim to fresh air. Get medical attention. If swallowed, do not induce vomiting. Get medical attention immediately.

ENVIRONMENTAL HAZARD

Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL AND CHEMICAL HAZARD

Combustible. Keep away from heat and open flame.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

**COP-R-TOX FOR PROTECTION
OF WOOD**

COP-R-TOX soaks into wood pores giving long lasting protection against smittes and rot-causing fungus, mildew and mold. Its lack of water solubility adds its waterproofing qualities. The formula of COP-R-TOX was tested in the Tropics by U.S. Government Agencies and found to be highly effective.

**COP-R-TOX FOR MARINE USE
CANVAS, WOOD, ROPES, NETS AND
SEINES, DIP OR SOAK UNTIL
THOROUGHLY WET.**

COP-R-TOX saturates the fiber protecting against rot, mildew and fungus.

Its waterproofing qualities add to its exceptional value in the preservation of these materials and to its long life and strength.

WOOD BOATS

COP-R-TOX affords protection against decay-causing fungus and mold in interior and exterior locations. It has particular utility in bilges and on surfaces to be painted. COP-R-TOX, when applied to bare wood which will be below the waterline, will give 30 to 60 days protection in the event that the anti-fouling exterior coat of paint is scraped off by contact with pilings or other surfaces.

DIRECTIONS

COP-R-TOX is a 20% copper naphthenate solution and each gallon may be thinned with one gallon of mineral thinner to produce a 10% copper naphthenate solution. COP-R-TOX may be applied by brushing freely, spraying or dipping in a tank. For lumber COP-R-TOX penetrates best and is most effective when wood is unpainted, dry and clean. COP-R-TOX may be painted over in 24 hours as it contains no creosote or tar products. A green cast may be noted in the first priming coat but this is not bleeding and should not show in subsequent topcoats of enamel. All wood in contact with the earth or secured to concrete slabs should receive two flowing coats by brushing or spraying or be dipped for at least five minutes. Other wood surfaces require only one coat. COP-R-TOX should be applied at the rate of 300 square feet per gallon.

**STORAGE AND
DISPOSAL**

PROHIBITIONS

Do not contaminate water, food, or feed by storage or disposal.

PESTICIDE STORAGE

Do not store near heat or open flame. Store in original container only. Close container after each use. Keep in a locked storage area, and out of reach of children.

PESTICIDE DISPOSAL

Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

EPA EST. 1719-AL-1
EPA REG. NO. 1719-2

ACCEPTED

SEP 15 1987

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. 1719-2



**BLP MOBILE
PAINTS**

COP-R-TOX

Wood Preservative

**PENETRATING LIQUID COPPER
PROTECTS AGAINST
WOOD ROT, TERMITES, FUNGUS
FOR MARINE USE**

ACCEPTED

74-1 SEP 15 1987

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. 1719-2

ACTIVE INGREDIENT

Copper Naphthenate 20.0%

(2.0% Copper as Metal)

INERT INGREDIENT 80.0%

Total 100.0%

REGISTERED U.S. PATENT OFFICE

KEEP OUT OF REACH OF CHILDREN

CAUTION

Harmful Or Fatal if Swallowed
SEE SIDE PANEL FOR ADDITIONAL
PRECAUTIONARY STATEMENTS