

ZIN-TOX

Clear Wood Preservative

ZIN-TOX preserves and protects all types of unpainted wood surfaces, lumber, timbers, fish nets, rope or twine.

Fish net, rope, or twine should be dipped in ZIN-TOX to thoroughly saturate the fibers.

ZIN-TOX may be applied by brushing freely, spray, or dipping in a tank or trough.

ZIN-TOX is most effective on unpainted, dry clean lumber as ZIN-TOX penetrates the pores and wood cells, filling them with Toxic Zinc, preventing Termites, Decay, Fungus, Mildew.

ZIN-TOX may be painted over in 24 hours as it contains no creosote or tar products.

All wood which is to come in contact with the earth should receive two flowing coats by brush or spraying or be dipped for at least 5 minutes for each inch of thickness. Other surfaces require only one coat.

ZIN-TOX covers 300 square feet per gallon, one coat.

CAUTION!

CONTAINS PETROLEUM
DISTILLATE

If swallowed, CALL PHYSICIAN IMMEDIATELY. COMBUSTIBLE. Keep away from heat and open flame. Avoid prolonged contact with skin and breathing of vapor or spray mist. Do not transfer contents to bottles or other unlabeled containers. Close container after each use.

DO NOT TAKE INTERNALLY.

USE WITH ADEQUATE
VENTILATION

KEEP OUT OF REACH OF
CHILDREN

USDA REG. NO. 1719-7



MOBILE PAINTS

ACCEPTED

June 4, 1977
BY THE FEDERAL REGISTER
OFFICE AND ROENTIGIDE ACT
ECONOMIC POISON REGISTER
UNDER NO. 1719-7 SUBJECT
ATTACHED COMMENTS.

1719-7

ACTIVE INGREDIENT

Zinc Naphthenate 16%

INERT INGREDIENT

Petroleum Distillate 84%

Total 100%

Zinc as metal 2%

BLP MOBILE ZIN-TOX

CLEAR WOOD PRESERVATIVE 74-2

PREVENTS

WOODROT: TERMITES: FUNGUS

CAUTION!

HARMFUL OR FATAL IF SWALLOWED
KEEP OUT OF REACH OF CHILDREN

See other cautions on side panel

MOBILE PAINT MANUFACTURING COMPANY
MOBILE, ALABAMA