



Jack Tar

ACTIVE INGREDIENTS
 Cuprous Oxide 37.8%
 (34.3% Copper As Metallic)
INERT INGREDIENTS 62.2%
TOTAL 100.0%
 Contains Petroleum Distillates

Marine Finishes

RECEIVED
 12 1982
 1719-12

V-I-P COLD PLASTIC
 ANTI-FOULING 473-71

KEEP OUT OF REACH OF CHILDREN

WARNING

Causes Eye Irritation. Harmful If Absorbed Through
 Skin. May Be Fatal If Swallowed or Inhaled.

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

MOBILE PAINT MFG. CO., INC. THEODORE, ALABAMA

BEST AVAILABLE COPY

PRECAUTIONARY STATEMENTS

CONTAINS XYLENE.

PHYSICAL AND CHEMICAL HAZARD.

Combustible. Keep away from heat and open flame.

HAZARD TO HUMANS AND DOMESTIC ANIMALS

WARNING! May be fatal if inhaled or swallowed. Do not breathe vapor or spray mist. Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and cap or hood. While spraying and/or sanding boat surfaces, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

STATEMENT OF PRACTICAL TREATMENT

In case of contact with the eyes, flush with plenty of water and get medical attention. In case of contact with the skin, wash with soap and water. Get medical attention if irritation persists. If product is inhaled, remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention. If product is swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

ENVIRONMENTAL HAZARD

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of debris in an approved landfill.

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling

This paint provides good resistance to fouling by barnacles and other salt water invertebrates on wood and steel boats. VIP Cold Plastic Anti-Fouling 473-71 is a traditional copper bottom paint containing bodied fish oil for a flexible film. It is suitable for anti-fouling protection on slower moving wooden vessels.

VIP Cold Plastic Anti-Fouling 473-71 may be applied by roller, brush, or spray techniques. It is very important to shake or stir thoroughly before each use to disperse any of the heavy copper pigment which may have settled. Use BLP Xylene 75-15 for clean-up and when necessary for thinning. One gallon covers approximately 200-250 square feet when applied in two coats. Allow a minimum of 4 hours dry time after each coat VIP Cold Plastic Anti-Fouling 473-71. It is preferable that the final coat be allowed to dry overnight before launching. Conditions of high humidity or low temperature increase this dry time.

INSTRUCTIONS FOR STEEL HULLS

REPAINT WORK: If the old coating is sound, clear the surface by scrubbing it free of all foreign matter. When dry, properly prepare and spot prime as indicated under New Work. Finish by applying two 2.0 mil coats of VIP Cold Plastic Anti-Fouling 473-71.

NEW WORK: Hull should be cleaned by scraping, wire brushing, or sandblasting to remove all rust and scale. Prime by applying 2 coats of Anti-Corrosive Primer 409-68 following directions on the can. Allow to dry overnight, then apply two 2.0 mil coats of VIP Cold Plastic Fouling 473-71.

INSTRUCTIONS FOR WOODEN HULLS

REPAINT WORK: Scrape clean and scrub with a stiff brush rinsing with high pressure water. Allow the surface to dry and apply two 2.0 mil coats of VIP Cold Plastic Anti-Fouling 473-71.

NEW WORK: Prime by applying 2 coats of Anti-Corrosive Primer 409-68 following directions on the can. Allow to dry overnight, then apply two 2.0 mil coats of VIP Cold Plastic Anti-Fouling 473-71.

STORAGE AND DISPOSAL

PROHIBITIONS

Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL

Pesticide, spray mixture, or clean up rinses that cannot be used according to label instructions must be disposed of according to Federal or approved state procedures under Subtitle C of the Resource Conservation and Recovery Act.

CONTAINER DISPOSAL

Triple rinse (or equivalent). Then puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

GENERAL

Consult federal, state, or local disposal authorities for approved alternative procedures. EPA EST. 1719-AL-1, EPA REG. NO. 1719-12

**NET CONTENTS
ONE GALLON
(3.79 LITERS)**