

BLP MOBILE PAINTS

ACTIVE INGREDIENT:	
Cadmium Oxide	68.1%
INERT INGREDIENTS	31.9%
TOTAL	100.0%



INYL ANTI-FOULING 473-73

CAUTION!

KEEP OUT OF REACH OF CHILDREN
HARMFUL OR FATAL IF SWALLOWED. FIF
IRRITANT. WARNING! FLAMMABLE. KEEP
AWAY FROM HEAT OR OPEN FLAME.

See back panel for additional cautions

MOBILE PAINT MFG CO., INC. MOBILE ALA 36688



Tar

Marine Finishes

INYL ANTI-FOULING 473-73

MOBILE PAINT MFG. CO. INC. MOBILE, ALABAMA

CAUTION!

KEEP OUT OF REACH OF CHILDREN
HARMFUL OR FATAL IF SWALLOWED. EYE
IRRITANT. WARNING! FLAMMABLE. KEEP
AWAY FROM HEAT OR OPEN FLAMES.

See back panel for additional cautions

Feb 26, 1974
UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGISTERED
EPA UNDER NO. 1719-24

one coat of BLP Jack Tar Wash Primer 409-72 following the directions on the can. Follow with four 1.5 mil coats of BLP Jack Tar Vinyl Red Lead Primer 409-71 and two 2.0 mils BLP Jack Tar Vinyl Anti-Fouling 473-73.

Wood: If old surface, scrape clean and hose off with high pressure water and stiff brush. Allow to dry completely. If new work or cleaned old surface, apply two 2.0 mil coats

BLP Jack Tar Wash Primer 409-72 followed by two 2.0 mil coats of BLP Jack Tar Vinyl Anti-Fouling 473-73.

Allow minimum of 4 hours dry time between all coats except Wash Primer and 4 hours after final coat of anti-fouling before launching. During conditions of high humidity or low temperature this dry time should be increased to a minimum of 8 hours.

CAUTION!

CONTAINS XYLOL AND METHYL ISOBUTYL KETONE

Avoid contact with eyes and breathing of vapor or spray mist. In case of contact with eyes, flood repeatedly with water. CALL PHYSICIAN IMMEDIATELY. Avoid prolonged contact with skin. Keep away from heat, sparks and open flame. Contact with flame or hot surfaces may produce toxic gases. Do not transfer contents to unlabeled containers. Close container after each use.

Harmful if swallowed. Do not reuse empty container. Destroy it by perforating or crushing. Bury or discard in a safe place away from water supply.

Do not contaminate water by cleaning of equipment, or disposal of wastes.

Use with adequate ventilation.

KEEP OUT OF REACH OF CHILDREN

XBOBIT

EPA REG. NO. 1719-24

