



MOBILE PAINTS

Jack Tar

ACTIVE INGREDIENTS
 Cuprous Oxide -----
 (50.4% Copper As Metal) -----
 INERT INGREDIENTS -----
 TOTAL ----- 100

100% Petroleum Distillates

1719.32

Marine Finishes

VINYL ANTI-FOULING
 FORMULA NO. 129 BLACK
 MII-P-15931D (SH)

KEEP OUT OF REACH OF CHILDREN

WARNING

Causes Eye Irritation. Harmful if Absorbed Through Skin. May be Fatal if Swallowed or Inhaled.

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

MOBILE PAINT MFG. CO. INC. THEODORE, ALABAMA

PRECAUTIONARY STATEMENTS ✓

CONTAINS XYLENE AND METHYL ISOBUTYL-KETONE.

PHYSICAL AND CHEMICAL HAZARD.

Flammable. Keep away from heat ✓ and open flame.

HAZARD TO HUMANS AND DOMESTIC ANIMALS. ✓

WARNING! May be fatal if inhaled or swallowed. Do not breathe vapor or spray mist. Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and cap or hood. While spraying and/or sanding boat surfaces, wear a mask or a respirator jointly approved by the ¹⁷¹⁹⁻³² Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

STATEMENT OF PRACTICAL TREATMENT

In case of contact with the eyes, flush with plenty of water and get medical attention. In case of contact with the skin, wash with soap and water. Get medical attention if irritation persists. If product is inhaled, remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention. If product is swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of waste. Do not allow chips and dust generated during paint removal to enter water. Dispose of debris in an approved landfill.

DIRECTIONS FOR USE

MILITARY OR COMMERCIAL USE ONLY. -- It is a violation of federal law to use this product in a manner inconsistent with its labeling. ✓

Formula No. 129 is intended for use on ship bottom exterior surfaces to resist fouling by barnacles and other salt water invertebrates. Use this product in accordance with Naval Ships Technical Manual Chapter 9190 or other approved specifications.

Always mix paint thoroughly before and during use. At least 15 minutes mixing time with a propeller type mechanical mixer is required before application. In cold weather store paint in a warm room 24 hours before use.

Paint may be applied by roller, brush, hot spray (temperature not to exceed 95°F) airless spray, or regular cold spray. Where thinning is necessary use Methyl Isobutyl Ketone

STORAGE AND DISPOSAL

PROHIBITIONS

Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL

Pesticide, spray mixture, or clean up rinses that cannot be used according to label instructions must be disposed of according to Federal or approved state procedures under Subtitle C of the Resource Conservation and Recovery Act.

CONTAINER DISPOSAL

Triple rinse (or equivalent).
Then puncture and dispose of in a
sanitary landfill or by other
approved state and local procedures.

GENERAL

Consult federal, state, or local
disposal authorities for approved
alternative procedures.

EPA EST. 1719-AL-1
EPA REG. NO. 1719-32