



CYANAMID

CYTOX® 3711 Industrial Microbiocide

(FOR CONTROL OF BACTERIA, YEASTS, AND FUNGI IN INDUSTRIAL WATER SYSTEMS)

DANGER!  **P O I S O N** 
KEEP OUT OF REACH OF CHILDREN
HARMFUL OR FATAL IF SWALLOWED OR ABSORBED THROUGH SKIN
CAUSES BURNS OF EYES AND SKIN

Do not get in eyes, on skin, on clothing; wear goggles and rubber gloves.
Avoid breathing vapor or mist.
Keep container closed.
Use with adequate ventilation.
Wash thoroughly after handling.
Do not store near food or feed.

FIRST AID

If swallowed, induce vomiting by sticking finger down throat or by giving soapy or strong salty water to drink. Repeat until vomit is clear. Call a physician. Never give anything by mouth to an unconscious person.

In case of contact, immediately remove contaminated clothing and shoes. Flush eyes or skin with plenty of water for at least 15 minutes. Call a physician. Wash clothing before reuse.

ACTIVE INGREDIENT:

Vinylene bithiocyanate

8%

INERT INGREDIENTS

92%

EPA Reg. No. 1730-19

L3889 R2 LN

PRINTED
IN
U.S.A.

Net Contents: 450 Pounds

AMERICAN CYANAMID COMPANY
INDUSTRIAL CHEMICALS AND PLASTICS DIVISION • WAYNE, NEW JERSEY 07470

DIRECTIONS FOR USE

PAPER MILLS: CYTOX® 3711 is added to the white-water system or to the stock furnish at a normal rate of 0.125 to 0.69 pounds per ton of paper. The exact dosage will depend upon operating conditions and extent of microbiologic contamination of the system. If slime buildup is heavy, addition is best made in periodic shock dosages such that the total required dosage is added within a two- to four-hour period. Otherwise, the microbiocide may be metered continuously into the system at the recommended dosage.

SOLUTIONS AND EMULSIONS: For the preservation of solutions, emulsions, adhesives, and other liquid products, the addition of 125 parts per million of CYTOX® 3711 based on total weight of the product is effective. Do not use in products of this type that are intended for the manufacture of food-packaging materials.

SECONDARY OIL RECOVERY: For control of sulfate-reducing bacteria and other microorganisms in water used for secondary oil recovery or subsurface injection, 1.6 to 10 fluid ounces of CYTOX® 3711 per 1000 gallons of water (12.5 to 80 parts of product per million parts of water) as a slug treatment once or twice per day is effective.

This product is toxic to wildlife. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label.

DRUM DISPOSAL: Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

CORRO

DIRECTIONS FOR USE

PAPER MILLS: CYTOX® 3711 is added to the white-water system or to the stock furnish at a normal rate of 0.125 to 0.69 pounds per ton of paper. The exact dosage will depend upon operating conditions and extent of microbiologic contamination of the system. If slime buildup is heavy, addition is best made in periodic shock dosages such that the total required dosage is added within a two- to four-hour period. Otherwise, the microbiocide may be metered continuously into the system at the recommended dosage.

SOLUTIONS AND EMULSIONS: For the preservation of solutions, emulsions, adhesives, and other liquid products, the addition of 125 parts per million of CYTOX® 3711 based on total weight of the product is effective. Do not use in products of this type that are intended for the manufacture of food-packaging materials.

SECONDARY OIL RECOVERY: For control of sulfate-reducing bacteria and other microorganisms in water used for secondary oil recovery or subsurface injection, 1.6 to 10 fluid ounces of CYTOX® 3711 per 1000 gallons of water (12.5 to 80 parts of product per million parts of water) as a slug treatment once or twice per day is effective.

This product is toxic to wildlife. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label.

DRUM DISPOSAL: Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.



CORROSIVE LIQUID, N. O. S.