

DIRECTIONS

WOOD PRESERVATION

Before treatment, all wood should be normally dry. All surface dirt should be removed to the extent of any visible evidence of decay. For best results, PENTA ROOD PRESERVATIVE should be applied so as to effect maximum

penetration into the wood and maximum absorption at joints and ends. Complete immersion, where possible, in an open tank is the best procedure for accomplishing this. At least five minutes immersion for each inch of thickness is recommended for all cases. Where wood will be in direct contact with the ground, such as in the case of fence posts, the immersion period should be from 12-48 hours, and the posts should be peeled of bark, dry and well seasoned. Where the immersion treatment is impractical, heavy brush application may be used. Where the wood will be in direct contact with the ground, several brush applications should be given. Estimated coverage: 1 to 2 gallons per 1000 board feet for open tank treatment; 200 square feet per gallon for brush application.

NOTICE-Neither the manufacturer nor the seller makes any representation or warranty, express or implied, concerning this material, except that it is of the manufacturers standard quality. Neither shall be held responsible in any manner for any personal injury or property damage, or other type of loss resulting from the handling, storage or use of this material. The buyer assumes and uses this material on the conditions.

PENTACHLOR

P-5

PENTA

WOOD PRESERVATIVE

U.S.D.A. REG. NO. 1748-18

CAUTION: KEEP OUT OF REACH OF CHILDREN!

ASSAY

ACTIVE INGREDIENTS:

- *Pentachlorophenol..... 4.65%
- *Other Chlorophenols and Related Compounds..... 0.65%
- Petroleum Solvents..... 95.00%
- *5% Technical Pentachlorophenol as defined in Fed. Spec TT-W-570.

See side panels for Directions and other warning statement.

Net Contents _____ Gal./s

YORK CHEMICAL CO., INC.

195 Atlantic Avenue

Garden City Park, New York 11044

APPLICATIONS

WOOD PRESERVATION

Clear out completely all loose soil and debris under or around infested buildings. Spray all ground under buildings, at rate of 1 gallon of PENTA ROOD PRESERVATIVE per 10 square feet of area to be treated. Break all wood-to-earth contacts, such as steps, door frames, etc. and replace with PENTA treated wood or concrete. Where construction permits, dig a trench around all foundations to a depth of 12 to 18 inches and apply 1 gallon of PENTA per 2 lineal feet. For buildings with deep foundations, trench 30 inches deep, and for base of foundation, apply 1 gallon of PENTA per foot of trench as backfill is added. Trees, shrubs or flowers should be protected from soil of trench by covering paper.

WARNING

Extremely irritating on absorbed through skin. Causes skin irritation. Do not breathe vapor, fumes or spray mist. Do not get in eyes or on skin. If in eyes, wash thoroughly. Do not use on food or feed of any kind.

100-100000

SEP 6 1967

RECEIVED
FOR RECORD
FEDERAL BUREAU OF INVESTIGATION
U.S. DEPARTMENT OF JUSTICE