

## DIRECTIONS

Cooling Towers - Evaporative Condensers

**Initial Dose:** When the system is noticeably fouled apply a dose of 14-28 fluid ounces product per 1000 gallons of contained water (125-250 ppm). Repeat daily as needed until control is obtained.

**Subsequent Dose:** Once the bulk of the growths are eliminated, or where the system is already under control, apply 2.2 to 4.4 fluid ounces product per 1000 gallons of contained water (20-40 ppm) daily, weekly, or as needed to maintain the system in excellent condition.

Badly fouled systems must be precleaned before treatment is begun. This product is inactivated in the presence of chlorine residuals at or above 10 ppm.

## FEEDING

Biosperse<sup>®</sup> 209 may be drip fed continuously from the drum or fed by any suitable chemical feed system. For slug feeding in cooling towers or evaporative condensers, it may be added directly into the sump or at any other convenient location where good distribution can be assured.

## HANDLING

This product is a toxic material. Causes skin or eye irritation. Harmful if swallowed. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. Do not take internally. In case of swallowing call a physician.

## ENVIRONMENTAL CAUTION

This product is toxic to fish and wildlife. Treated effluent should not be discharged where it will drain into lakes, streams, ponds or public water. Apply this product only as specified on the label.

# BIOCIDIDE 20

## FOR CONTROL OF BACTERIA AND FU

### FOR INDUSTRIAL USE ONLY

#### ACTIVE INGREDIENTS:

|  |               |
|--|---------------|
| Sodium 2, 4, 5 - Trichlorophenate . . . . .              | 15.06%        |
| Sodium Pentachlorophenate . . . . .                      | 11.06%        |
| Isopropanol . . . . .                                    | 10.00%        |
| Nabam (Disodium Ethylene<br>Bisdithiocarbamate . . . . . | 7.45%         |
| Other Sodium Chlorophenates . . . . .                    | 1.54%         |
| <b>INERT INGREDIENTS*</b> . . . . .                      | <b>54.89%</b> |

\* Includes solubilizing and dispersing agents.

This product helps control slime growths in paper mills, cooling towers and similar recirculating water systems. It should be added directly to the water at a dosage of 50-200 ppm of product, depending upon the system being treated. Do not discharge wastes directly into fish-bearing waters. Biocide 207 is an approved product for use in the manufacture of paper for food packaging. For application times, methods, intervals, specific treatment programs, or where critical results are essential, consult your Drew Service Engineer.

Biocide 207 is a  
Harmful if swallowed  
on clothing. Wash  
Do not take into  
vomiting by admin-  
emetic. Call a p

**Keep C**

USDA Reg. No. 1757-25

1874-68

**DREW CHEMICAL CORPORATION**  
POWER CHEMICALS DIVISION  
New York, N. Y. • Boonton, N. J.

# BIOCIDE 207

## CONTROL OF BACTERIA AND FUNGI

ACCEPTED  
JUL 19 1968  
UNDER THE FEDERAL INSECTICIDE  
FUNGICIDE AND ROBOTICIDE ACT  
FOR ECONOMIC POISON REGISTERED  
UNDER NO. 1757-25

### FOR INDUSTRIAL USE ONLY

This product helps control slime growths in paper mills, cooling towers and similar recirculating water systems. It should be added directly to the water at a dosage of 50-200 ppm of product, depending upon the system being treated. Do not discharge wastes directly into fish-bearing waters. Biocide 207 is an approved product for use in the manufacture of paper for food packaging. For application times, methods, intervals, specific treatment programs, or where critical results are essential, consult your Drew Service Engineer.

**DREW CHEMICAL CORPORATION**  
POWER CHEMICALS DIVISION  
New York, N. Y. • Boonton, N. J.

### WARNING

Biocide 207 is a toxic material. Causes skin irritation. Harmful if swallowed. Do not get in eyes, on skin or on clothing. Wash thoroughly after handling.

Do not take internally. In case of swallowing, induce vomiting by administering warm salt water or other emetic. Call a physician.

**Keep Out of Reach of Children**

Contents - 55 Gallons  
See Markings on Top of Drum  
For Net Weight

15.06%  
11.06%  
10.00%  
  
7.45%  
1.54%  
54.89%