

Net Contents Gallons

AMPICIDE 5

ACTIVE INGREDIENT: Poly [oxyethylene (dimethyliminio) ethylene (dimethyliminio) ethylene dichloride].

INERT INGREDIENT: Water by weight

5%
95%

100%

Weight per gallon 8.4 lbs.
Weight of active ingredient 0.42 lbs./gal.

CAUTION

KEEP OUT OF THE REACH OF CHILDREN

Harmful if swallowed. Avoid contact with skin and eyes. In case of contact, flush with plenty of water for at least 15 minutes. If eye irritation persists get medical attention. Avoid contamination of food.

This product is toxic to fish. Do not add treated effluent to lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of waste. Use only as directed on label.

Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place. Destroy small containers by perforating or crushing then bury or discard in a safe place.

DIRECTIONS

AMPICIDE 5 is used to control algae, bacteria and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, micro-biological slime and other deposits. An initial slug addition of 12 to 30 fluid ounces of AMPICIDE 5 per 1,000 gallons of water, to provide 95 to 237 parts per million of AMPICIDE 5 based on the total weight of water in the system is recommended. Repeat if necessary until control is evident. Subsequent slug additions of 3 to 30 fluid ounces of AMPICIDE 5 per 1,000 gallons of water (24 to 237 parts per million) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleed-off and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

Manufactured By

AMPION CORPORATION

4-88 47th Avenue

Long Island City, New York 11101

EPA Reg. No. 1760-24

1760-24

1760-24