

PRECAUTIONARY STATEMENTS

WARNING!

Hazardous to Humans and Domestic Animals

Do not breathe vapor, fumes or spray mist. Do not get in eyes. Pentachlorophenol is irritating to the skin and should be handled with heavy oil resistant rubber gloves. If spilled on hands or clothing remove clothing at once and wash skin thoroughly with strong soap suds. Do not allow livestock to contact freshly treated posts or lumber. Do not paint or spray near a flame. Harmful or fatal if swallowed, inhaled, or absorbed through the skin. Induce vomiting by administering an emetic of mustard and water. Call a physician immediately.

Harmful if absorbed through skin. Do not get in eyes, on skin, or on clothing. Wear rubber gloves when handling freshly treated lumber.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL OR CHEMICAL HAZARDS

Do not use, pour, spill or store near heat or open flame.

STORAGE AND DISPOSAL

Do not reuse empty container (bottle, can, bucket). Wrap container and put in trash collection.



**TRIANGLE PENTACHLOROPHENOL 10:1
CONCENTRATED WOOD PRESERVATIVE**

ACTIVE INGREDIENTS:

Pentachlorophenol	38.72%
Other Chlorophenols	4.50%
Petroleum Hydrocarbons	38.66%
INERT INGREDIENTS	18.12%

For Controlling Decay of Wood. For Termite Control.

KEEP OUT OF REACH OF CHILDREN

WARNING!

SEE SIDE PANEL FOR
ADDITIONAL PRECAUTIONARY STATEMENTS

ACCEPTED
MAY 8 1982
1842-34

Mfg. By
TRIANGLE CHEMICAL
Macon, Georgia

EPA Reg. No. 1842-34
EPA Est. No. 1842 Ga 1

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Add 1 gallon of Triangle 10:1 concentrate to 10 gallons of fuel oil, kerosene or mineral spirits. The resulting product contains approximately 5% chlorophenols by weight.

If surface is to be painted mineral spirits is to be preferred because it dries quicker. Timber should be dry. If necessary to cut wood after treatment, swab the cut surfaces thoroughly.

FOR TREATING FENCE POSTS dilute 5 gallons of 10:1 concentrate in an open barrel with 50 gallons of fuel oil. Mix well. Fill another barrel with peeled and seasoned posts and pour in diluted preservative until barrel is full. Soak 24 hours, then turn posts end for end and soak another 24 hours. The posts may be set out any time thereafter.

FOR TERMITES ALREADY IN BUILDING locate and destroy tunnels. Replace badly damaged wood with new treated pieces. Exposed wood should be soaked with preservative by brush or spray, applying generously to joints and cracks.

LUMBER, SASH, FRAMES. Spray, brush or dip (at least 3 minutes for each inch of thickness) with diluted preservative. If surface is to be painted or is sheltered from weather a single treatment is sufficient. Otherwise apply two or more coats as the more penetration the better the protection. Wood which is to be used in contact with the ground or exposed to severe moisture should be soaked thoroughly.

WARRANTY STATEMENT

Seller warrants that this product conforms to its chemical description and is reasonably fit for the purpose stated on the label when used in accordance with directions under normal conditions of use, but neither this warranty nor any other warranty of merchantability or fitness for a particular purpose, expressed or implied, extends to the use of this product contrary to label instructions, or under abnormal conditions, or under conditions not reasonably foreseeable to the seller, and buyer assumes the risk of any such use.