

**TERMITE CONTROL: SPECIFIC DIRECTIONS FOR COMMERCIAL OPERATORS**

To control termites add 1 gallon Triangle Heptachlor-3 Emulsible Concentrate (3 lbs. per gal.) to 71 gallons of water (0.5% Emulsion). Apply the resulting emulsion at the following rates:

**(A) Buildings with crawl spaces**

(1) Apply 2 gallons per 5 linear feet to critical areas only under the house, such as along the outside of foundation walls, around piers, sewer pipes, conduits, etc. Trench according to directions in part (2) below.

(2) Along the outside of foundation walls, dig a narrow trench, such trench to be dug no deeper than the top of the footings. If the trench is less than 15 inches in depth to the top of the footings, apply 1 gallon per 5 linear feet. Replace the soil and apply another 1 gallon per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. If the trench is more than 15 inches in depth to the top of the footings, apply 2 gallons per 5 linear feet. Replace the soil and apply another 2 gallons per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. A trench 30 inches deep is a maximum depth required alongside those foundations where the top of the footings is greater than 30 inches deep. In lieu of trenching to a 30" depth, make the trench 12 to 15" deep and rod to footing, spacing the holes about 1 foot apart.

(3) Apply 1 gallon per 10 square feet of soil surface under porches, entrance platforms, utility entrances, and similar situations where slab or fill is at the grade level. Where crawl spaces exist, treat as described in part (1) above.

(4) Treat all voids in hollow masonry units of the foundation at the rate of at least 1 gallon per 5 linear feet of wall. It is best to apply the chemical near the footing.

**(B) Buildings With Concrete Slab on the Ground—(Pre-Construction)**

(1) Apply 1 gallon per 10 square feet as an over-all treatment under the slab as well as under attached porches, entrance platforms, utility entrances and similar situations where slab or fill is at grade level. In case of washed gravel, cinders, or similar coarse material, increase the dosage by at least one-half.

(2) Apply 2 gallons per 5 linear feet to critical areas only under the slab, such as along the inside of foundation walls, around sewer pipes, conduits, etc. Trench as in part (3) below.

(3) Along the outside of foundation walls, dig a narrow trench no deeper than the top of the footings, but no deeper than 15 inches, unless the footing is much deeper in some places on account of the slope of the land, then treat as under (A) (2).

(4) Treat all voids in hollow masonry units of the foundation at the rate of at least 1 gallon per 5 linear feet of wall. It is best to apply the chemical near the footings.

**(C) Buildings With Basements**

(1) Apply 1 gallon per 10 square feet as an over-all treatment under the basement flooring as well as under attached porches, entrance platforms, utility entrances, and similar situations where slab fill is at the grade level. In case of washed gravel, cinders, or similar coarse material, increase the dosage by at least one-half. Where crawl spaces exist, treat as described in part (2) below.

*Buildings (PCO) Termites*

# HEPTACHLOR-3 E. C. For Termite Control

ACTIVE INGREDIENTS:	By Weight
Heptachlor*	35.0%
Related Compounds	13.7%
Petroleum Hydrocarbons	46.3%
INERT INGREDIENTS	5.0%
	<hr/> 100.0%

\*HEPTACHLOR-3 EMULSIBLE CONCENTRATE  
\*Heptachlorotetrahydro -4,7-methanoindene

**WARNING:** Keep out or reach of children.

### GENERAL DIRECTIONS

Triangle Heptachlor-3 Emulsible Concentrate (3 lbs. actual per gal.) can be used in conventional hydraulic sprayers.

### Mixing Directions

Mix Triangle Heptachlor Emulsible Concentrate with water by agitation; agitate the mixture while spraying. If allowed to stand, reagituate before use.

**CAUTION**

Do not reuse container. Destroy when empty.

MANUFACTURED BY

ACCEPT **Triangle Chemical Co.**

MACON, GEORGIA

*6-4-68*

Net Contents Gal.

*1842-183 ←*

(2) Apply 2 gallons per 5 linear feet to critical areas only under the basement flooring, as well as porches and entrances having crawl spaces, such as along the inside of foundation walls, around sewer pipes, conduits, piers, etc. Trench according to directions in part (3) below.

(3) Along the outside of foundation walls, dig a narrow trench, such trench to be dug no deeper than the top of the footings. If the trench is less than 15 inches in depth to the top of the footings, apply 1 gallon per 5 linear feet. Replace the soil and apply another 1 gallon per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. If the trench is more than 15 inches in depth to the top of the footings, apply 2 gallons per 5 linear feet. Replace the soil and apply another 2 gallons per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. A trench 30 inches deep is a maximum depth required alongside foundations where the top of the footings is greater than 30 inches deep. In lieu of trenching to a 30" depth, make the trench 12 to 15" deep and rod to footing, spacing the holes about 1 foot apart.

(4) Treat all voids in hollow masonry units of the foundation at the rate of at least 1 gallon per 5 linear feet of wall. It is best to apply the chemical near the footing.

### WARNING

May be fatal if swallowed. Do not breathe vapor or dust. Do not get on skin. In case of contact, immediately remove contaminated clothing and flush skin or eyes with plenty of water; for eyes get medical attention. Wash thoroughly with soap and water after handling and before eating or smoking. Wear clear clothing. During commercial or prolonged exposure in mixing operations wear clean synthetic rubber gloves and a mask or respirator passed by the U. S. Dept. of Agriculture for

Heptachlor protection. Do not apply or allow to drift to areas occupied by unprotected humans. Do not contaminate feed or food stuffs.

Highly toxic to fish and wildlife. Do not contaminate any body of water nor apply when conditions favor drift from the area.

### Notice Of Warranty

Seller warrants that this product conforms to its chemical description and is reasonably fit for the purpose stated on the label when used in accordance with directions under normal conditions of use, but neither this warranty nor any other warranty of merchantability or fitness for a particular purpose, expressed or implied, extends to the use of this product contrary to label instructions, or under abnormal conditions, or under conditions not reasonably foreseeable to the seller, and buyer assumes the risk of any such use.