

LEAST

- WATER REPELLENT
- KILLS TERMITES
- STOPS ROT & STAIN

ACTIVE INGREDIENTS—
 Chlorane Tech, **1%, Pentachlorophenol *5%, Petroleum Distillates 84% .. 90%
 MERT INOR ~~Water-Soluble~~ 10%
 *As determined by Federal Specifications TT-W-570 Total 100%
 **Octachloro-4, 7-methane-tetrahydroindane .6%, related compounds .4%
 Lumber Last complies with Federal Specifications TT-W-572

CAUTION

KEEP OUT OF REACH OF CHILDREN
 HARMFUL OR FATAL IF SWALLOWED

see additional warnings on back panel

Elco MANUFACTURING COMPANY
 PITTSBURGH, PENNSYLVANIA

Considerable savings can be effected with the use of ELGO CHLOR-DIEL for this purpose. Detailed and easy-to-follow instructions are included with ELGO CHLOR-DIEL which can be obtained from your LUMBER LAST DEALER.

LUMBER LAST
 COLD SOAP
 on amount of
 COLD SOAP
 of thickness
 beard feet
 rough 'vat'
 tion Timber
 whether use
 purpose. Pe
 BRUSHING:
 1000 beard
 brushed lib
 SPRAYING:
 spray bound
 IMPORTANT
 BEFORE P
 dry. Drying
 ditions. Mi
 primers, ha
 take).
 SHINGLE T
 odd color g

TERMITE
 trolling ter
 step.

Harmful if
 vapor, fume
 oughly with
 using. Avoi
 should be t

ANTIDOTE
 raw egg w
 spoonful of

1941-20