

DIRECTIONS

Read Directions and Precautions carefully before use.

Drains, Drain Lines, Line to Sewers: Initially, for clogged and sluggish lines dilute four ounces of Elcocene with one quart of water and pour into drains. Repeat until lines are free flowing. Apply in evening when system is inactive, and Elcocene can remain undisturbed in the clogged facility for a minimum of 2 hours or preferably overnight. In multiple story buildings treat the lowest floor first until lines are free flowing; then continue upward allowing sufficient time to clear out lower lines. For preventive maintenance use two ounces per quart of water weekly, bi-weekly or as necessary to keep facilities flowing.

Grease Traps and Catch Basins: Clean trap of accumulated grease - then regular Elcocene treatment will keep the trap odor-free and grease-free and eliminate costly manual cleanouts. Add 1 ounce of Elcocene per quart of water for each 20 gallon of tank capacity.

Septic Tanks, Cesspools, Dry Wells, Drain Fields: Pour $\frac{1}{2}$ pint Elcocene into toilet bowl and flush, pour $\frac{1}{2}$ pint into kitchen drain. Wait 15 minutes to give Elcocene time to work, then add two quarts of water. Repeat treatment next day. If tank is accessible, dilute one pint Elcocene to one gallon of water and pour into tank. One pint of Elcocene is recommended for each 500 gallon of tank capacity. For preventive maintenance pour 1 to 2 ounces into kitchen sink and toilet bowl weekly.

Sluggish Drains in Sink, Wash Bowl, Tub: Pour 2 ounces of Elcocene into each drain. After 15 minutes add one quart of water.

Odor Control-Sanitary Maintenance: Spray, or mop a dilution of 1 or 2 ounces of Elcocene per gallon of water over odorous areas. Use also for refuse cans. In lavatories, mop floors and walls with 2 ounces of Elcocene per gallon of water and then pour balance of diluted material into urinals and toilets.

Chemical Toilets: Start Tanks with 1 quart of Elcocene per 100 gallons of water. Maintain concentration by adding 1 pint of Elcocene for each 50 gallon increase in volume.

Trailer and Airplane Toilets: Mix one tablespoon of Elcocene in two quarts of water and pour into toilet. Repeat after each disposal of waste.

Pit Privies: Apply 1 ounce of Elcocene per square foot in water sufficient to cover surface.

Drain Flies: Since grease and slime in sewers is the breeding place of the maggots, by removing the breeding areas, the flies will be diminished. Also the orthodichlorobenzene is a toxicant for drain flies. Treat in the evening when the utilities are no longer in use. Pour $\frac{1}{2}$ pint of Elcocene into toilet bowl and flush. Then pour $\frac{1}{2}$ pint of Elcocene into each drain and sewer opening followed by 1 quart of water. If necessary retreat. If the vent openings are accessible, pure Elcocene (about 1 pint) should be poured into each one. A tablespoonful of Elcocene should be placed in the lip of each sewer opening. Under basement shower stalls, muck frequently accumulates. This area should be treated with $\frac{1}{2}$ pint of Elcocene mixed into a quart of water.

Pine Scented

ELCOOCENE

for Septic Tanks, Drains
Cesspools, Greasetraps
Catchbasins, Drainflies

KILLS DRAINFLIES

KILLS ODORS

CLEANS SEWAGE SYSTEMS

WARNING

Keep out of reach of children.

See side panel for additional precautions

ACTIVE INGREDIENTS: 90%

Coal Tar Neutral Oil, Orthodichlorobenzene, Soap, Coal Tar Acids, Isopropanol, Pine Oil.

INERT INGREDIENTS:

Water. 10%

Contents: 1 Quart

ELCO MANUFACTURING CO.

PITTSBURGH PA

Odor Control: Controls malodors in septic tanks and odor producing by

Grease Solvent: Dissolves grease lines, grease traps, and catch backup in septic tanks and cesspools, slime buildup.

Drain Flies: Kills Drain Flies, Ground.

Keep out of reach of children

Caution: May be absorbed through skin. Eye and skin irritation. Avoid ventilation. Avoid contact with eyes. Irritating to eye system. Do not use on clothing. May stain. Wash thoroughly if on skin.

ANTIDOTE:

EXTERNAL: Wash thoroughly with soap and water.

INTERNAL: Give emetic (if conscious, 1% soap solution), or administer coffee or milk. Warm cover and rest are essential.

Elcocene is a solvent. If spilled, wash promptly with large amount of water.

ACCEPTED
10/4/68
UNDER THE FEDERAL INSECTICIDE ACT
FUNGICIDE AND RODENTICIDE ACT
FOR USE AS A PUBLIC POISON REGISTERED
UNDER NO. 1941-5
TO ATTACHED COMMENTS.
1941-5

Pine Scented

ELCOCENE

for Septic Tanks, Drains
Cesspools, Greasetraps
Catchbasins, Drainflies

KILLS DRAINFLIES
KILLS ODORS
CLEANS SEWAGE SYSTEMS

WARNING

Keep out of reach of children.

See side panel for additional precautions:

ACTIVE INGREDIENTS: 90%

Coal Tar Neutral Oil, Orthodichlorobenzene, Soap, Coal
Tar Acids, Isopropanol, Pine Oil.

INERT INGREDIENTS:

Water. 10%

Contents: 1 Quart

ELCO MANUFACTURING CO

PITTSBURGH PA

Odor Control: Controls melodors coming from drains, grease traps, septic tanks and odor producing bacteria.

Grease Solvent: Dissolves grease and slime deposits in drain lines, grease traps, and catch basins. Prevents clogging and backup in septic tanks and cesspools, caused by thick grease and slime buildup.

Drain Flies: Kills Drain Flies, Maggots, and Destroys Breeding Ground.

Keep out of reach of children.

Caution: May be fatal if swallowed or absorbed through skin. Vapor harmful. Eye and skin irritant. Use with adequate ventilation. Avoid breathing of vapors. Irritating to eyes and upper respiratory system. Do not get in eyes, on skin or on clothing. May produce severe burns. Wash thoroughly after handling.

ANTIDOTE

EXTERNAL: Wash thoroughly with soap and water.

INTERNAL: Give emetics (mustard of soap solution), olive oil, cathartics, administer coffee, and administer oxygen. Warm covering, fresh air, and rest are essential. CALL PHYSICIAN.

Elcocene is a solvent for plastics, paints, rubber, and linoleum. If spilled, wash promptly with a large amount of water to minimize damage.

ACCEPTED
10/4/68
UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR LOCAL TOXIC POISON REGIST
EPA HANDLER NO. 1941-31
TO ATTACHED COMMENTS.
1941-31

USDA REG. # 1941-31