

ACCEPTED
4/24/66
1941-66

ELCO

TERMITE KILLER

EMULSIFIABLE CONCENTRATE

ACTIVE INGREDIENTS:	
Technical Chlordane	45.3%
Petroleum Distillate	49.7%
INERT INGREDIENTS	
	5.0%
TOTAL 100.0%	

Equivalent to 27.2% Octachloro-4,7-methanotetrahydroindane and 18.1% related compounds.

Contains 4.0 lbs. actual Chlordane per gallon

Net Contents: 1 Gallon

WARNING
Keep Out of Reach of Children

See left panel for antidote and additional warning statements

MANUFACTURED BY

ELCO MANUFACTURING CO.
PITTSBURGH, PA. 15215

WARNING

Harmful if swallowed. Contact with skin can cause toxic symptoms. Avoid breathing vapors or spray mist. In case of contact with skin, wash with soap and water. Avoid contamination of feed and foodstuffs. Keep out of the reach of children. Keep out of any body of water. Toxic to fish and wildlife. Do not use in any manner not specified on this label.

ANTIDOTE

EXTERNAL—In case of spillage on skin wash promptly with soap and water.
INTERNAL—Emetic of 1 tablespoonful mustard in tumbler of water. Call a physician.

CONTAINER DISPOSAL

Rinse equipment and containers and dispose of wastes by burying in non-crop lands away from water supplies. Containers should be disposed of by punching holes in them and burying with wastes, or by burning. Keep out of smoke.

Premises treated with 1.0% Elco Termite Killer will give residual control for a minimum of five years.

USDA REG.# 1941-66

Add 1 gallon of **TERMITE KILLER** emulsifiable concentrate to 99 gallons of water. Apply the 1.0% emulsion of

- 1 - SLAB-TYPE CONSTRUCTION**
 - a- Apply 1 gallon per 10 square feet as an overall pre-construction treatment under the slab and along attached porches or entrance platforms.
 - b- Apply 2 gallons per 5 lineal feet to critical areas under the slab as pre-construction treatment, such as along the inside of the foundation walls and around utility entrances and interior partition foundation walls.
- 2 - BUILDINGS WITH CRAWL SPACES**
 - a- Apply 2 gallons per 5 lineal feet in a trench along the outside of foundation walls, including entrance platforms and porches where the foundation is not more than 15-18 inches deep. If over 15-18 inches deep but not over 30 inches, apply 4 gallons per 5 lineal feet. Do not go deeper than the top of the footing.
 - b- Apply 2 gallons per 5 lineal feet as a trenching application to critical areas under the house, such as along the inside of foundation walls and around piers and utility entrances. If trench is deeper than 15-18 inches but not over 30 inches apply 4 gallons per 5 lineal feet. Do not go deeper than the top of the footing.
 - c- Apply 1 gallon per 10 square feet of soil surface as a pre-construction treatment where the attached porches, entrance platforms, utility entrances have covering slab on fill of ground.

a- Apply in hole
b- Apply pre-construction treatment
c- Apply along ing en found If over apply deeper
d- Apply applic such porch deep inches go de
e- Treat found feet o
Note: trench level of

ACCEPTED

4/29/71

1941-66

ELCO

TERMITE KILLER

EMULSIFIABLE CONCENTRATE

ACTIVE INGREDIENTS:

Technical Chlordane 45.3%

Petroleum Distillate 49.7%

INERT INGREDIENTS 5.0%

TOTAL 100.0%

Equivalent to 27.2% Octachloro-4,7-methanotetrahydroindane and 18.1% related compounds.

Contains 4.0 lbs. actual Chlordane per gallon

Net Contents: 1 Gallon

WARNING

Keep Out of Reach of Children

See left panel for antidote and additional warning statements

MANUFACTURED BY

ELCO MANUFACTURING CO.
PITTSBURGH, PA. 15215

Add 1 gallon of

TERMITE CONTROL

Elco Termite Killer emulsifiable to 48 gallons of water (1.0% emulsion).
Apply the 1.0% emulsion as follows.

1 - SLAB-TYPE CONSTRUCTION

a- Apply 1 gallon per 10 square feet as an overall pre-construction treatment under the slab and along attached porches or entrance platforms.

b- Apply 2 gallons per 5 lineal feet to critical areas under the slab as pre-construction treatment, such as along the inside of the foundation walls and around utility entrances and interior partition foundation walls.

2 - BUILDING WITH CRAWL SPACES

a- Apply 2 gallons per 5 lineal feet in a trench along the outside of foundation walls, including entrance platforms and porches where the foundation is not more than 15-18 inches deep. If over 15-18 inches deep but not over 30 inches, apply 4 gallons per 5 lineal feet. Do not go deeper than the top of the footing.

b- Apply 2 gallons per 5 lineal feet as a trenching application to critical areas under the house, such as along the inside of foundation walls and around piers and utility entrances. If trench is deeper than 15-18 inches but not over 30 inches apply 4 gallons per 5 lineal feet. Do not go deeper than the top of the footing.

c- Apply 1 gallon per 10 square feet of soil surface as a pre-construction treatment where the attached porches, entrance platforms, utility entrances have covering slab on fill of ground.

d- Apply 1 gallon per 5 lineal feet of wall to voids in hollow masonry units of the foundation.

3 - BUILDINGS WITH BASEMENTS

a- Apply 1 gallon per 10 square feet as an overall pre-construction treatment under the basement flooring, attached porches, entrance platforms, utility entrances and similar situations where slab fill is at ground level.

b- Apply 2 gallons per 5 lineal feet in a trench along the outside of foundation walls, including entrance platforms and porches where the foundation is not more than 15-18 inches deep. If over 15-18 inches deep but not over 30 inches, apply 4 gallons per 5 lineal feet. Do not go deeper than the top of the footing.

c- Apply 2 gallons per 5 lineal feet as a trenching application to critical areas under the house such as along the inside of foundation walls, porches, entrances and piers. If trench is deeper than 15-18 inches but not over 30 inches, apply 4 gallons per 5 lineal feet. Do not go deeper than the top of the footing.

d- Treat all voids in hollow masonry units of the foundation at the rate of 1 gallon per 5 lineal feet of wall.

Note: For buildings with deep footings, dig trench 30 inches deep. Do not dig trench below level of footing.