Vancide*

ACTIVE INGREDIENTS:

30.0%

SODIUM DIMETHYLDITHIOCARBAMATE 27.6% SODIUM 2-MERCAPTOBENZOTHIAZOLE 2.4% INERT INGREDIENTS:

70.0% 100.0%

This product is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or KEEP OUT OF REACH OF CHILDREN other waters unless in accordance with the requirements of a STATEMENT OF PRACTICAL TREATMENT

If swallowed: Call a physician or Poison Control Center, Drink 1 or 2 glasses of water and induce vomiting by touching the back of the throat with finger, or if available by administering syrup ipecac. If person is unconscious, do not give anything by mouth and do not induce verniting

If inhaled, remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth, Get medical attention,

If on skin, immediately flush with plenty of water for at least 15 minutes. Get medical attention.

If in eyes, hold eyelids open and flush with a gentle stream of water for 15 minutes. Call a physician if irritation persists.

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS CAUTION

May be harmful if swallowed, inhaled or absorbed through skin! Causes moderate eye irritation. May cause irritation of nose, throat and skin. Avoid contact with eyes, skin or clothing. Avoid breathing spray mist. In case of contact, flush with plenty of water. For eyes, get medical attention. Wash thoroughly with soap and water after handling.

See side panel for additional Precautionary Statements. Consult MSDS for additional information on handling and safety Directions For Use (continued)

Preservation for Paste-Add 0.33% to 1.0% VANCIDE 51 to starch paste based on the weight of the starch, but no less than 0.02% based on the total weight of the paste. To preserve alginate pastes. add 0.1% to 0.2% VANCIDE 51 based on the alginate solution. To preserve casein solution, add 0,33% to 1,0% VANCIDE 51 based on the weight of the casein, but no less than 0.1% based on the total weight of the paste.

Wood Veneer-Add 4.8 pounds or 2 quarts of VANCIDE 51/100 gallons of water to make a dip solution for sap stain and mold control. Freshly cut veneer should be dipped at least 15 seconds.

Preservation of Cutting Oils-To prevent cutting oil solutions and emulsions from developing undesirable odors and broken emulsions due to bacterial and fungal action, add VANCIDE 51 to diluted fluid at 500 to 1000 ppm based on fluid weight. To prepare 500 ppm, add 4.175 pounds (55.4 fluid ounces) of VANCIDE 51 per 1000 callons of fluid and for 1000 ppm, add 8.35 pounds (110.8 fluid ounces) per 1000 gallons of fluid.

STORAGE AND DISPOSAL - Store in a cool dry place. Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Do not reuse empty container.

PESTICIDE DISPOSAL - Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL - Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or incineration, or if allowed by state and local authorities, by burning. If burned, stay out of smoke,

> EPA REG. No. 1965-8 EPA EST. No. 1965-KY-1

Issued: 12/04 Replaces: 3/99

fabric, treat as follows based on 100% wet pick-up: 1. Pad on a solution of 5 parts VANCIDE 51 and 95 parts water

ENVIRONMENTAL HAZARDS

National Pollutant Discharge Elimination System (NPDES) permit

and the permitting authority has been notified in writing prior to dis-

charge. Do not discharge effluent containing this product to sewer

systems without previously notifying the local sewage treatment

plant authority. For quidance contact your State Water Board or

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner incon-

Mold-Resistant Paper and Paperboard-To impart mold-resistant

properties to paper or paperboard, apply 1.65% to 3.3% VANCIDE

51 based on the weight of the sheet as a surface treatment at the

size press or calendar stack. Do not use for the manufacture of

mold-resistant paper and paperboard intended for food packaging

Preservation of Cotton Fabrics-To prepare mildew-proof cotton

2. Pad on a 1.2% solution of zinc acetate dihydrate and dry.

See side panel for additional directions for use.

NET WEIGHT 525 lbs., 55 Gallons

Precautionary Statements, continued

Regional Office of the EPA.

sistent with its labeling

purposes.

RTV PRODUCT 47808



R.T. Vanderbilt Company, Inc.

30 Winfield Street, P.O. Box 5150, Norwalk, CT 06856-5150

 FOR CHEMICAL EMERGENCY - Spill, Leak, Fire, Exposure or Accident, Call CHEMTREC[®] - Day or Night: 800-424-9300 International Emergencies: 202-483-7616 (Call Collect) • Non-Emergencies: 800-262-8200

NON-MAREANTY OF RESULTS. We do not warrant the results to be obtained in using any material supplied by us. and because the conditions of use are beyond bur control, we disclaim all liability with respect to the use, handling or further processing of such material

Under the Federal Insecticias, rungicide, and Rodenticide Act as amended, for the pesticide, registered under

EPA Reg. No. 1965-8