

NET WEIGHT 50 LBS

**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS & DOMESTIC ANIMALS  
DANGER**

Causes irreversible eye damage. Harmful if swallowed or inhaled. May cause allergic skin reactions. Do not get in eyes. Wear goggles or face shield when handling. Avoid contact with skin and clothing. Remove and separately launder clothing before reuse.

**ENVIRONMENTAL HAZARDS**

This product is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or public water unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

**DIRECTIONS FOR USE**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

**READ ENTIRE LABEL. USE STRICTLY IN ACCORDANCE WITH THE PRECAUTIONARY STATEMENTS AND DIRECTIONS, AND WITH APPLICABLE STATE AND FEDERAL REGULATIONS.**

**Vinyl**-To protect vinyl compounds from mildew growth and stiffening caused by bacteria and fungi, add 0.5 to 1 part VANCIDE 89 based on 100 parts, by weight, of resin.

**Paint**-Protect paint from damage by mold by milling in 0.25 to 1.0% VANCIDE 89 based on the weight of the paint. For linseed oil exterior paints, use from 0.25% VANCIDE 89 (3 lbs./100 gallons) with 2.5 pounds zinc oxide per gallon to 1.0% VANCIDE 89 (12 lbs./100 gallons) with 1.5 pounds zinc oxide per gallon. For zinc-free exterior paints, such as alkyd blister-proof paints, use 0.75% to 1.0% VANCIDE 89 (9 to 12 lbs./100 gallons) For maintenance paints for breweries, hospitals and food processing plants, based on alkyds or other varnishes containing little or no zinc, use 1% VANCIDE 89 (12 lbs./100 gallons). Not recommended for emulsion paints. VANCIDE 89 is a dry powder, disperse in the paint as a pigment. Impermeable gloves must be worn when applying oil-based paints for home or professional use.

See side panel for additional directions for use

# Vancide\* 89

## INDUSTRIAL PRESERVATIVE

Active Ingredients	By Wt.
*Captan .....	88%
Related Derivatives .....	2%
Inert Ingredients .....	10%

N-Trichloromethylthio-4-cyclohexene-1,2-dicarboximide.  
FORM-E NA-9188 N.O.S.  
(CAPTAN)

*Per self Center  
OCT 3 1987*

**KEEP OUT OF REACH OF CHILDREN**

### DANGER

#### STATEMENT OF PRACTICAL TREATMENT

**If in eyes:** Flush with plenty of water. Call a physician.  
**If swallowed:** Drink promptly a large quantity of milk, egg whites, gelatin solutions, or if these are not available drink large quantities of water. Avoid alcohol.  
**If inhaled:** Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

**Note to Physicians:**  
Emergency Information - call (415) 233-3737.

See side panel for additional precautionary statements.

**Directions for Use (Continued)**  
**Lacquer**-To protect lacquer from the growth of mildew, a the solids.

**Rubber and Rubber Coater**- latex for making cast or coat based on the total dry weight

**Polyethylene**-To protect pol bacteria, mill in 0.75% VANC

**Soap**-To make sanitizing c 1.0% VANCIDE 89 by weight mended for bar or liquid soap

**Wallpaper Flour Paste**-For against growth of mold, use weight of the paste.

#### STORAGE AND DISPO

#### PROHIBITIONS:

Do not contaminate water, cleaning of equipment. Oper

#### STORAGE:

Store in cool, dry place. Prote in original container. Do not

#### PESTICIDE DISPOS

"Pesticide wastes are acutely pesticide, spray mixture, or if these wastes cannot be di instructions, contact your S Agency, or the Hazardous Was Regional Office for guidance

#### CONTAINER DISPOS

Completely empty liner by sha loosen clinging particles. Er ment. Then dispose of liner in allowed by State and local au cannot be reused, dispose of

E.P.A. REG NO. 1965-11