

Reg # 1965-11 PM-23

NET WEIGHT 50 LBS

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS & DOMESTIC ANIMALS
DANGER**

CORROSIVE

Causes irreversible eye damage. Harmful if swallowed or inhaled. May cause allergic skin reactions. Do not get in eyes. Avoid contact with skin and clothing or inhalation of dust. Workers must wear respirators, gloves, protective clothing (such as long-sleeved shirts and trousers) at all phases of the application process.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not apply directly to water or wetlands.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

READ ENTIRE LABEL. USE STRICTLY IN ACCORDANCE WITH PRECAUTIONARY STATEMENTS AND DIRECTIONS, AND WITH APPLICABLE STATE AND FEDERAL REGULATIONS.

Vinyl - To protect vinyl compounds from mildew growth and stiffening caused by bacteria and fungi, add 0.5 to 1 part VANCIDE 89 based on 100 parts, by weight, of resin.

Paint - Protect paint from damage by mold by milling in 0.25 to 1.0% VANCIDE 89 based on the weight of the paint. For linseed oil exterior paints, use from 0.25% VANCIDE 89 (3 lbs./100 gallons) with 2.5 pounds zinc oxide per gallon to 1.0% VANCIDE 89 (12 lbs./100 gallons) with 1.5 pounds zinc oxide per gallon. For zinc-free exterior paints, such as alkyd blister-proof paints, use 0.75% to 1.0% VANCIDE 89 (9 to 12 lbs./100 gallons). For maintenance paints for breweries, hospitals and food processing plants, based on alkyds or other varnishes containing little or no zinc, use 1% VANCIDE 89 (12 lbs./100 gallons). Not recommended for emulsion paints. VANCIDE 89 is a dry powder, disperse in the paint as a pigment. Impermeable gloves must be worn when applying oil-based paints for home or professional use.

See side panel for additional directions for use

181
Vancide* 89
INDUSTRIAL PRESERVATIVE

Active Ingredients	By Wt.
★ Captan	88%
Related Derivatives	2%
Inert ingredients	10%
★ N-[(trichloromethyl)thio]-4-cyclohexene-1,2-dicarboximide	



*RQ Hazardous substance, solid, n.o.s.
NA 9188 (Captan)*

KEEP OUT OF REACH OF CHILDREN

DANGER

STATEMENT OF PRACTICAL TREATMENT

If in eyes: Flush with plenty of water. Call a physician.
If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solutions, or if these are not available drink large quantities of water. Avoid alcohol.
If inhaled: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

Note to Physicians:

Emergency Information - call (415) 233-3737.

See side panel for additional precautionary statements.

Directions for Use (Continued)

Lacquer - To protect lacquer used in coating electrical equipment from the growth of mildew, add 1% to 3% VANCIDE 89 based on the solids.

Rubber and Rubber Coated Articles - To prepare bacteriostatic latex for making cast or coated products, add 0.4% VANCIDE 89 based on the total dry weight of the latex compound.

Polyethylene - To protect polyethylene from the growth of fungi and bacteria, mill in 0.75% VANCIDE 89 by weight of the polyethylene.

Soap - To make sanitizing deodorant powdered hand soap, add 0.4% VANCIDE 89 by weight of the anhydrous soap. Not recommended for bar or liquid soap.

Wallpaper Flour Paste - For preservation of wallpaper flour paste against growth of mold, use 0.25% VANCIDE 89 based on the weight of the paste.

STORAGE AND DISPOSAL

PROHIBITIONS:

Do not contaminate water, food or feed by storage, disposal or cleaning of equipment. Open dumping is prohibited.

STORAGE:

Store in cool, dry place. Protect from excessive heat. Keep pesticide in original container. Do not store or transport near food and feed.

PESTICIDE DISPOSAL:

Pesticide, spray mixture, or rinse water that cannot be used according to the label instructions must be disposed of according to applicable Federal, State, or local procedures.

CONTAINER DISPOSAL:

Completely empty liner by shaking and tapping sides and bottom to loosen clinging particles. Empty residue into application equipment. Then dispose of liner in a sanitary landfill or by incineration if allowed by State and local authorities. If drum is contaminated and cannot be reused, dispose of in the same manner.

NOTIFICATION
LABEL NOT REVIEWED
PER PR NOTICE

DATE: NOV 20 1998