


Intended for Industrial or Professional Use ONLY. NOT FOR SALE TO THE PUBLIC

DIRECTIONS FOR USE



THIS PRODUCT is a high-strength chemical solution which will protect wood against deterioration caused by dry rot, damp rot and similar wood-rotting fungi. It is available in CLEAR for surfaces intended to be top-coated with paint. It is an effective rot inhibitor and when thoroughly dry, is non-toxic to plant life.

APPLICATION—Use treatment as received without thinning for best protection. Small objects should be immersed in a dip tank sufficiently long to obtain deep penetration (3 minutes minimum). Large wood objects such as fence posts should be soaked for 12 to 48 hours.

CAUTION: THIS PRODUCT CONTAINS AN INFLAMMABLE SOLVENT: THEREFORE, KEEP AWAY FROM FIRE OR FLAME, AND DO NOT SMOKE DURING APPLICATION. ALWAYS PROVIDE PLENTY OF MOVING FRESH AIR TO CARRY OFF EVAPORATING SOLVENTS WHILE DRYING. AVOID BREATHING CONCENTRATED VAPORS FOR LONG PERIODS. If surface is to be top-coated with paint, be sure to use the CLEAR formula. KEEP OUT OF THE REACH OF CHILDREN.

May cause skin irritation. Avoid prolonged or repeated contact with skin. KEEP AWAY FROM EYES AND MOUTH. IF CHEMICAL SOLUTION GETS IN EYES OR MOUTH SEE DOCTOR IMMEDIATELY. Avoid prolonged or repeated breathing of vapor, fumes, or spray mist. USE WITH ADEQUATE VENTILATION. HARMFUL IF SWALLOWED.

Form 123 ZNS

969 - 2.5M