

---- DIRECTIONS FOR USE ------

CONTAINS PETROLEUM DISTILLATES

CAUTIONI COMBUSTIBLE

Do not use, pour, spill or store near heat or open flame. Use only with adequate ventilation. Avoid prolonged breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin Harmful if swallowed.

Keep closures tight and upright to prevent leakage. In case of spillage absorb and dispose of in accordance with local applicable regulations.

This product is toxic to fish. Keep out of lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not reuse container. Destroy when empty.

FIRST AID—In case of skin contact, flush with plenty of water; For eyes, immediately flush with plenty of water for 15 minutes and get medical attention. If affected by inhalation of vapor, remove to fresh air. If swallowed, call a Physician immediately. **DO NOT** induce vomiting.

This product is a high strength chemical solution which will protect wood against deterioration caused by dry rot, damp rot and similar wood rotting fungi. It is available in clear for surfaces intended to be top-coated with paint. It is an effective rot inhibitor and when thoroughly dry, is non-toxic to plant life.

APPLICATION—Use treatment as received without thinner for best protection. Small objects should be immersed in a dip tank sufficiently long to obtain deep penetration (3 minutes minimum). Large wood object like fence posts should be soaked for 12 to 48 hours.

INTENDED FOR INDUSTRIAL OR PROFESSIONAL USE ONLY NOT FOR SALE TO THE PUBLIC

1 Gallon U.S. Standard Measure (3.785 Liters)

01

ACCEPTED APR 1 7 1979

4

.

.

•

.

.

.

.

,

\$

Under the Foderal Speectickies, Frequeside, and Rodenstickie And memory and the the posticies regimered under 2072-6

1 1

主义

.

,

.