

"TEXASPHALTIC"

TRADE MARK REG. U. S. A. PATENT OFFICE

Copper Preservative 1 GAL.

FOR PRESERVING COMMERCIAL FISHING NETS AND GEAR.
FOR PRIMING WOODEN BOAT HULLS AND OTHER WOODWORK.
FOR TERMITE PROOFING LUMBER.

DIRECTIONS:— NETS: Dip and hang to dry in the shade. Submerge net and gear for 1 minute in unadulterated Copper Preservative.

WOOD: Dip or paint with brush or use spray gun. Wood to be in contact with excessive moisture or with the soil should be given two brush coats or dipped for at least 3 minutes in Copper Preservative to

give effective control of wood rotting fungi and termites.

CANVAS, ROPE, AND SIMILAR FABRICS: Completely submerged fabric, fibers or dip or paint with brush or use spray gun.



BEST BY ACID TEST

ACTIVE INGREDIENTS: - 100%
Copper Naphthenate - - - - 25%
(Equivalent to 2% of copper expressed as metallic.)

Rubber Gums - - - - - 10%
Petroleum distillate - - - - 65%

DANGER

CONTAINS PETROLEUM DISTILLATE
KEEP OUT OF REACH OF CHILDREN.
HARMFUL OR FATAL IF SWALLOWED.
IF SWALLOWED DO NOT INDUCE VOMITING.

Call Physician Immediately

USDA REG. NO. 2158-2

Manufactured Under U. S. Patent

Manufactured By

TEXASPHALTIC COMPANY

2028 ABUNDANCE STREET —:— NEW ORLEANS, LA., U. S. A.

2158 - 2

2158 - 2

