

# RED SPOT CREOSOTE OIL

## PROTECTS WOOD AGAINST INSECT ATTACK AND DECAY

EPA Registration No. 2192-4

Active Ingredient: Creosote Oil ..... 97%  
Inert Ingredient: Water ..... 3%

### WARNING

KEEP OUT OF REACH OF CHILDREN  
MAY CAUSE SKIN IRRITATION

Avoid contact with skin.  
Keep away from eyes and mouth. If Creosote Oil  
gets in eyes or mouth see doctor immediately.  
Avoid breathing of vapor, fumes or spray mist.  
Use with adequate ventilation.  
Harmful if swallowed.

RED  SPOT

## RED SPOT C

Red Spot Creosote Oil is a pure distillate with a reduction of freezing point and is for use in contact with the ground. Wood saturated with this oil is resistant to decay, powder post beetles, or termites. Is not to be painted.

CO

Estimate need of Red Spot Creosote Oil for painting or about one gallon per cubic foot of wood.  
After application by brush or spray, allow to dry in atmospheric conditions.

APP

For best penetration, especially in cold weather, use at 125°-150° F. using a water double boiler. If possible, otherwise keep it in a warm place.

Crystalline solids separate from Creosote Oil in cold atmosphere. These solids are not harmful and should be redissolved by heat.

For best results:

1. Remove all loose foreign matter from wood. Creosote Oil.
2. Use dry and seasoned wood.
3. If dipping process is used, fence posts and wood members should be free of paint and immersed in Red Spot Creosote Oil.
4. Application by brush or spray should be made in flowing coats of the material by hand.
5. All wood that is to come into contact with the ground should be treated.
6. Underwater structures should be treated preferably, should be pressure treated.
7. For protection against termite infestation, apply to foundation and construction.

### WA

MAY CAUSE  
KEEP OUT OF

Avoid contact with skin.  
Keep away from eyes and mouth.  
Avoid breathing of vapor, fumes or spray mist.  
Use with adequate ventilation.  
Harmful if swallowed.

RED SPOT PAINT

Evaporates

ONE

# SPOT DTE OIL

## S WOOD SECT ATTACK DECAY

tion No. 2192-4

..... 97%  
..... 3%

### WARNING REACH OF CHILDREN SKIN IRRITATION

in.  
and mouth. If Creosote Oil  
uth see doctor immediately.  
or, fumes or spray mist.  
ntilation.



## RED SPOT CREOSOTE OIL

### USES

Red Spot Creosote Oil is a pure distillate of high temperature Coal Tar processed for reduction of freezing point and is for use on fence posts, sills, joists, and wood in contact with the ground. Wood saturated with it will not be attacked by fungi, powder post beetles, or termites. Is not suitable for application to surfaces that are to be painted.

### COVERAGE

Estimate need of Red Spot Creosote Oil at 200 square feet per gallon per coat by painting or about one gallon per cubic foot when hot-cold dipping.

After application by brush or spray, let wood dry for 4 to 24 hours, as required by atmospheric conditions.

### APPLICATION

For best penetration, especially in cold weather, heat Red Spot Creosote Oil to 125°-150° F. using a water double boiler. Avoid working with Creosote in direct sunlight, if possible, otherwise keep it off exposed skin surfaces.

Crystalline solids separate from Creosote Oil naturally when the material is exposed to cold atmosphere. These solids are a part of the preservative material in Creosote Oil and should be redissolved by heating and stirring before the Oil is used.

For best results:

1. Remove all loose foreign matter from surface before application of Red Spot Creosote Oil.
2. Use dry and seasoned wood.
3. If dipping process is used, fence posts, poles, foundation timbers, and heavy wood members should be free of bark, dry to limit of good air seasoning, and immersed in Red Spot Creosote Oil for a period of 12 to 48 hours.
4. Application by brush or spray should cover all surfaces, cracks, and knots.
5. All wood that is to come into contact with the ground should receive 2 to 3 flowing coats of the material by the brush or spray method.
6. Underwater structures should have 3 to 4 brush or spray treatments or, preferably, should be pressure treated.
7. For protection against termites, wood should be treated prior to use in construction.

### WARNING

MAY CAUSE SKIN IRRITATION  
KEEP OUT OF REACH OF CHILDREN

Avoid contact with skin.

Keep away from eyes and mouth. If Creosote Oil  
gets in eyes or mouth see doctor immediately.

Avoid breathing of vapor, fumes or spray mist.

Use with adequate ventilation.

Harmful if swallowed.

## RED SPOT PAINT & VARNISH CO., INC.

Evansville, Indiana

ONE U.S. GALLON