



Red Spot 330 is a non-flammable, non-toxic, water-soluble wood preservative. It is effective against termites and wood-rotting fungi. It is also effective against decay fungi, including those that cause structural rot. Treatment with Red Spot 330 may be applied with maximum strain in the form of a spray or dip. It is NOT recommended for use on Red Wood and Yellow Pine.

Red Spot 330 may be applied by dipping, spraying or brushing. The preservative should be applied to all wood which is in contact with the soil. It should be applied to timbers at the time of construction if possible. Work will open into cracks and checks. Give special attention to end-grain wood as this is a likely spot for decay. All wood should be removed to avoid maximum protection. If dipping is possible, allow immersion of at least three minutes where this product is to be used as a control of termites and wood-rotting fungi. Fence posts, poles, foundation timbers and heavy wooden members should be free of bark, dry and well seasoned and immersed in the product for a period of 12 to 48 hours to be an effective wood preserver.

Wood may be painted after 48 hours drying, following painting directions as for new wood.

RED SPOT®

One U.S. Gallon

CAUTION, CONTAINS PETROLEUM DISTILLATE. IF SWALLOWED, CALL PHYSICIAN IMMEDIATELY. COMBUSTIBLE. DO NOT USE, POUR, SPILL, OR STORE NEAR HEAT OR OPEN FLAME. USE WITH ADEQUATE VENTILATION. Avoid contact with skin

and breathing of vapor or spray mist. Do not transfer contents to bottles or other unlabeled containers. Close container after each use. Do not reuse empty container. Destroy it by perforating or crushing. Bury or discard in a safe place away from water supplies.

RED SPOT PAINT & VARNISH CO., INC., Evansville, Indiana



RED  **SPOT**

One U.S. Gallon

CAUTION, CONTAINS PETROLEUM DISTILLATE. IF SWALLOWED, CALL PHYSICIAN IMMEDIATELY. COMBUSTIBLE. DO NOT USE, POUR, SPILL, OR STORE NEAR HEAT OR OPEN FLAME. USE WITH ADEQUATE VENTILATION. Avoid contact with skin

and breathing of vapor or spray mist. Do not transfer contents to bottles or other unlabeled containers. Close container after each use. Do not reuse empty container. Destroy it by perforating or crushing. Bury or discard in a safe place away from water supplies.

RED SPOT PAINT & VARNISH CO., INC., Evansville, Indiana

POT

One U.S. Gallon

RED  SPOT

rid-rot[®] 330

**WOOD PRESERVATIVE
FOR SURFACES THAT
REQUIRE PAINTING**

ACCEPTED KEEP OUT OF REACH OF CHILDREN

AUG 13 1974

UNDER FEDERAL PESTICIDE ACT
FUNGICIDE REGISTERED
EPA REG. NO. 2192-1
SUBMIT

Copper, as metal, 2% minimum	
ACTIVE INGREDIENT	
Copper naphthenate	20%
INERT INGREDIENTS	
Petroleum distillate	45%
Linseed oil	35%
EPA Registration No 2192-1	

CAUTION!

HARMFUL IF SWALLOWED

See caution on back panel

ing of vapor or spray mist.
fer contents to bottles or
led containers. Close con-
each use. Do not reuse
ainer. Destroy it by perfo-
ishing. Bury or discard in a
way from water supplies.

C., Evansville, Indiana