

CHLORDANE 72% EMULSIFIABLE

PRECAUTIONARY STATEMENTS

Hazards to Humans & Domestic Animals

WARNING: May be fatal if swallowed. May breathe vapor, dust or spray mist. Do not get in eyes, on skin or clothing. In case of skin contact, wash immediately with soap and water. Avoid contamination of feed and foodstuffs.

Environmental Hazards

This product is toxic to fish, birds and other wildlife. Birds feeding on treated areas may be killed. Keep out of lakes, streams and ponds. Do not apply where runoff is likely to occur. Do not apply when weather conditions favor drift from treated areas. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

Physical or Chemical Hazards

Do not use, pour, spill or store near heat or open flame.

ACCEPTED

AUG 28 1980

Under the Federal Insecticide, Fungicide and Rodenticide Act as amended for the pesticide registered under EPA Reg. No. 2217-713

FOR THE CONTROL OF TERMITES

ACTIVE INGREDIENTS

*Technical Chlordane 72.0%

Kerosene 22.0%

INERT INGREDIENTS 6.0%

Total 100.0%

*Equivalent to 8 lbs. technical chlordane and 2 lbs. other related compounds.

This product contains 8 lbs. technical chlordane per gallon.

KEEP OUT OF REACH OF CHILDREN WARNING

Statement of Practical Treatment

If Swallowed: Drink one or two glasses of water and induce vomiting by touching back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person. Get medical attention immediately.

If Inhaled: Remove victim to fresh air and apply respiration if indicated.

If On Skin: Wash promptly with soap and water. Rinse thoroughly.

If In Eyes: Rinse eyes for at least 15 minutes with water and call a physician immediately.

See side panels for additional precautionary statements.

NET CONTENTS ONE HALF GALLON

(cont. from left side panel)

one foot apart that extend from the trench bottom to the footing. Make holes closer in hard packed clay soils. Never dig below the top of the footing. Apply the solution in the trench at a rate of 4 gallons per 10 linear feet per foot of depth. Apply half of this to the back foot likewise, treat along the inside and outside of foundations of crawlspace buildings. Cover treated soil with a thin layer of untreated soil, and take care to avoid contaminating water supplies.

For raised porches, terraces, and entrance slabs, drill holes at one foot intervals, 6 inches from the foundation, and pour one-half gallon of solution into each hole. Refill holes. Slabs with heat ducts or radiating heat pipes should be treated by professional pest control operators.

The object is to establish a treated soil barrier which will prevent termite entry. Other critical areas may also require treatment, particularly if there are inaccessible areas, basements or slab type construction. It is suggested that you contact the Agricultural Cooperative Extension Service for advice or consult a Professional Pest Control Service.

Avoid contamination of public and private water supplies by following these precautions. Use anti-backflow siphonage equipment. Refer to federal (Federal Housing Administration), state and local specifications for safe distances of treatment areas from wells. Soil in the vicinity of wells should not be treated if it is water saturated, or by injecting the solution under pressure. Soil should be removed to an area safe from well contamination, treated, and returned to the trench which has been lined with plastic sheeting.

DISPOSAL

Do not reuse empty container. Wrap container and put in trash collection.

NOTICE: Seller warrants that this product conforms to the ingredient statement on the label. Some conditions of use, such as weather, compatibility with other chemicals, and condition of application equipment will vary. Seller makes no representation other than those stated on this label.

EPA REG. NO. 2217-9X
EPA EST. NO. 2017-KS-1
EPA 6X

15A

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.


SUBTERRANEAN TERMITES

Use Chlordane 72% Emulsifiable in a 10% water emulsion as follows: Add one part Chlordane 72% to 12 gallons of water and mix thoroughly.

Buildings with Basements or Crawl-Spaces

First remove all wood debris and wood floors. Around piers, pipes, chimney bases and along foundations of poured concrete dig a trench 6 inches wide and 4 inches deep. For brick or block foundations dig the trench at least 12 inches deep. If termites more than 12 inches deep, make holes with 1/2 inch diameter pipe in a grid about

(cont. on right side panel)

Made by  pbi / Gordon CORPORATION
HANSBERRY, MASSACHUSETTS