

ACCEPTED
Nov 12, 1971
UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGISTER-
ED UNDER NO. 2337-65 SUBJECT
WOOD PRESERVATIVE COMMENTS.

2337-65

WOOD PRESERVATIVE

D & D

CAUTION

This product is toxic to fish. Do not contaminate water by cleaning of equipment, or disposal of wastes.

Avoid contact with the skin and wash with warm water and soap if spilled on body. Do not breathe spray mist. If swallowed, induce vomiting by sticking finger down throat or by giving soapy or strong water to drink. Repeat until vomit is clear. Call a physician. Never give anything by mouth to an unconscious person.

****DO NOT RE-USE EMPTY CONTAINER. DESTROY IT BY PERFORATING OR CRUSHING. BURY OR DISCARD IN A SAFE PLACE.

A symbol of quality—dependability — economy for more than a quarter of a century.

Copyright by DeMert & Dougherty, Inc.

DEMERT & DOUGHERTY, INC.
CHICAGO, ILLINOIS 60650

HIGHLY REFINED No.1

For Dipping, Brushing or Spraying

ACTIVE INGREDIENTS	100%
Refined Creosote Oil	100%

CAUTION HARMFUL OR FATAL IF SWALLOWED
READ CAREFULLY CAUTION ON SIDE PANEL

KEEP OUT OF REACH OF CHILDREN

E.P.A. REG. NO. 2337-65

NET CONTENTS-1 GALLON

WOOD PRESERVATIVE

Use D&D Highly Refined No. 1 Creosote Oil — the perfect finish for fence rails and posts — brings out the beauty of the wood: protects against rot and decay.

LIGHT BROWN STAIN — Easily applied — Gives beautiful finish.

DIPPING — Immerse the wood to be treated for at least one hour. Be sure that wood to be treated is completely peeled and thoroughly seasoned.

BRUSHING — Flood over surface to completely fill all checks and defects. After approximately 24 hours or after the first coat has dried, apply a second coat in the same manner as the first.

SPRAYING — Use any spray equipment, apply the same as paint. After first coat has dried, apply a second coat in the same manner as the first. Clean spray equipment with kerosene.

DO NOT CUT OR SAW TREATED TIMBER — Treated timber should never be cut if it can be avoided. All sawing and framing should be done, if possible, before treatment. If it is necessary to trim it after treatment, the exposed untreated wood should be painted with several coats of hot creosote before it is put in place.

If buff-treated posts are not to be used for some time, they should be piled in such a manner that air can circulate between them. If they are close-piled or allowed to lie on the ground for a long time, decay is likely to start in the untreated parts.

When setting treated posts, poles, and other timbers, allow at least 6 inches of treated wood to extend above the ground after the posts are set. Otherwise decay may begin above the treated part. Where possible, brush coat the entire surface extending above the ground.

Approximate covering capacity: Dipping and Spraying 1 gallon per 100 square feet; Brushing 1½ gallons per 100 square feet.

D
971
Pesticide
Label
Subject

7-65

HIGHLY REFINED No.1

For Dipping, Brushing or Spraying

ACTIVE INGREDIENTS 100%
Refined Creosote Oil 100%

CAUTION HARMFUL OR FATAL IF SWALLOWED
READ CAREFULLY CAUTION ON SIDE PANEL

KEEP OUT OF REACH OF CHILDREN

E.P.A. REG. NO. 2337-65

NET CONTENTS-1 GALLON

WOOD PRESERVATIVE

Use D&D Highly Refined No. 1 Creosote Oil -
the perfect finish for fence rails and posts -
brings out the beauty of the wood: protects
against rot and decay.

WOOD STAIN - Easily applied - Gives
rich finish.

Immerse the wood to be treated for
one hour. Be sure that wood to be
completely peeled and thoroughly

BLENDING - Flood over surface to completely
fill checks and defects. After approximately
24 hours or after the first coat has dried, apply
second coat in the same manner as the first.

SPRAYING - Use any spray equipment, apply
the same as paint. After first coat has dried,
apply a second coat in the same manner as the
first. Clean spray equipment with kerosene.

DO NOT CUT OR SAW TREATED TIMBER -
Treated timber should never be cut if it can be
avoided. All sawing and framing should be done,
if possible, before treatment. If it is necessary
to trim it after treatment, the exposed untreated
wood should be painted with several coats of
hot creosote before it is put in place.

If buff-treated posts are not to be used for some
time, they should be piled in such a manner that
air can circulate between them. If they are
close piled or allowed to lie on the ground for a
long time, decay is likely to start in the untreated
parts.

When setting treated posts, poles, and other
timbers, allow at least 6 inches of treated wood
to extend above the ground after the posts are
set. Otherwise decay may begin above the
treated part. Where possible, brush coat the en-
tire surface extending above the ground.

Approximate covering capacity: Dipping and
Spraying 1 gallon per 100 square feet; Brushing
1½ gallons per 100 square feet.

HIGHLY REFINED No.1

For Dipping, Brushing or Spraying

ACTIVE INGREDIENTS 100%
Refined Creosote Oil 100%

CAUTION HARMFUL OR FATAL IF SWALLOWED
READ CAREFULLY CAUTION ON SIDE PANEL

KEEP OUT OF REACH OF CHILDREN

E.P.A. REG. NO. 2337-65

NET CONTENTS-1 GALLON