

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act,  
as amended, for the pesticide  
registered under  
EPA Reg. No. 2342-933



# ALDRIN LIQUID-4

ALDRIN LIQUID-4 is an emulsifiable insecticidal concentrate containing 4 pounds of aldrin per gallon. It is designed for use against termites when diluted with water and applied as directed below.

## DIRECTIONS FOR USE

### DO NOT APPLY IN A BROADCAST MANNER.

**TERMITE CONTROL** — Add 1 gallon of ALDRIN LIQUID-4 to 95 gallons of water and mix to make a 0.5% emulsion. Apply the 0.5% emulsion as follows:

#### A. Buildings with Crawl Spaces

(1) Apply 2 gallons per 5 linear feet to critical areas only under the house, such as along the inside of foundation walls, around piers, sewer pipes, conduits, etc. Trench according to directions in part (2) below.

(2) Along the outside of foundation walls, dig a narrow trench out from the foundation no wider than 6 inches, such trench to be dug no deeper than the top of the footings. If the trench is less than 15 inches in depth to the top of the footings, apply 1 gallon per 5 linear feet. Replace the soil and apply another 1 gallon per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. If the trench is more than 15 inches in depth to the top of the footings, apply 2 gallons per 5 linear feet. Replace the soil and apply another 2 gallons per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. A trench 30 inches deep is a maximum depth required alongside foundations where the top of the footings is greater than 30 inches deep. In lieu of trenching to a 30 inch depth, make the trench 12 inches deep and rod to footings, spacing the holes about 1 foot apart.

(3) Apply 1 gallon per 10 square feet of soil surface under attached porches, entrance platforms, utility entrances, and similar situations where slab or fill is at the grade level. Where crawl spaces exist treat as described in part (1) above.

(4) Treat all voids in hollow masonry units of the foundation at the rate of at least 1 gallon per 5 linear feet of wall. It is best to apply the chemical near the footing.

#### B. Buildings with Concrete Slab on the Ground

(1) Apply 1 gallon per 10 square feet as an over-all treatment under the slab as well as under attached porches, entrance platforms, utility entrances and similar situations where slab or fill is at grade level. In case of washed gravel, cinders, or similar coarse material, increase the dosages by at least one-half. If soil is treated and the concrete slab is not poured on the same day, a polyethylene sheeting or other waterproof material shall be placed over the treated soil.

(2) Apply 2 gallons per 5 linear feet to critical areas only under the slab, such as along the inside of foundation walls, around sewer pipes, conduits, etc. Trench as in part (3) below.

(3) Along the outside of foundation walls, dig a narrow trench out from the foundation no wider than 6 inches, no deeper than the top of the footings, but no deeper than 15 inches, unless the footing is much deeper in some places on account of the slope of the land, then treat as under (A) (2). Cover the back fill with a thin layer of soil.

(4) Treat all voids in hollow masonry units of the foundation at the rate of at least 1 gallon per 5 linear feet of wall. It is best to apply the chemical near the footings.

Revision I

E.P.A. Est. 2342-FL-1

ACTIVE INGREDIENTS:		BY WEIGHT
Aldrin	42.55%	†
Aromatic petroleum derivative solvents	48.60%	
INERT INGREDIENTS:		8.85%

† Equivalent to 40.43% hexachloro-hexahydro-endo-exodimethanonaphthalene and 2.12% related compounds.

CONTAINS 4 POUNDS ACTUAL ALDRIN PER GALLON.

**WARNING: MAY BE FATAL IF SWALLOWED,  
INHALED OR ABSORBED THROUGH SKIN.**

**KEEP OUT OF REACH OF CHILDREN**

Do not get in eyes, on skin or on clothing. Do not breathe vapor or spray mist. Keep container closed. Use with adequate ventilation. Wash hands, arms, and face with soap and water after handling and before eating or smoking. Wear clean clothing. During commercial or prolonged exposure in spray mixing and loading operations, wear clean synthetic rubber gloves, protective clothing and goggles. Wear mask or respirator of a type passed by the U.S. Bureau of Mines for aldrin protection. Do not use, pour, spill or store near heat or open flame.

See side panel for first aid information.

NET CONTENTS    GALLONS

Product No. 20-70268

#### C. Buildings with Basements

(1) Apply 1 gallon per 10 square feet as an over-all treatment under the basement flooring, as well as under attached porches, entrance platforms, utility entrances, and similar situations where slab fill is at the grade level. In case of washed gravel, cinders, or similar coarse material, increase the dosage by at least one-half. Where crawl spaces exist, treat as described in part (2) below.

(2) Apply 2 gallons per 5 linear feet to critical areas only under the basement flooring, as well as porches and entrances having crawl spaces, such as along the inside of foundation walls, around sewer pipes, conduits, piers, etc. Trench according to directions in part (3) below.

(3) Along the outside of foundation walls dig a narrow trench out from the foundation no wider than 6 inches, such trench to be dug no deeper than the top of the footings. If the trench is less than 15 inches in depth to the top of the footings, apply 1 gallon per 5 linear feet. Replace the soil and apply another 1 gallon per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. If the trench is more than 15 inches in depth to the top of the footings, apply 2 gallons per 5 linear feet. Replace the soil and apply another 2 gallons per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. A trench 30 inches deep is a maximum depth required alongside foundations where the top of the footings is greater than 30 inches deep. In lieu of trenching to a 30 inch depth, make the trench 12 to 15 inches deep and rod to footings, spacing the holes about 1 foot apart.

(4) Treat all voids in hollow masonry units of the foundation at the rate of 1 gallon per 5 linear feet of wall. It is best to apply the chemical near the footing.

**NOTE:** Do not apply or allow to drift to areas occupied by unprotected humans or beneficial animals.

Do not store at temperatures below freezing, as such low temperatures may be harmful to this product.

#### ENVIRONMENTAL PRECAUTIONS

**FISH AND WILDLIFE:** This product is highly toxic to fish, birds, and other wildlife. Birds and other wildlife in treated areas may be killed. Keep out of lakes, streams, or ponds. Do not apply where runoff is likely to occur. Do not apply when weather conditions favor drift from areas treated. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

**CONTAINER DISPOSAL:** Do not reuse container. Destroy when empty.

**FIRST AID:** If swallowed, induce vomiting by sticking finger down throat or by giving soapy or strong salty water to drink. Repeat until vomit is clear. Call a physician. Never give anything by mouth to an unconscious person. If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Call a physician. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Call a physician. Wash clothing before reuse.

#### CONDITIONS OF SALE

All statements concerning the use of this product apply only when the product is used as directed. THERE ARE NO WARRANTIES INCLUDING MERCHANTABILITY WHICH EXTEND BEYOND THE DESCRIPTION ON THE LABEL. The manufacturer shall in no event be liable for consequential damages. Read all directions carefully.

EPA Reg. No. 2342-933

K-2-75-W

MANUFACTURED BY  
 **KERR-McGEE CHEMICAL CORPORATION**  
OKLAHOMA CITY, OKLAHOMA