



HEPTACHLOR EMULSIFIABLE

FOR THE CONTROL OF TERMITES
CONTAINS 3 LBS. HEPTACHLOR PER GALLON
THIS PACKAGE CONTAINS

ACCEPTED
Apr. 19, 1972
247-146

ACTIVE INGREDIENTS:	
Heptachlor*	31.4%
Related Compounds	12.2%
Petroleum Distillate	49.4%
INERT INGREDIENTS	7.0%
TOTAL 100.0%	

*Heptachloro—4, 7—methanotetrahydroindene

DIRECTIONS:

DO NOT USE, POUR, SPILL OR STORE NEAR HEAT OR OPEN FLAME
Add 1 gallon of Heptachlor Emulsifiable to 72 gallons of water (0.5% emulsion).
Apply the 0.5% emulsion as follows:

1—SLAB-TYPE CONSTRUCTION

- a—Apply 1 gallon per 10 square feet as an overall pre-construction treatment under the slab and along attached porches or entrance platforms.
- b—Apply 2 gallons per 5 lineal feet to critical areas under the slab as pre-construction treatment, such as along the inside of the foundation walls and around utility entrances and interior partition foundation walls.

2—BUILDING WITH CRAWL SPACES

- a—Apply 2 gallons per 5 lineal feet in a trench along the outside of foundation walls, including entrance platforms and porches where the foundation is not more than 15-18 inches deep. If over 15-18 inches deep but not over 30 inches, apply 4 gallons per 5 lineal feet. Do not go deeper than the top of the footing.
- b—Apply 2 gallons per 5 lineal feet as a trenching application to critical areas under the house, such as along the inside of foundation walls and around piers and utility entrances. If trench is deeper than 15-18 inches but not over 30 inches, apply 4 gallons per 5 lineal feet. Do not go deeper than the top of the footing.
- c—Apply 1 gallon per 10 square feet of soil surface as a pre-construction treatment where the attached porches, entrance platforms, utility entrances, etc., have covering slab on fill of ground.
- d—Apply 1 gallon per 5 lineal feet of wall to voids in hollow masonry units of the foundation.

3—BUILDINGS WITH BASEMENTS

- a—Apply 1 gallon per 10 square feet as an overall pre-construction treatment under the basement flooring, attached porches, entrance platforms, utility entrances, and similar situations where slab fill is at ground level.
- b—Apply 2 gallons per 5 lineal feet in a trench along the outside of foundation walls, including entrance platforms and porches where the foundation is not more than 15-18 inches deep. If over 15-18 inches deep but not over 30 inches, apply 4 gallons per 5 lineal feet. Do not go deeper than the top of the footing.

- c—Apply 2 gallons per 5 lineal feet as a trenching application to critical areas under the house, such as along the inside of foundation walls, porches, entrance and piers. If trench is deeper than 15-18 inches but not over 30 inches, apply 4 gallons per 5 lineal feet. Do not go deeper than the top of the footing.
- d—Treat all voids in hollow masonry units of the foundation at the rate of 1 gallon per 5 lineal feet of wall.

Premises treated with 0.5% heptachlor will give residual control for a minimum of five years.

WARNING:

Keep Out of the Reach of Children

May be fatal if swallowed. Do not breathe vapor, dust or spray mist. Do not get on skin. In case of contact wash immediately with soap and water. Do not contaminate feed and foodstuffs.

Rinse empty container thoroughly with water and discard it.

Do not reuse empty drum. Return to drum reconitioner or destroy by perforating or crushing and burying in a safe place.

This product is toxic to fish, birds and other wildlife. Keep out of any body of water. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply only as specified on this label.

ANTIDOTE:

External—In case of spillage on skin, wash promptly with soap and water.
Internal—Emetic of 1 tablespoonful mustard in tumbler of water. Call a physician.

NOTICE

Stevens Industries, Inc. warrants that the product conforms to its chemical description and is reasonably fit for the purpose stated on the label when used in accordance with directions under normal conditions of use, but neither this warranty nor any other warranty of MERCHANTABILITY or FITNESS for a particular purpose, express or implied, extends to the use of this product contrary to label instructions, or under abnormal conditions, or under conditions not reasonably foreseeable to Stevens Industries, Inc. and buyer assumes the risk of any such use. Any damage arising from a breach of this warranty shall be limited to direct damages, and shall not include consequential commercial damage such as loss of profits.

Manufactured By

STEVENS INDUSTRIES, INC.

DAWSON, GEORGIA

81742

E. g. N. 3-116