

# REGATTA WORM PAINT

3804

BALTOCOP PENTA-CLEAR

ACTIVE INGREDIENT

Pentachlorophenol 4.86%

Fine Oil 7.00%

INERT INGREDIENTS

4.86%

7.00%

88.14%

100.00%

ACCEPTED

3/17/69

UNDER THE FEDERAL INSPECTION OF  
FUNGICIDE AND RODENTICIDE ACT  
FOR ECONOMIC POISON REGISTRED  
IN U.S.A. NO. 2568-4

DANGER!  
HARMFUL OR FATAL IF SWALLOWED.  
KEEP OUT OF REACH OF CHILDREN.  
SEE BACK FOR OTHER CAUTIONS.

1 U.S. GALLON

3.785 LITERS

MANUFACTURED BY

**BALTIMORE COPPER PAINT CO.**  
OLIVER REEDER & SON, INC.

BALTIMORE MD. 21230

REDFERNS LTD

NEW YORK, N.Y. 10038

ACCEPTED WITH COMMENTS

ESTABLISHED 1870

# REGATTA YACHT PAINT

104  
BALTIMORE, MD.

3/17/49

Antifouling Paint	104
Permanently protective	4.160
Flame Retardant	4.00
UV Protection	4.160
Anti-fouling paint	4.160

25.68-4  
3

PAINTED!  
MANUFACTURED IN SHALLOW B.  
PAINT & PAINTER OF CHILDREN.  
SEE BACK FOR OTHER PAINTERS.

1 U.S. GALLON  
3.785 LITERS

MANUFACTURED BY

## BALTIMORE COPPER PAINT CO.

OLIVER REEDER & SON, INC.

PROPRIETORS

BALTIMORE, MD. 21230

NEW YORK, N.Y. 10038

ACCEPTED WITH COMMENT

2966  
UNDER THE FEDERAL INSECTICIDE  
FUNGICIDE AND RODENTICIDE ACT  
FOR ECONOMIC SECURITY  
ED UNDER NO. 25

Comment

3804 BALTOCOP FENTA-CLEAR (Pentachlorophenol Type)  
WOOD PRESERVATIVES  
(USDA Reg. No. 2568-4)

All wood to be treated should be dry, and in any case where wood has been previously painted or varnished the existing coating must be removed. Coverage 400 to 600 square feet per gallon depending on the roughness and porosity of the wood. 72 hours drying time should be allowed before applying paint or varnish. Baltocop Green may show a slight bleed in the first coat of paint applied over it, but the second coat will show no discoloration. Use Baltocop Pentaclear on the surfaces to be varnished.

Wood to be dip treated should be immersed for at least 3 minutes; if sprayed or brushed, two flowing coats should be applied for effective control of wood rot. Baltocop Green and Baltocop Pentaclear contain poison which destroys the larvae of wood eating insects in addition to protecting against wood destroying bacteria and fungi. Do not add thinner or drier because any alteration of the formula will cause loss of effectiveness. Surface treatment of buildings is of little protection against termites as pressure application is required.

CAUTION: CONTAINS PETROLEUM DISTILLATE. If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. COMBUSTIBLE. Keep away from heat and open flame. Use with adequate ventilation. Avoid prolonged contact with skin and breathing of vapor or spray mist. Do not transfer contents to bottles or other unlabeled containers. Close container after each use.

KEEP OUT OF THE REACH OF CHILDREN.