

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist. Wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

FIRST AID

If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

If in eyes: Flush with plenty of water. Get medical attention.

If on skin: Wash with plenty of soap and water. Get medical attention.

If inhaled: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS

Flammable. Keep away from heat and open flame.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Stir thoroughly both before and during application, and allow 4-6 hours drying time between coats and before launching. It is not advisable to delay launching longer than 24 hours. For wooden hulls apply to bare wood or to a surface properly prepared by sanding, wire brushing, and cleaning. For best results two coats should be applied, and on new work no less than three coats. No other primer should be used. For application to metal hulls, apply first several coats of underwater primer. No thinner is normally needed. . . #7 Thinner may be used to wash brushes or replace solvent lost by evaporation.

ANALYSIS

PIGMENT 54.82%	
Red Iron Oxide	8.27%
Carbon Oxide	46.55%
Waxes from Copra	
Cade	2.53%
Cade or barite	2.38%
Silica	2.30%
VEHICLE 38.05%	
Cumarone Indene	18.47%
Resin	4.40%
Hydrogenated Methyl Abletate	2.20%
Aliphatic and Aromatic Hydrocarbons	12.61%
	100.00%
	(R-73 C)

STORAGE AND DISPOSAL

PESTICIDE

CONTAINER

1 U.S. Gallon
3.785 LITERS

T CO.

JAN 18 1983

Mr. Theodore R. Hopper
Jotun Marine Coatings, Inc.
940 Key Highway
Baltimore, MD 21230

Dear Mr. Hopper:

Subject: Antifouling Paint Label Improvement Program
Sea Proof 4270 Tritox Red Anti-Fouling
EPA Registration No. 2568-8
Regatta Vinyltex 55 Fast Red Anti-Fouling
EPA Registration No. 2568-11
Your Submissions of January 6, 1982

The amendment referred to above, submitted in connection with registration under FIFRA sec. 3(c)(7)(A), is acceptable, provided that you:

1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data.
2. Make the labeling changes listed below before you release the product for shipment bearing the amended labeling:
 - a. For EPA Registration No. 2568-8, relocate the pesticide ingredient statement so that it in no way is obscured by background illustrations.
3. Submit five (5) copies of your final printed labeling before you release the product for shipment.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 5(e). Your release for shipment of the product bearing the amended labeling constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely yours,

Richard E. Mountfort
Product Manager (21)
Fungicide-Herbicide Branch
Registration Division (25-157)

Enclosure

REF ID: A66041 (7:00AM-20820:pg):Raven:477-013:1/14/83