

ESTABLISHED 1870

# REGATTA YACHT PAINT

3900

## Anti-Fouling RED LATEX\*

**CAUTION: KEEP OUT OF  
REACH OF CHILDREN. SEE BACK  
PANEL FOR OTHER CAUTIONS.**

1 U. S. QUART

.946 LITERS

ACTIVE INGREDIENTS	
Cuprous Oxide	35.1%
INERT INGREDIENTS	64.9%
	100.0%

ANALYSIS

Pigment	45.7%
Vehicle	54.3%
	100.0%
PIGMENT	
Cuprous Oxide	77.0%
Red Iron Oxide	7.7%
Magnesium Silicate	15.3%
	100.0%
VEHICLE	
Latex Solids	35.6%
Water	64.4%
	100.0%

NSDA Reg. No. 2568-40

### ANTI-FOULING LATEX

A break-through in formulating technique . . . the first commercial anti-fouling paint made on a water-dispersible latex base. Anti-Fouling Latex is hard and tough, easy to apply and may be used over most other anti-fouling coatings. Launch time is not critical . . . brushes and equipment may easily be cleaned with water.

**WARNING: PROTECT FROM FREEZING.**

### DIRECTIONS

**APPLICATION OVER ANTI-FOULING COATINGS** — Be sure old coating is in good condition — not cracked or peeling. Sand to remove any powdery, loose decomposed paint and any dried slime.

**WOODEN HULLS** — Apply directly to bare wood. Use at least 2 full wet coats.

**FIBREGLASS HULLS** — Sand thoroughly with medium grit paper and wash with 3830 Fibreglass Solvent Wash to remove all traces of mold release agent. Then apply 2 coats of Anti-Fouling Latex.

**METAL HULLS** — Clean surface thoroughly and apply 1 coat REGATTA Vinyltex Wash Primer, followed by a thick anti-corrosive "barrier" coating. Apply 2 coats of Anti-Fouling Latex.

**GENERAL** — Do not apply when temperature is below 50° F. Mix well before using. Brushes and equipment may be cleaned with water when the job is finished. Anti-Fouling Latex may be applied by brush, roller or spray — if thinning is needed for spray application, water should be used. Do not thin more than 10%. Allow 4 hours drying time between coats and at least 18 hours between final coat and launch. Launching may be delayed for several months with no adverse effect on anti-fouling efficiency.

**CAUTION! CONTAINS COMPOUNDS HARMFUL OR FATAL IF EATEN.** Do not apply on any interior surfaces of a dwelling, or a place used for the care of children, or on window sills, toys, cribs and other furniture which might be chewed by children. Avoid prolonged contact with skin. Wash thoroughly after handling and before eating or smoking. Keep container closed when not in use. **KEEP OUT OF THE REACH OF CHILDREN.** Use with adequate ventilation. Do not take internally.

**\*PATENT PENDING**  
The FIRST water-based  
Anti-Fouling Paint

MANUFACTURED BY

## BALTIMORE COPPER PAINT CO.

OLIVER REEDER & SON, INC.

PROPRIETORS

BALTIMORE, MD. 21230

NEW YORK, N.Y. 10038