

Regatta®

ESTABLISHED 1870

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS
(and Domestic Animals)**

WARNING

Causes eye and skin irritation. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Do not take internally. Harmful or fatal if swallowed. Do not breathe vapor or spray mist. USE WITH ADEQUATE VENTILATION. Wash thoroughly with soap and water after handling and before eating and smoking.

FIRST AID

In case of contact immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes call a physician. Remove and wash contaminated clothing before reuse. If swallowed drink 1 or 2 glasses of water and induce vomiting by placing finger in back of throat. Never give anything by mouth to an unconscious person. Get medical attention. If inhaled remove to fresh air. If not breathing give artificial respiration.

ENVIRONMENTAL HAZARDS

Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL OR CHEMICAL HAZARDS

Flammable. Keep away from heat or open flame.

Note—When product is used in confined areas or applied by spraying wear protective clothing and a pesticide respirator jointly approved by the Mining Enforcement and Safety Administration (formerly the U. S. Bureau of Mines) and by the National Institute for Occupational Safety and Health under the provisions of 30 CFR 11.

ACCEPTED
AUG 13 1980
Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the EPA Reg. No. 2568-41

3950

**BALTOPLATE RACING
ANTI-FOULING**

ACTIVE INGREDIENTS

Cuprous Oxide (Copper, as metal 37.29%) ... 41.19%
INERT INGREDIENTS 58.81%
100.00%

FLAMMABLE

KEEP OUT OF REACH OF CHILDREN.

WARNING!

**SEE SIDE PANEL FOR ADDITIONAL
PRECAUTIONARY STATEMENTS**

EPA Establishment No. 2568-MD-01
EPA Registration No. 2568-41



ANALYSIS

PIGMENT 63.05%	
Red Iron Oxide	4.07%
Cuprous Oxide	41.19%
Inerts from Cuprous Oxide	2.17%
Sodium Chromate	0.27%
Molybdenum Sulfide ...	14.00%
Silicates	1.35%
VEHICLE 36.95%	
Vinyl Chloride Resin ...	4.34%
Rosin	4.34%
Tricresyl Phosphate	1.58%
Aromatic Hydrocarbons ..	9.70%
Ketones	16.99%
	100.00%
	(V-146-B)

JOTUN BCP MARINE COATINGS

2568-41

08/13/1980

1/2

**It is a violation of Federal Law to use this product
in a manner inconsistent with its labeling.**

BALTOPLATE RACING ANTI-FOULING

Baltoplate Racing Anti-Fouling combines the fouling resistance of a premium quality anti-fouling finish with the smoothness and lubricity of a superior racing bottom finish in one coating.

Baltoplate Racing Anti-Fouling is unlike any bottom paint you have ever used. It dries to a dull, reddish-Brown finish. Sand it and watch an amazing change take place. What was a dull brown finish is now a gleaming, metallic finish which easily could be mistaken for a polished metal plate.

DIRECTIONS FOR USE

1. Baltoplate should not be applied over other anti-fouling coatings unless it is determined that the old finish is of the "vinyl" family and is in good condition. The old finish should be well sanded to remove any chalky film. However, Baltoplate should not be applied over vinyl anti-fouling paint containing organotin (T.B.T.O.).
2. Preparation of Surface:
 - (a) Fibreglass—Sand surface with #100 grit abrasive paper to completely remove the gloss of the gel coat. Rinse with #3830 Fibreglass Solvent Wash to remove any waxy, mold release agent.
 - (b) Wood—Surface should be clean and dry. Fill dents, gouges and surface irregularities with REGATTA #3709 White Surfacing Compound. Sand smooth.
 - (c) Metal—Consult REGATTA "Boat Paintenance" booklet for proper surface preparation and barrier coats for use under anti-fouling paints containing copper compounds.
3. Apply one heavy coat of Baltoplate Racing Anti-Fouling. Flow on with a minimum of brushing. Dry overnight.
4. Apply a second coat of Baltoplate Racing Anti-Fouling. This should be a somewhat thinner application than the first coat. Dry overnight before launching.
5. Prior to launch sand using either 500 grit wet or dry paper, or 180-240 grit dry paper. Try to sand to a smooth finish removing any brush marks that may be present.
6. Polish with fine bronze wool until a smooth, shiny, metallic surface is obtained.

STORAGE & DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

Do not reuse empty containers.

Wrap container and put in trash collection.

1 U.S. Gallon

3.785 LITERS



JOTUN — BALTIMORE COPPER PAINT CO.

501 KEY HIGHWAY BALTIMORE, MD. 21230 (301) 539-0045

2/2