

ESTABLISHED 1870

REGATTA YACHT PAINT

3018

FAF BLUE

Fiberglass Anti-Fouling

**CAUTION: KEEP OUT OF
REACH OF CHILDREN. SEE BACK
PANEL FOR OTHER CAUTIONS**

1 U.S. GALLON
3.785 LITERS

MANUFACTURED BY

BALTIMORE COPPER PAINT CO.

BALTIMORE, MD. 21230

NEW YORK, N.Y. 10038

ACTIVE INGREDIENTS
Cuprous Oxide 6.4%
Copper, as metal 12.4%
Bis (Tributyltin) Oxide 1.4%
INERT INGREDIENTS 52.2%
100.0%

ACCEPTED

November 3, 1972
UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGISTRATION
ED UNDER NO. 2568-45

ANALYSIS
PIGMENT—64.4%
Cuprous Oxide 46.4%
Titanium Dioxide, Type III 5.6%
Phthalocyanine Blue 1.0%
Inert Extenders 11.4%
VEHICLE—35.6%
Processed Rosin 16.3%
Coumarone-Indene Resin 4.7%
Bis (tributyltin) Oxide 1.4%
Aromatic Hydrocarbons 7.0%
Mineral Spirits 5.9%
Additives 0.3%
Total 100.0%
E.P.A. Reg. No. 2568-45

FAF has been formulated for use on glass. However, it will not adhere to primed metal or over a previous condition.

Stir thoroughly both by hand and machine—allowing 4 to 6 hours. It is not advisable to use a brush or spray gun. Ordinarily, no more than 10% REGATTA

Fiberglass. Sand the surface down carefully with 60 grit Solvent Wash and a brush. Then apply a gel-coat.

An alternate method is to Wash and 3351 Fiberglass. No necessity of sanding.

Wood. Apply three coats.

Metal. Apply one coat of REGATTA 3630/3631.

Previously Coated Surfaces. 3802 Xylol Solvent.

**CAUTION! COMBUSTIBLE
FLAME. CONTAINS
TOXIC MATERIALS.**
Do not use on interior surfaces
such as walls, ceilings, sills,
toys, cribs and other places
where vapor or spray mist
may be inhaled. Keep out of
reach of children. Wash hands
or on clothing. In case of
contact with soap and water.

Keep container closed. Do not
use open flame. Destroy if
empty.

1870

REGATTA PAINT

BLUE
Anti-Fouling

KEEP OUT OF
SEE BACK
CAUTIONS

LONG
ERS

ED BY

PER PAINT CO.

NEW YORK, N.Y. 10038

ACCEPTED

November 3, 1972

UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGISTRATION
ED UNDER NO. 2568-45

ANALYSIS

PIGMENT—44.4%	
Cuprous Oxide	46.4%
Titanium Dioxide, Type III	5.6%
Phthalocyanine Blue	1.0%
Inert Extenders	11.4%
VEHICLE—35.6%	
Processed Resin	16.3%
Coumarone-Indene Resin	4.7%
Bis (tributyltin) Oxide	1.4%
Aromatic Hydrocarbons	7.6%
Mineral Spirits	5.9%
Additives	0.3%

Total 100.0%

E.P.A. Reg. No. 2568-45

FAF has been formulated using modern resins, selected for maximum adhesion to fiberglass. However, it will give completely satisfactory results when used on wood, properly primed metal or over most types of a previous season's anti-fouling paint that is in good condition.

DIRECTIONS

Stir thoroughly both before and during application. Apply at least two coats—three on bare wood—allowing 4 to 6 hours drying time between coats and between final coat and launch. It is not advisable to delay launch more than 3 days after final coat. Apply by brush, roller, or spray gun. Ordinarily thinning is not necessary, but where it is desired, add not more than 10% REGATTA #3800 Thinner.

SURFACE PREPARATION

Fiberglass. Sand the bottom thoroughly, using medium grit (about #100) paper. Wipe down carefully with REGATTA 3830 Fiberglass Solvent Wash. Use generous quantities of Solvent Wash and clean rags in order to remove the wax-like substance from the fiberglass gel-coat.

An alternate method of surface preparation is to use REGATTA 3840 Fiberglass Pre-Prime Wash and 3351 Fiberglass No-Sand Primer according to directions, thereby avoiding the necessity of sanding.

Wood. Apply three coats of FAF directly to bare wood.

Metal. Apply one coat of REGATTA Vinyltex 50/51 Wash Primer followed by two coats of REGATTA 3630/3631 Epoxydur Black Mastic.

Previously Coated Surfaces. Sand thoroughly, then wipe down with #3800 Thinner or 3802 Xylol Solvent.

CAUTION! COMBUSTIBLE! DO NOT USE, POUR, SPILL OR STORE NEAR HEAT OR OPEN FLAME. CONTAINS COMPOUNDS HARMFUL OR FATAL IF SWALLOWED. Do not apply on any interior surfaces of a dwelling, or a place used for the care of children, or on window sills, toys, cribs and other furniture which might be chewed by children. Avoid breathing vapor or spray mist. Wash thoroughly after handling and before eating or smoking. **KEEP OUT OF REACH OF CHILDREN.** May be absorbed through skin. Do not get in eyes, on skin or on clothing. In case of contact, immediately remove contaminated clothing and wash with soap and water. Wash contaminated clothing before reuse. Causes skin irritation.

Keep container closed when not in use. Use with adequate ventilation. Do not reuse empty container. Destroy it by perforating or crushing. Burn or discard in a safe place.