

#2568-61

PUBLISHED 1970

ACTIVE INGREDIENTS

Cuprous Oxide (Copper as metal 30.75%) 33.97%  
Tributyltin Fluoride 1.94%

INERT INGREDIENTS

64.09%  
100.00%

ANALYSIS

PIGMENT 49.56%

Cuprous Oxide  
Tributyltin Fluoride  
Red Iron Oxide  
Zinc Oxide  
Inert Pigment

VEHICLE 50.44%

Chlorinated Rubber  
Rosin  
Tricresyl Phosphate  
Aromatic Hydrocarbons  
Additives

33.97%  
1.94%  
7.36%  
3.97%  
2.32%  
8.19%  
5.96%  
2.71%  
31.95%  
1.63%

100.00%

REGATTA is an anti-fouling paint based on Chlorinated Rubber. It may be used on wood, fiberglass, properly primed metal or most types of previous season's anti-fouling paint that is in good condition.

DIRECTIONS

Start painting late before and during application. Apply at least two coats—allowing 4 to 6 hours, or, no time between final coat and launch. It is not advisable to delay launch more than 3 days after final coat. Apply by brush, roller or spray gun. Ordinarily thinning is not necessary, but where it is desired, add not more than 10% Regatta 3602 Xylol Solvent.

SURFACE PREPARATION

FIBREGLASS: Sand to a fine finish, using medium grit (about #100) paper. Wipe down thoroughly with REGATTA 3630 Fibreglass Solvent Wash. Use generous quantities of Solvent Wash and clean rags in order to remove the wax-like substance from the fibreglass gel coat.

An alternate method of surface preparation is to use REGATTA 3640 Fibreglass Pre-Prime Wash and 3651 Fibreglass Primer according to directions, thereby avoiding the necessity of sanding.

WOOD: Apply three coats outboard only to bare wood. Allow 4-6 hours between coats.

METAL: Apply one coat of REGATTA 3651 Wash Primer followed by two coats of REGATTA 3630 3631 Epoxy Primer-Mastic.

PREVIOUSLY COATED SURFACES: Sand thoroughly, then wipe down with 3602 Xylol Solvent.


CAUTION! COMBUSTIBLE! DO NOT USE, POUR, SPILL OR STORE NEAR HEAT OR OPEN FLAME. CONTAINS COMPOUNDS HARMFUL OR FATAL IF SWALLOWED. Do not apply to any interior surfaces of a dwelling or a place used for the care of children, or on window sills, toys, cribs and other furniture which might be chewed by children. Avoid breathing vapor or spray mist. Wash thoroughly after handling and before eating or smoking. KEEP OUT OF REACH OF CHILDREN. May be absorbed through skin. Do not get in eyes, on skin or on clothing. In case of contact, immediately remove contaminated clothing and wash with soap and water. Wash contaminated clothing before reuse. Causes skin irritation.

Keep container closed when not in use. Use with adequate ventilation. Do not reuse empty container. Destroy it by perforating or crushing. Burn or discard in a safe place. Do not contaminate water by cleaning equipment or disposal of waste.

BEST DOCUMENT AVAILABLE



3



International

BEST AVAILABLE

**CAUTION! COMBUSTIBLE**

Keep away from heat and open flame. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use.

Use with adequate ventilation.

KEEP OUT OF THE REACH OF CHILDREN.

WIDE SPECTRUM

PART B

NET ONE U.S.C

100% PURE

100% PURE