

**ACCEPTED**  
 AUG 23 2004  
 Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 2568-93

HEALTH	3
ENVIRONMENT	3
PROTECTIVE EQUIPMENT	C

D.O.T. SHIPPING NAME: PAINT  
 D.O.T. HAZARD CLASS: UN1263  
 D.Q.T. HAZARD IDENTIFICATION NUMBER: 60A2000  
 E.P.A. REG. NO.: 2568-93  
 E.P.A. EST. NO.: 002568-LA-001  
 Jotun Paints, Inc.  
 9203 Highway 23  
 Belle Chasse, LA 70037

**STORAGE AND DISPOSAL**

DO NOT CONTAMINATE WATER, FOOD OR FEED BY STORAGE OR DISPOSAL. KEEP CONTAINER CLOSED WHEN NOT IN USE. IN CASE OF SPILLAGE, ABSORB WITH INERT MATERIAL AND DISPOSE OF IN ACCORDANCE WITH APPLICABLE REGULATIONS.

**PESTICIDE DISPOSAL**

PESTICIDE WASTES ARE TOXIC. IMPROPER DISPOSAL OF EXCESS PESTICIDE, SPRAY MIXTURE OR RINSATE IS A VIOLATION OF FEDERAL LAW. IF THESE WASTES CANNOT BE DISPOSED OF BY USE ACCORDING TO LABEL INSTRUCTIONS. CONTACT YOUR STATE PESTICIDE OR ENVIRONMENTAL CONTROL AGENCY, OR THE HAZARDOUS WASTE REPRESENTATIVE AT THE NEAREST EPA REGIONAL OFFICE FOR GUIDANCE.

**CONTAINER DISPOSAL**

TRIPLE RINSE, (OR EQUIVALENT) THEN OFFER FOR RECYCLING OR RECONDITIONING, OR PUNCTURE AND DISPOSE OF IN A SANITARY LANDFILL, OR BY OTHER APPROVED STATE AND LOCAL PROCEDURES.



**ANTI-FOULING  
 HYDROCLEAN LOW VOC  
 RED  
 60A2000**

ACTIVE INGREDIENT: CUPROUS OXIDE..... 44.59%  
 INERT INGREDIENTS:..... 55.41%  
 ..... 100.00%

KEEP OUT OF THE REACH OF CHILDREN.

**WARNING  
 CONTAINS PETROLEUM DISTILLATES.**

FOR COMMERCIAL USE ONLY. DO NOT USE IN OR AROUND A HOUSEHOLD OR DWELLING.

NOT SOLD FOR USE IN AIR POLLUTION REGULATION AREAS. PHOTOCHEMICALLY REACTIVE PER RULE 102.

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

Net 5 Gallons (18.925 Liters)

**PRECAUTIONARY STATEMENTS  
 HAZARDS TO HUMANS & DOMESTIC ANIMALS**

**WARNING**

CAUSES EYE IRRITATION. HARMFUL IF ABSORBED THROUGH THE SKIN.

AVOID CONTACT WITH EYES, SKIN AND CLOTHING. WEAR PROTECTIVE CLOTHING SUCH AS GLOVES, LONG-SLEEVED COTTON SHIRT, LONG PANTS, AND A HAT. MAY BE FATAL IF SWALLOWED OR INHALED. DO NOT BREATHE VAPORS OR SPRAY MIST. WHEN USED IN ENCLOSED AREAS, SPRAYING PAINT OR SANDING BOAT SURFACE, WEAR APPROPRIATE, PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) DURING AND AFTER APPLICATION UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS ARE BELOW APPLICABLE LEVELS.

**ENVIRONMENTAL HAZARDS**

THIS MATERIAL IS TOXIC TO FISH. DO NOT APPLY DIRECTLY TO WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTE. DO NOT ALLOW CHIPS AND DUST GENERATED DURING PAINT REMOVAL TO ENTER WATER. DISPOSE OF PAINT DEBRIS IN AN APPROVED LANDFILL.

PHYSICAL OR CHEMICAL HAZARDS  
 DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME.

FIRST AID PESTICIDE CLASS 3	
IF INHALED	REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. GET MEDICAL ATTENTION.
IF ON SKIN OR CLOTHING	IMMEDIATELY FLUSH SKIN WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHING AND SHOES. COVER THE IRRITATED SKIN WITH AN EMOLLIENT. WASH CLOTHING BEFORE REUSE. THOROUGHLY CLEAN SHOES BEFORE REUSE. GET MEDICAL ATTENTION.
IF IN EYES	HOLD EYES OPEN AND RINSE SLOWLY AND GENTLY FOR 15-20 MINUTES. REMOVE CONTACT LENSES IF PRESENT AFTER THE FIRST 5 MINUTES. CALL A POISON CONTROL CENTER OR DOCTOR FOR PRETREATMENT ADVICE.
IF SWALLOWED	DO NOT INDUCE VOMITING UNLESS DIRECTED TO DO SO BY MEDICAL PERSONNEL. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. IF LARGE QUANTITIES OF THIS MATERIAL ARE SWALLOWED, CALL A PHYSICIAN IMMEDIATELY. LOOSEN TIGHT CLOTHING SUCH AS A COLLAR, TIE, BELT OR WAISTBAND.

MEDICAL EMERGENCY NUMBER: 1-800-424-9300  
 PESTICIDE CLASS 3

NOTE TO PHYSICIAN  
 Contains petroleum distillate - vomiting may cause aspiration pneumonia

**DIRECTIONS FOR USE**

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.  
**ANTI-FOULING FOR METAL BOTTOMS:**  
 TO CONTROL THE ATTACHMENT OF MARINE FOULING, I.E. BARNACLES, GRASS, ALGAE, ETC. ON STEEL BOTTOMS IN SALT AND BRACKISH WATER WHICH WOULD SUSTAIN SUCH GROWTH. NOT RECOMMENDED FOR USE ON ALUMINUM. A MINIMUM OF TWO COATS IS RECOMMENDED FOR BEST PERFORMANCE.

**SURFACE PREPARATION:**

BEFORE APPLICATION OF ANTI-FOULING, ALL SURFACES MUST BE DRY AND CLEANED OF DIRT, DUST, OIL, RUST, LOOSE PAINT, SALT RESIDUES AND OTHER CONTAMINANTS. STEEL MUST BE COATED WITH A SUITABLE PRIMER OR ANTI-CORROSIVE BARRIER COATS. FOLLOW RESPIRATOR MANUFACTURER'S DIRECTIONS FOR USE. REMOVE CONTAMINATED CLOTHING AND WASH CLOTHING BEFORE RE-USE. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING AND BEFORE EATING, DRINKING, OR USING TOBACCO.

**MIXING:**

BEFORE USE POWER MIX OR BOX THE PAINT UNTIL THE PRODUCT IS UNIFORM. STIR THE PAINT AT INTERVALS DURING APPLICATION TO MAINTAIN UNIFORMITY.

**APPLICATION:**

APPLY BY BRUSH, ROLL, OR SPRAY. CONTENTS MAY BE APPLIED BY HOT SPRAY (TEMPERATURES NOT TO EXCEED 95 F) AIRLESS SPRAY OR REGULAR COLD SPRAY. APPLY A FULL WET COAT IN A DOUBLE CROSS HATCH PATTERN. DONOT PAINT IN COLD OR DAMP WEATHER.

**THINNING:**

NORMALLY NO THINNING REQUIRED. WHERE THINNING IS NECESSARY, USE THINNER 7-T-33, XYLENE.

**DRYING TIME:**

AT 70 F AND 50% RH, ALLOW AT LEAST 4 HOURS DRY TIME BETWEEN COATS, AND A MINIMUM OF 8 HOURS BEFORE RECOATING. REFER TO PRODUCT MATERIAL SAFETY DATA BULLETIN AVAILABLE UPON REQUEST FOR FURTHER SAFETY AND HANDLING INFORMATION.

THE VOC OF THIS PAINT IS 330 GRAMS/LITER (2.75 LBS./GAL.).

2568-93

08/23/2004

1/4

FLAMMABILITY	3
PROTECTIVE EQUIPMENT	C

D.O.T. SHIPPING NAME: PAINT  
 D.O.T. HAZARD CLASS: UN1263  
 D.O.T. HAZARD IDENTIFICATION NUMBER: FLAMMABLE LIQUID

60A2001  
 E.P.A. REG. NO.: 2568-93  
 E.P.A. EST. NO.: 002568-LA-001

Jotun Paints, Inc.  
 9203 Highway 23  
 Belle Chasse, LA 70037



### STORAGE AND DISPOSAL

DO NOT CONTAMINATE WATER, FOOD OR FEED BY STORAGE OR DISPOSAL. KEEP CONTAINER CLOSED WHEN NOT IN USE, IN CASE OF SPILLAGE, ABSORB WITH INERT MATERIAL AND DISPOSE OF IN ACCORDANCE WITH APPLICABLE REGULATIONS.

### PESTICIDE DISPOSAL

PESTICIDE WASTES ARE TOXIC. IMPROPER DISPOSAL OF EXCESS PESTICIDE, SPRAY MIXTURE OR RINSATE IS A VIOLATION OF FEDERAL LAW. IF THESE WASTES CANNOT BE DISPOSED OF BY USE ACCORDING TO LABEL INSTRUCTIONS, CONTACT YOUR STATE PESTICIDE OR ENVIRONMENTAL CONTROL AGENCY, OR THE HAZARDOUS WASTE REPRESENTATIVE AT THE NEAREST EPA REGIONAL OFFICE FOR GUIDANCE.

### CONTAINER DISPOSAL

TRIPLE RINSE, (OR EQUIVALENT) THEN OFFER FOR RECYCLING OR RECONDITIONING, OR PUNCTURE AND DISPOSE OF IN A SANITARY LANDFILL, OR BY OTHER APPROVED STATE AND LOCAL PROCEDURES.

# ANTI-FOULING HYDROCLEAN LOW VOC LIGHT RED 60A2001

ACTIVE INGREDIENT: CUPROUS OXIDE..... 44.59%  
 INERT INGREDIENTS:..... 55.41%  
 ..... 100.00%

KEEP OUT OF THE REACH OF CHILDREN.

## WARNING CONTAINS PETROLEUM DISTILLATES.

FOR COMMERCIAL USE ONLY. DO NOT USE IN OR AROUND A HOUSEHOLD OR DWELLING.

NOT SOLD FOR USE IN AIR POLLUTION REGULATION AREAS. PHOTOCHEMICALLY REACTIVE PER RULE 102.

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

Net 5 Gallons (18.925 Liters)

### PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS & DOMESTIC ANIMALS

## WARNING

CAUSES EYE IRRITATION. HARMFUL IF ABSORBED THROUGH THE SKIN.

AVOID CONTACT WITH EYES, SKIN AND CLOTHING. WEAR PROTECTIVE CLOTHING SUCH AS GLOVES, LONG-SLEEVED COTTON SHIRT, LONG PANTS, AND A HAT. MAY BE FATAL IF SWALLOWED OR INHALED. DO NOT BREATHE VAPORS OR SPRAY MIST. WHEN USED IN ENCLOSED AREAS, SPRAYING PAINT OR SANDING BOAT SURFACE, WEAR APPROPRIATE, PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) DURING AND AFTER APPLICATION UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS ARE BELOW APPLICABLE LEVELS.

### ENVIRONMENTAL HAZARDS

THIS MATERIAL IS TOXIC TO FISH. DO NOT APPLY DIRECTLY TO WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES. DO NOT ALLOW CHIPS AND DUST GENERATED DURING PAINT REMOVAL TO ENTER WATER. DISPOSE OF PAINT DEBRIS IN AN APPROVED LANDFILL.

PHYSICAL OR CHEMICAL HAZARDS  
 DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME.

### DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

### ANTI-FOULING FOR METAL BOTTOMS:

TO CONTROL THE ATTACHMENT OF MARINE FOULING, IE, BARNACLES, GRASS, ALGAE, ETC. ON STEEL BOTTOMS IN SALT AND BRACKISH WATER WHICH WOULD SUSTAIN SUCH GROWTH. NOT RECOMMENDED FOR USE ON ALUMINUM. A MINIMUM OF TWO COATS IS RECOMMENDED FOR BEST PERFORMANCE.

### SURFACE PREPARATION:

BEFORE APPLICATION OF ANTI-FOULING, ALL SURFACES MUST BE DRY AND CLEANED OF DIRT, DUST, OIL, RUST, LOOSE PAINT, SALT RESIDUES AND OTHER CONTAMINANTS. STEEL MUST BE COATED WITH A SUITABLE PRIMER OR ANTI-CORROSIVE BARRIER COATS. FOLLOW MANUFACTURER'S DIRECTIONS FOR USE. REMOVE CONTAMINATED CLOTHING AND WASH CLOTHING BEFORE RE-USE. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING AND BEFORE EATING, DRINKING, OR USING TOBACCO.

### MIXING:

BEFORE USE POWER MIX OR BOX THE PAINT UNTIL THE PRODUCT IS UNIFORM. STIR THE PAINT AT INTERVALS DURING APPLICATION TO MAINTAIN UNIFORMITY.

### APPLICATION:

APPLY BY BRUSH, ROLL, OR SPRAY. CONTENTS MAY BE APPLIED BY HOT SPRAY (TEMPERATURES NOT TO EXCEED 95 F) AIRLESS SPRAY OR REGULAR COLD SPRAY. APPLY A FULL WET COAT IN A DOUBLE CROSS HATCH PATTERN. DONOT PAINT IN COLD OR DAMP WEATHER.

### THINNING:

NORMALLY NO THINNING REQUIRED. WHERE THINNING IS NECESSARY, USE THINNER 7-T-33, XYLENE.

### DRYING TIME:

AT 70 F AND 50% R.H. ALLOW AT LEAST 4 HOURS DRY TIME BETWEEN COATS, AND A MINIMUM OF 8 HOURS BEFORE REFLOATING. REFER TO PRODUCT MATERIAL SAFETY DATA BULLETIN, AVAILABLE UPON REQUEST, FOR FURTHER SAFETY AND HANDLING INFORMATION.

THE VOC OF THIS PAINT IS 330 GRAMS/LITER (2.75 LBS./GAL.).

FIRST AID PESTICIDE CLASS 3	
IF INHALED	REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. GET MEDICAL ATTENTION.
IF ON SKIN OR CLOTHING	IMMEDIATELY FLUSH SKIN WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHING AND SHOES. COVER THE IRRITATED SKIN WITH AN EMOLLIENT. WASH CLOTHING BEFORE REUSE. THOROUGHLY CLEAN SHOES BEFORE REUSE. GET MEDICAL ATTENTION.
IF IN EYES	HOLD EYES OPEN AND RINSE SLOWLY AND GENTLY FOR 15-20 MINUTES. REMOVE CONTACT LENSES, IF PRESENT AFTER THE FIRST 5 MINUTES. CALL A POISON CONTROL CENTER OR DOCTOR FOR PRETREATMENT ADVICE.
IF SWALLOWED	DO NOT INDUCE VOMITING UNLESS DIRECTED TO DO SO BY MEDICAL PERSONNEL. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. IF LARGE QUANTITIES OF THIS MATERIAL ARE SWALLOWED, CALL A PHYSICIAN IMMEDIATELY. LOOSEN TIGHT CLOTHING SUCH AS A COLLAR, TIE, BELT OR WAISTBAND.
MEDICAL EMERGENCY NUMBER: 1-800-424-9300 PESTICIDE CLASS 3	
NOTE TO PHYSICIAN Contains petroleum distillate - vomiting may cause aspiration pneumonia	

HEALTH	3
FLAMMABILITY	3
REACTIVITY	1
PROTECTIVE EQUIPMENT	C

D.O.T. SHIPPING NAME: PAINT  
D.O.T. HAZARD CLASS: UN1263  
D.O.T. HAZARD IDENTIFICATION NUMBER: 60A2002  
E.P.A. REG. NO.: 2568-93  
E.P.A. EST. NO.: 002568-LA-001  
Jotun Paints, Inc.  
9203 Highway 23  
Belle Chasse, LA 70037



### STORAGE AND DISPOSAL

DO NOT CONTAMINATE WATER, FOOD OR FEED BY STORAGE OR DISPOSAL. KEEP CONTAINER CLOSED WHEN NOT IN USE. IN CASE OF SPILLAGE, ABSORB WITH INERT MATERIAL AND DISPOSE OF IN ACCORDANCE WITH APPLICABLE REGULATIONS.

### PESTICIDE DISPOSAL

PESTICIDE WASTES ARE TOXIC. IMPROPER DISPOSAL OF EXCESS PESTICIDE, SPRAY MIXTURE OR RINSATE IS A VIOLATION OF FEDERAL LAW. IF THESE WASTES CANNOT BE DISPOSED OF BY USE ACCORDING TO LABEL INSTRUCTIONS, CONTACT YOUR STATE PESTICIDE OR ENVIRONMENTAL CONTROL AGENCY, OR THE HAZARDOUS WASTE REPRESENTATIVE AT THE NEAREST EPA REGIONAL OFFICE FOR GUIDANCE.

### CONTAINER DISPOSAL

TRIPLE RINSE, (OR EQUIVALENT) THEN OFFER FOR RECYCLING OR RECONDITIONING, OR PUNCTURE AND DISPOSE OF IN A SANITARY LANDFILL, OR BY OTHER APPROVED STATE AND LOCAL PROCEDURES.

# ANTI-FOULING HYDROCLEAN LOW VOC BLUE 60A2002

ACTIVE INGREDIENT: CUPROUS OXIDE..... 44.59%  
INERT INGREDIENTS..... 55.41%  
..... 100.00%

KEEP OUT OF THE REACH OF CHILDREN.

## WARNING CONTAINS PETROLEUM DISTILLATES.

FOR COMMERCIAL USE ONLY. DO NOT USE IN OR AROUND A HOUSEHOLD OR DWELLING.

NOT SOLD FOR USE IN AIR POLLUTION REGULATION AREAS. PHOTOCHEMICALLY REACTIVE PER RULE 102.

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

Net 5 Gallons (18.925 Liters)

### PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS & DOMESTIC ANIMALS

## WARNING

CAUSES EYE IRRITATION. HARMFUL IF ABSORBED THROUGH THE SKIN.

AVOID CONTACT WITH EYES, SKIN AND CLOTHING. WEAR PROTECTIVE CLOTHING SUCH AS GLOVES, LONG-SLEEVED COTTON SHIRT, LONG PANTS, AND A HAT. MAY BE FATAL IF SWALLOWED OR INHALED. DO NOT BREATHE VAPORS OR SPRAY MIST. WHEN USED IN ENCLOSED AREAS, SPRAYING PAINT OR SANDING BOAT SURFACE, WEAR APPROPRIATE, PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) DURING AND AFTER APPLICATION UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS ARE BELOW APPLICABLE LEVELS.

#### ENVIRONMENTAL HAZARDS

THIS MATERIAL IS TOXIC TO FISH. DO NOT APPLY DIRECTLY TO WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES. DO NOT ALLOW CHIPS AND DUST GENERATED DURING PAINT REMOVAL TO ENTER WATER. DISPOSE OF PAINT DEBRIS IN AN APPROVED LANDFILL.

PHYSICAL OR CHEMICAL HAZARDS  
DO NOT USE OR STORE NEAR  
HEAT OR OPEN FLAME.

FIRST AID PESTICIDE CLASS 3	
IF INHALED	REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. GET MEDICAL ATTENTION.
IF ON SKIN OR CLOTHING	IMMEDIATELY FLUSH SKIN WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHING AND SHOES. COVER THE IRRITATED SKIN WITH AN EMOLLIENT. WASH CLOTHING BEFORE REUSE. THOROUGHLY CLEAN SHOES BEFORE REUSE. GET MEDICAL ATTENTION.
IF IN EYES	HOLD EYES OPEN AND RINSE SLOWLY AND GENTLY FOR 15-20 MINUTES. REMOVE CONTACT LENSES, IF PRESENT AFTER THE FIRST 5 MINUTES. CALL A POISON CONTROL CENTER OR DOCTOR FOR PRE-TREATMENT ADVICE.
IF SWALLOWED	DO NOT INDUCE VOMITING UNLESS DIRECTED TO DO SO BY MEDICAL PERSONNEL. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. IF LARGE QUANTITIES OF THIS MATERIAL ARE SWALLOWED, CALL A PHYSICIAN IMMEDIATELY. LOOSEN TIGHT CLOTHING SUCH AS A COLLAR, TIE, BELT OR WAISTBAND.
MEDICAL EMERGENCY NUMBER: 1-800-424-9300 PESTICIDE CLASS 3	
NOTE TO PHYSICIAN Contains petroleum distillate - vomiting may cause aspiration pneumonia	

### DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

#### ANTI-FOULING FOR METAL BOTTOMS:

TO CONTROL THE ATTACHMENT OF MARINE FOULING, I.E. BARNACLES, GRASS, ALGAE, ETC. ON STEEL BOTTOMS IN SALT AND BRACKISH WATER WHICH WOULD SUSTAIN GROWTH. NOT RECOMMENDED FOR USE ON ALUMINUM. A MINIMUM OF TWO COATS IS RECOMMENDED FOR BEST PERFORMANCE.

#### SURFACE PREPARATION:

BEFORE APPLICATION OF ANTI-FOULING, ALL SURFACES MUST BE DRY AND CLEANED OF DIRT, DUST, OIL, RUST, LOOSE PAINT, SALT RESIDUES AND OTHER CONTAMINANTS. STEEL MUST BE COATED WITH A SUITABLE PRIMER OR ANTICORROSIVE BARRIER COATS, FOLLOW RESPIRATOR MANUFACTURER'S DIRECTIONS FOR USE. REMOVE CONTAMINATED CLOTHING AND WASH CLOTHING BEFORE RE-USE. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING AND BEFORE EATING, DRINKING, OR USING TOBACCO.

#### MIXING:

BEFORE USE POWER MIX OR BOX THE PAINT UNTIL THE PRODUCT IS UNIFORM. STIR THE PAINT AT INTERVALS DURING APPLICATION TO MAINTAIN UNIFORMITY.

#### APPLICATION:

APPLY BY BRUSH, ROLL, OR SPRAY. CONTENTS MAY BE APPLIED BY HOT SPRAY (TEMPERATURES NOT TO EXCEED 95 F) AIRLESS SPRAY OR REGULAR COLD SPRAY. APPLY A FULL WET COAT IN A DOUBLE CROSS HATCH PATTERN. DONOT PAINT IN COLD OR DAMP WEATHER.

#### THINNING:


NORMALLY NO THINNING REQUIRED. WHERE THINNING IS NECESSARY, USE THINNER 7-T-33, XYLENE.

#### DRYING TIME:


AT 70 F AND 50% R.H. ALLOW AT LEAST 4 HOURS DRY TIME BETWEEN COATS, AND A MINIMUM OF 8 HOURS BEFORE REFLOATING. REFER TO PRODUCT MATERIAL SAFETY DATA BULLETIN, AVAILABLE UPON REQUEST, FOR FURTHER SAFETY AND HANDLING INFORMATION.

THE VOC OF THIS PAINT IS 330  
GRAMS/LITER (2.75 LBS./GAL.).

h/c



D.O.T. SHIPPING NAME: PAINT  
 D.O.T. HAZARD CLASS: UN1263  
 D.O.T. HAZARD IDENTIFICATION NUMBER: 1  
 IDENTIFICATION NUMBER: 60A2003  
 E.P.A. REG. NO.: 2568-93  
 E.P.A. EST. NO.: 002568-LA-001  
 Jotun Paints, Inc.  
 9203 Highway 23  
 Belle Chasse, LA 70037



**STORAGE AND DISPOSAL**

DO NOT CONTAMINATE WATER, FOOD OR FEED BY STORAGE OR DISPOSAL. KEEP CONTAINER CLOSED WHEN NOT IN USE. IN CASE OF SPILLAGE, ABSORB WITH INERT MATERIAL AND DISPOSE OF IN ACCORDANCE WITH APPLICABLE REGULATIONS.

**PESTICIDE DISPOSAL**  
 PESTICIDE WASTES ARE TOXIC. IMPROPER DISPOSAL OF EXCESS PESTICIDE, SPRAY MIXTURE OR RINSATE IS A VIOLATION OF FEDERAL LAW. IF THESE WASTES CANNOT BE DISPOSED OF BY USE ACCORDING TO LABEL INSTRUCTIONS, CONTACT YOUR STATE PESTICIDE OR ENVIRONMENTAL CONTROL AGENCY, OR THE HAZARDOUS WASTE REPRESENTATIVE AT THE NEAREST EPA REGIONAL OFFICE FOR GUIDANCE.

**CONTAINER DISPOSAL**  
 TRIPLE RINSE, (OR EQUIVALENT) THEN OFFER FOR RECYCLING OR RECONDITIONING, OR PUNCTURE AND DISPOSE OF IN A SANITARY LANDFILL, OR BY OTHER APPROVED STATE AND LOCAL PROCEDURES.

**ANTI-FOULING  
 HYDROCLEAN LOW VOC  
 BLACK  
 60A2003**

ACTIVE INGREDIENT: CUPROUS OXIDE..... 44.59%  
 INERT INGREDIENTS:..... 55.41%  
 ----- 100.00%

KEEP OUT OF THE REACH OF CHILDREN.

**WARNING  
 CONTAINS PETROLEUM DISTILLATES.**

FOR COMMERCIAL USE ONLY. DO NOT USE IN OR AROUND A HOUSEHOLD OR DWELLING.

NOT SOLD FOR USE IN AIR POLLUTION REGULATION AREAS. PHOTOCHEMICALLY REACTIVE PER RULE 102.

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

Net 5 Gallons (18.925 Liters)

**PRECAUTIONARY STATEMENTS  
 HAZARDS TO HUMANS & DOMESTIC ANIMALS**

**WARNING**

CAUSES EYE IRRITATION. HARMFUL IF ABSORBED THROUGH THE SKIN.

AVOID CONTACT WITH EYES, SKIN AND CLOTHING. WEAR PROTECTIVE CLOTHING SUCH AS GLOVES, LONG-SLEEVED COTTON SHIRT, LONG PANTS, AND A HAT. MAY BE FATAL IF SWALLOWED OR INHALED. DO NOT BREATHE VAPORS OR SPRAY MIST. WHEN USED IN ENCLOSED AREAS, SPRAYING PAINT OR SANDING BOAT SURFACE WEAR APPROPRIATE, PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) DURING AND AFTER APPLICATION UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS ARE BELOW APPLICABLE LEVELS.

**ENVIRONMENTAL HAZARDS**  
 THIS MATERIAL IS TOXIC TO FISH. DO NOT APPLY DIRECTLY TO WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES. DO NOT ALLOW CHIPS AND DUST GENERATED DURING PAINT REMOVAL TO ENTER WATER. DISPOSE OF PAINT DEBRIS IN AN APPROVED LANDFILL.

**PHYSICAL OR CHEMICAL HAZARDS**  
 DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME.

FIRST AID PESTICIDE CLASS 3	
IF INHALED:	REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. GET MEDICAL ATTENTION.
IF ON SKIN OR CLOTHING:	IMMEDIATELY FLUSH SKIN WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHING AND SHOES. COVER THE IRRITATED SKIN WITH AN EMOLLIENT. WASH CLOTHING BEFORE REUSE. THOROUGHLY CLEAN SHOES BEFORE REUSE. GET MEDICAL ATTENTION.
IF IN EYES:	HOLD EYES OPEN AND RINSE SLOWLY AND GENTLY FOR 15-20 MINUTES. REMOVE CONTACT LENSES, IF PRESENT AFTER THE FIRST 5 MINUTES. CALL A POISON CONTROL CENTER OR DOCTOR FOR PRETREATMENT ADVICE.
IF SWALLOWED:	DO NOT INDUCE VOMITING UNLESS DIRECTED TO DO SO BY MEDICAL PERSONNEL. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. IF LARGE QUANTITIES OF THIS MATERIAL ARE SWALLOWED, CALL A PHYSICIAN IMMEDIATELY. LOOSEN TIGHT CLOTHING SUCH AS A COLLAR, TIE, BELT OR WAISTBAND.
MEDICAL EMERGENCY NUMBER: 1-800-424-9300 PESTICIDE CLASS 3	
NOTE TO PHYSICIAN Contains petroleum distillate - vomiting may cause aspiration pneumonia	

**DIRECTIONS FOR USE**  
 IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

**ANTIFOULING FOR METAL BOTTOMS:**  
 TO CONTROL THE ATTACHMENT OF MARINE FOULING, I.E. BARNACLES, GRASS, ALGAE, ETC. ON STEEL BOTTOMS IN SALT AND BRACKISH WATER WHICH WOULD SUSTAIN SUCH GROWTH, NOT RECOMMENDED FOR USE ON ALUMINUM. A MINIMUM OF TWO COATS IS RECOMMENDED FOR BEST PERFORMANCE.

**SURFACE PREPARATION:**  
 BEFORE APPLICATION OF ANTI-FOULING, ALL SURFACES MUST BE DRY AND CLEANED OF DIRT, DUST, OIL, RUST, LOOSE PAINT, SALT RESIDUES AND OTHER CONTAMINANTS. STEEL MUST BE COATED WITH A SUITABLE PRIMER OR ANTICORROSIVE BARRIER COATS. FOLLOW MANUFACTURER'S DIRECTIONS FOR USE. REMOVE CONTAMINATED CLOTHING AND WASH CLOTHING BEFORE RE-USE. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING AND BEFORE EATING, DRINKING, OR USING TOBACCO.

**MIXING:**  
 BEFORE USE POWER MIX OR BOX THE PAINT UNTIL THE PRODUCT IS UNIFORM. STIR THE PAINT AT INTERVALS DURING APPLICATION TO MAINTAIN UNIFORMITY.

**APPLICATION:**  
 APPLY BY BRUSH, ROLL OR SPRAY. CONTENTS MAY BE APPLIED BY HOT SPRAY (TEMPERATURES NOT TO EXCEED 95 F) AIRLESS SPRAY OR REGULAR COLD SPRAY. APPLY A FULL WET COAT IN A DOUBLE CROSS HATCH PATTERN. DONOT PAINT IN COLD OR DAMP WEATHER.

**THINNING:**  
 NORMALLY NO THINNING REQUIRED. WHERE THINNING IS NECESSARY, USE THINNER 7-T-33, XYLENE.

**DRYING TIME:**  
 AT 70 F AND 50% RH, ALLOW AT LEAST 4 HOURS DRY TIME BETWEEN COATS, AND A MINIMUM OF 8 HOURS BEFORE REFLOATING. REFER TO PRODUCT MATERIAL SAFETY DATA BULLETIN, AVAILABLE UPON REQUEST, FOR FURTHER SAFETY AND HANDLING INFORMATION.

THE VOC OF THIS PAINT IS 330 GRAMS/LITER (2.75 LBS./GAL.).

4/14