

2568-93

10/4/2012

1/3



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON D C 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

ST Technical Associates, LLC
5 Rodgers Avenue
Milford, CT 06460-5230

OCT - 4 2012

Attention Patricia Turley

Subject Primary Brand Name Change to ANTIFOULING SEAFORCE 200 AV DARK RED
EPA Reg No 2568-93
Amendment Letter dated July 5, 2012

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act, as amended, is acceptable. The following changes to the container disposal section were also notice addition of "Fill the container 1/4 full with water and recap" as well as "Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal". The Agency has no objection to amending your label to correct the flash point in the Precautionary Statements and adding an Establishment Number. A stamped copy of the label is submitted with this letter.

If you have any questions concerning this letter, please contact Elizabeth Hernandez at (703) 347-0241

Sincerely,

A handwritten signature in black ink, appearing to read "M Swindell".

Marshall Swindell
Product Manager (33)
Regulatory Management Branch 1
Antimicrobials Division (7510C)

BATCH 51118419 DOM 12/01/2009

| | |
|----------------------|---|
| Health | 3 |
| Fire hazard | 3 |
| Reactivity | 1 |
| Protective Equipment | C |

STORAGE AND DISPOSAL

DO NOT CONTAMINATE WATER FOOD OR FEED BY STORAGE OR DISPOSAL KEEP CONTAINER CLOSED WHEN NOT IN USE IN CASE OF SPILLAGE ABSORB WITH INERT MATERIAL AND DISPOSE OF IN ACCORDANCE WITH APPLICABLE REGULATIONS

PESTICIDE DISPOSAL

PESTICIDE WASTES ARE TOXIC IMPROPER DISPOSAL OF EXCESS PESTICIDE SPRAY MIXTURE OR RINSATE IS A VIOLATION OF FEDERAL LAW IF THESE WASTES CANNOT BE DISPOSED OF BY USE ACCORDING TO LABEL INSTRUCTIONS CONTACT YOUR STATE PESTICIDE OR ENVIRONMENTAL CONTROL AGENCY OR THE HAZARDOUS WASTE REPRESENTATIVE AT THE NEAREST EPA REGIONAL OFFICE FOR GUIDANCE

DOT SHIPPING NAME PAINT


DOT HAZARD CLASS FLAMMABLE LIQUID

DOT HAZARD IDENTIFICATION NUMBER UN1263

3GEDRD

**EPA REG NO 2568 93
EPA EST NO 002568 LA 001**

**Jotun Paints, Inc
9203 Highway 23
Belle Chasse LA 70037**



**ANTIFOULING
SEAFORCE 200 AV
DARK RED**

ACTIVE INGREDIENT CUPROUS OXIDE
INERT INGREDIENTS

44.59%
55.41%
100.00%

* METALLIC COPPER EQUIVALENT 39.60%

**CONTAINS PETROLEUM DISTILLATES XYLENE OR XYLENE RANGE AROMATIC SOLVENTS

KEEP OUT OF THE REACH OF CHILDREN

WARNING

FOR COMMERCIAL USE ONLY DO NOT USE IN OR AROUND A HOUSEHOLD OR DWELLING

NOT SOLD FOR USE IN AIR POLLUTION REGULATION AREAS PHOTOCHEMICALLY REACTIVE PER RULE 102

SEE SIDE PANEL FOR FIRST AID AND ADDITIONAL PRECAUTIONARY STATEMENTS

Net 20 LITERS (5.28 GALLONS)

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS & DOMESTIC ANIMALS
WARNING**

CAUSES EYE IRRITATION
HARMFUL IF ABSORBED THROUGH SKIN

AVOID CONTACT WITH EYES SKIN AND CLOTHING WEAR PROTECTIVE CLOTHING SUCH AS GLOVES LONG SLEEVED COTTON SHIRT LONG PANTS AND HAT MAY BE FATAL IF SWALLOWED OR INHALED DO NOT BREATHE VAPORS OR SPRAY MIST WHEN USED IN ENCLOSED AREAS SPRAYING PAINT OR SANDING BOAT SURFACE WEAR APPROPRIATE PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) DURING AND AFTER APPLICATION UNLESS AIR MONITORING DEMONSTRATES VAPOR MIST LEVELS ARE BELOW APPLICABLE LEVELS

REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING AND BEFORE EATING DRINKING CHEWING GUM USING TOBACCO OR USING THE WASHROOM

ENVIRONMENTAL HAZARDS

THIS MATERIAL IS TOXIC TO FISH DO NOT APPLY DIRECTLY TO WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES DO NOT ALLOW CHIPS AND DUST GENERATED DURING PAINT REMOVAL TO ENTER WATER DISPOSE OF PAINT DEBRIS IN AN APPROVED LANDFILL

PHYSICAL OR CHEMICAL HAZARDS

COMBUSTIBLE DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME

| FIRST AID | |
|---|--|
| IF IN EYES | HOLD EYES OPEN AND RINSE SLOWLY AND GENTLY FOR 15-20 MINUTES REMOVE CONTACT LENSES IF PRESENT AFTER THE FIRST 5 MINUTES AND THEN CONTINUE RINSING CALL A POISON CONTROL CENTER OR DOCTOR FOR TREATMENT ADVICE |
| IF SWALLOWED | IMMEDIATELY CALL A POISON CONTROL CENTER OR DOCTOR DO NOT INDUCE VOMITING UNLESS TOLD TO DO SO BY A POISON CONTROL CENTER OR DOCTOR DO NOT GIVE ANY LIQUID TO THE PERSON DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON TAKE OFF CONTAMINATED CLOTHING RINSE SKIN IMMEDIATELY WITH PLENTY OF WATER FOR 15-20 MINUTES CALL A POISON CONTROL CENTER OR DOCTOR FOR TREATMENT ADVICE |
| IF ON SKIN OR CLOTHING | MOVE PERSON TO FRESH AIR IF PERSON IS NOT BREATHING CALL 911 OR AN AMBULANCE THEN GIVE ARTIFICIAL RESPIRATION PREFERABLY MOUTH TO MOUTH IF POSSIBLE CALL A POISON CONTROL CENTER OR DOCTOR FOR FURTHER TREATMENT ADVICE |
| IF INHALED | HAVE THE PRODUCT CONTAINER OR LABEL WITH YOU WHEN CALLING A POISON CONTROL CENTER OR DOCTOR OR GOING FOR TREATMENT |
| OTHER | |
| MEDICAL EMERGENCY NUMBER 1 800 424 9300 | |
| NOTE TO PHYSICIAN | |
| Contains Petroleum distillate - vomiting may cause aspiration pneumonia | |

ACCEPTED
OCT 24 2004
Under the Federal Insecticide Fungicide and Rodenticide Act, this product for the sale, distribution, or use is hereby approved.

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING

ANTIFOULING FOR METAL BOTTOMS

TO CONTROL THE ATTACHMENT OF MARINE FOULING IE BARNACLES GRASS ALGAE TUBE WORMS MUSSELS AND SNAILS ON HULLS OF BOATS AND VESSELS IN SALT BRACKISH AND FRESH WATER WHICH WOULD SUSTAIN SUCH GROWTH NOT RECOMMENDED FOR USE ON ALUMINUM A MINIMUM OF TWO COATS OF THIS PRODUCT IS RECOMMENDED FOR BEST PERFORMANCE

SURFACE PREPARATION

BEFORE APPLICATION OF ANTIFOULING ALL SURFACES MUST BE DRY AND CLEANED OF DIRT DUST OIL RUST LOOSE PAINT SALT RESIDUES AND OTHER CONTAMINANTS STEEL MUST BE COATED WITH A SUITABLE PRIMER OR ANTI CORROSIVE BARRIER COATS

MIXING

BEFORE USE POWER MIX OR BOX THE PAINT UNTIL THE PRODUCT IS UNIFORM STIR THE PAINT AT INTERVALS DURING APPLICATION TO MAINTAIN UNIFORMITY

APPLICATION

APPLY BY BRUSH ROLL OR SPRAY CONTENTS MAY BE APPLIED BY HOT SPRAY (TEMPERATURES NOT TO EXCEED 95°F) AIRLESS SPRAY OR REGULAR COLD SPRAY APPLY A FULL WET COAT IN A DOUBLE CROSSHATCH PATTERN DO NOT PAINT IN COLD OR DAMP WEATHER

THINNING

NORMALLY NO THINNING REQUIRED WHERE THINNING IS NECESSARY USE JOTUN THINNER 7

DRYING TIME

AT 70°F AND 50% R.H. ALLOW AT LEAST 4 HOURS DRY TIME BETWEEN COATS AND A MINIMUM OF 8 HOURS BEFORE IMMERSION

REFER TO PRODUCT MATERIAL SAFETY DATA BULLETIN AVAILABLE UPON REQUEST FOR FURTHER SAFETY AND HANDLING INFORMATION

**THE VOC OF THIS PAINT IS
330 GRAMS/LITER (2.75 LBS/GAL)**

2/3