



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, D.C. 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

ST Associates
c/o for Jotun Paints
5 Rogers Avenue
Milford, CT 06460-6436

DEC 15 2010

Attention: Pat Turley
Regulatory Specialist

Subject: Seavictor 50 Antifouling 60A5000 Dark Red 3GFDRD
EPA Reg. No. 2568-99
Notification Letter Dated October 27, 2010
EPA Received Date November 17, 2010

This will acknowledge receipt of your notification for the aforementioned product label, submitted under the provisions of FIFRA Section 3(c) (9). Based on a review of the submitted material, the following apply:

- Minor change in the DIRECTIONS FOR USE section

The Notification is in compliance with PR Notice 98-10 and is acceptable. This information has been made a part of your file.

If you have any questions concerning this letter, please contact Demson Fuller at (703) 308-8062.

Sincerely,


Marshall Swindell
Product Manager (33)
Regulatory Management Branch 1
Antimicrobials Division (7510C)

276

Print Form

Please read instructions on reverse before completing form.

Form Approved, OMB No. 2070-0080, Approval expires 2-21



United States
Environmental Protection Agency
Washington, DC 20460

Registration
 Amendment
 Other

OPP Identifier Number

Application for Pesticide - Section I

1. Company/Product Number Jotun Paints, Inc. / 2568-99		2. EPA Product Manager Marshall Swindell		3. Proposed Classification <input type="checkbox"/> None <input type="checkbox"/> Restrictive	
4. Company/Product (Name) Jotun Paints/ Seavictor 50 Antifouling 60A5000 Dark Red 3GFDRD		PM# 33			
5. Name and Address of Applicant (Include ZIP Code) Jotun Paints, Inc. 9203 Highway 23 Belle Chasse, LA 70037 <input type="checkbox"/> Check if this is a new address		6. Expedited Review. In accordance with FIFRA Section 3(c)(3) (b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____			

Section - II

<input type="checkbox"/> Amendment - Explain below.	<input type="checkbox"/> Final printed labels in response to Agency letter dated _____
<input type="checkbox"/> Resubmission in response to Agency letter dated _____	<input type="checkbox"/> "Me Too" Application.
<input checked="" type="checkbox"/> Notification - Explain below.	<input type="checkbox"/> Other - Explain below.

Explanation: Use additional page(s) if necessary. (For section I and Section II.)

Change of thinner name on label under THINNING paragraph of DIRECTIONS FOR USE

This notification is consistent with the provisions of PR Notice 98-10 and EPA regulations at 40 CFR 152.46, and no other changes have been made to the labeling or the confidential statement of formula of this product. I understand that it is violation of 18 U.S.C. Sec. 1001 to willfully make any false statement to the EPA. I further understand that if this notification is not consistent with the terms of PR Notice 98-10 and 40 CFR 152.46, this product may be in violation of FIFRA and I may be subject to enforcement action and penalties under sections 12 and 14 of FIFRA.

Section - III

1. Material This Product Will Be Packaged In:					
Child-Resistant Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Unit Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Water Soluble Packaging <input type="checkbox"/> Yes <input type="checkbox"/> Text <input type="checkbox"/> No	2. Type of Container <input type="checkbox"/> Metal <input type="checkbox"/> Plastic <input type="checkbox"/> Glass <input type="checkbox"/> Paper <input type="checkbox"/> Other (Specify) _____		
* Certification must be submitted		If "Yes" Unit Packaging wgt.	No. per container	If "Yes" Package wgt.	No. per container
3. Location of Net Contents Information <input type="checkbox"/> Label <input type="checkbox"/> Container		4. Size(s) Retail Container		5. Location of Label Directions <input type="checkbox"/> On Label <input type="checkbox"/> On Labeling accompanying product	
6. Manner in Which Label is Affixed to Product <input type="checkbox"/> Lithograph <input type="checkbox"/> Paper glued <input type="checkbox"/> Stenciled			<input type="checkbox"/> Other _____		

Section - IV

1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)					
Name Patricia A. Turley, Ph.D.		Title Regulatory Representative		Telephone No. (Include Area Code) 203-314-6096	
<p align="center">Certification</p> <p>I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.</p>					6. Date Application Received (Stamped)
2. Signature <i>Stanhope Turnbull/PAT</i>		3. Title Regulatory Coordinator/Laboratory Manager			
4. Typed Name Stanhope Turnbull, Ph.D.		5. Date 10/27/2010			



ST Technical Associates, LLC
Technical & Regulatory Communications

October 27, 2010

Document Processing Desk (NOTIF)
Office of Pesticide Programs (7504P)
Room S4900, 1 Potomac Yard
2777 S. Crystal Drive
Arlington, VA 22202-4501

Attention: Mr. Marshall Swindell
PM 33, Antimicrobial Division

Re: Notification of a minor label change per PR Notice 98-10
Product: Seavictor 50 Antifouling 60A5000 Dark Red 3GFDRD
Registration Number: **2568-99**
Service fee: not required for notification

Dear Mr. Swindell,

This notification is submitted on behalf of and at the request of Jotun Paints, Inc.

In accordance with PR Notice 98-10, Jotun Paints, Inc. is notifying the EPA of a minor label change in one paragraph under the DIRECTIONS FOR USE for Seavictor 50 Antifouling 60A5000 Dark Red (EPA Reg. No. 2568-99). In particular, the name of the thinner in the THINNING paragraph has been changed to: JOTUN THINNER 7. This replaces the previously specified name: THINNER NO. 7 XYLENE.

The following information is enclosed:

1. Form 8570-1 (Application form)
2. Copy of most recent EPA-stamped label showing changed wording
3. Letter of authorization for ST Technical Associates, LLC to act on Jotun Paint's behalf

Please feel free to contact me if you need more information or have any questions.

Sincerely,

Patricia A. Turley, Ph.D.
Regulatory Representative for Jotun Paints, Inc.
ST Technical Associates, LLC
5 Rogers Avenue
Milford, CT 06460-5230
Ph: 203-314-6096
Fax: 203-878-0114
Email: paturley@sttechnical.com

4 8 6



Jotun Paints

January 22, 2010

Document Processing Desk
Office of Pesticide Programs (7504P)
U.S. Environmental Protections Agency
1200 Pennsylvania Ave. NW
Washington, D. C. 20460

Re: Authorization of Regulatory Representative for Jotun Paints, Inc.

Dear Sir/Madam,

We wish to notify the USEPA's Office of Pesticide Programs that ST Technical Associates, LLC is authorized to act on behalf of Jotun Paints, Inc. in regulatory matters related to the registration of antifouling paint products in the United States. The primary contacts will be Dr. Patricia A. Turley and Dr. Bonnie B. Sandel. The address of their main office is:

ST Technical Associates, LLC
5 Rogers Avenue
Milford, CT 06460-6436

More detailed contact information will be provided in cover letters and application forms.

If there are any questions, please contact me.

Sincerely,

Name: Emile Oustalet
Title: President
Jotun Paints, Inc.

Cc: Patricia A. Turley

Jotun Paints, Inc.

P.O. Box 159
9203 Highway 23
Belle Chasse, LA 70037

Tel: 800.638.7756

Tel: 504.394.3538

Fax: 504.394.3726

Customer Service Fax: 504.207.3626

See 11/1/08 for change (11/1/2010)

BATCH 51118419 DOM 08/01/2008

Health	3
Fire hazard	3
Reactivity	1
Protective Equipment	x

STORAGE AND DISPOSAL

DO NOT CONTAMINATE WATER, FOOD OR FEED BY STORAGE OR DISPOSAL. KEEP CONTAINER CLOSED WHEN NOT IN USE. IN CASE OF SPILLAGE, ABSORB WITH INERT MATERIAL AND DISPOSE OF IN ACCORDANCE WITH APPLICABLE REGULATIONS.

PESTICIDE DISPOSAL

PESTICIDE WASTES ARE TOXIC. IMPROPER DISPOSAL OF EXCESS PESTICIDE, SPRAY MIXTURE OR RINSATE IS A VIOLATION OF FEDERAL LAW. IF THESE WASTES CANNOT BE DISPOSED OF BY USE ACCORDING TO LABEL INSTRUCTIONS, CONTACT YOUR STATE PESTICIDE OR ENVIRONMENTAL CONTROL AGENCY, OR THE HAZARDOUS WASTE REPRESENTATIVE AT THE NEAREST EPA REGIONAL OFFICE FOR GUIDANCE.

**CONTAINER DISPOSAL
NONREFILLABLE CONTAINER**

DO NOT REUSE OR REFILL THIS CONTAINER. OFFER FOR RECYCLING IF AVAILABLE. TRIPLE RINSE CONTAINER PROMPTLY AFTER EMPTYING. TRIPLE RINSE AS FOLLOWS: EMPTY THE REMAINING CONTENTS INTO APPLICATION EQUIPMENT OR A MIX TANK AND DRAIN FOR 10 SECONDS AFTER THE FLOW BEGINS TO DRIP. FILL THE CONTAINER 1/10TH FULL WITH THINNER AND RECAP. SHAKE FOR 10 SECONDS. POUR RINSATE INTO APPLICATION EQUIPMENT OR A MIX TANK OR STORE RINSATE FOR LATER USE OR RECYCLING. DRAIN FOR 10 SECONDS AFTER THE FLOW BEGINS TO DRIP. REPEAT THIS PROCEDURE TWO MORE TIMES. THEN OFFER THE CONTAINER FOR RECYCLING OR RECONDITIONING, OR PUNCTURE AND DISPOSE OF IN A SANITARY LANDFILL, OR BY OTHER APPROVED STATE AND LOCAL PROCEDURES.

D.O.T. SHIPPING NAME: PAINT

**D.O.T. HAZARD
CLASS: FLAMMABLE LIQUID**

**D.O.T. HAZARD
IDENTIFICATION NUMBER: UN1263**

3GFDRD

**E.P.A. REG. NO.: 2568-99
E.P.A. EST. NO.: 002568-LA-001**

**Jotun Paints, Inc.
9203 Highway 23
Belle Chasse, LA 70037**

**ACCEPTED
FOR COMMENT
EPA Letter Dat**

DEC 7 2008
Under the Federal Insecticide, and Fungicide, and Rodenticide Act, this product is registered under E.P.A. Reg. No. 2568-99

**SEAVICTOR 50
ANTIFOULING
60A5000
DARK RED
3GFDRD**

ACTIVE INGREDIENT: CUPROUS OXIDE.....39.59%*
ACTIVE INGREDIENT: 4,5-DICHLORO-2-N-OCTYL-4-ISOTHIAZOLIN-3-ONE.....2.19%
INERT INGREDIENTS.....58.22%**
.....100.00%

* METALLIC COPPER EQUIVALENT: 35.16%

** CONTAINS PETROLEUM DISTILLATES, XYLENE, OR XYLENE RANGE AROMATIC SOLVENTS

KEEP OUT OF THE REACH OF CHILDREN.

DANGER

FOR USE IN COMMERCIAL OR GOVERNMENT SHIPYARDS ONLY. NOT FOR USE BY PRIVATE APPLICATORS OR MARINAS. NOT FOR USE ON STATIONARY STRUCTURES.

NOT SOLD FOR USE IN AIR POLLUTION REGULATION AREAS. PHOTOCHEMICALLY REACTIVE PER RULE 102

SEE FIRST AID AND OTHER PRECAUTIONS ON SIDE PANEL.

Net 20 LITERS (5.28 GALLONS)

5
8
10

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS & DOMESTIC ANIMALS
DANGER**

CORROSIVE. CAUSES IRREVERSIBLE EYE DAMAGE. HARMFUL IF SWALLOWED OR ABSORBED THROUGH SKIN. AVOID CONTACT WITH EYES, SKIN, OR CLOTHING. WEAR A FULL FACE SHIELD. AVOID BREATHING VAPOR, MIST, DUST OR CHIPS FROM PAINTING OR SANDING WHILE SPRAYING PAINT OR SANDING BOAT SURFACE. WEAR A SUPPLIED-AIR OR POWERED AIR PURIFYING RESPIRATOR (PAPR) APPROVED BY NIOSH FOR USE WITH PAINTS AND COATINGS.

WEAR A TYVEK HOODED COVERALL OR THE EXACT EQUIVALENT, COVERALLS BENEATH THE TYVEK HOODED COVERALLS, IMPERVIOUS GLOVES AND IMPERVIOUS FOOTWEAR THAT PROTECTS THE LOWER LEG. REMOVE CONTAMINATED CLOTHING AND DISCARD AFTER EACH USE. DO NOT REUSE. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING AND BEFORE EATING OR SMOKING.

ENVIRONMENTAL HAZARDS

THIS PESTICIDE IS TOXIC TO FISH AND AQUATIC INVERTEBRATES. DO NOT DISCHARGE EFFLUENT CONTAINING THIS PRODUCT INTO LAKES, STREAMS, PONDS, ESTUARIES, OCEANS OR OTHER WATER UNLESS IN ACCORDANCE WITH THE REQUIREMENTS OF A NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM (NPDES) PERMIT AND THE PERMITTING AUTHORITY HAS BEEN NOTIFIED IN WRITING PRIOR TO DISCHARGE. DO NOT DISCHARGE EFFLUENT CONTAINING THIS PRODUCT TO SEWER SYSTEMS WITHOUT PREVIOUSLY NOTIFYING THE LOCAL SEWAGE TREATMENT PLANT AUTHORITY. FOR GUIDANCE CONTACT YOUR STATE WATER BOARD OR REGIONAL OFFICES OF THE EPA. DO NOT APPLY DIRECTLY TO WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES. DO NOT ALLOW CHIPS AND DUST GENERATED DURING PAINT REMOVAL TO ENTER WATER. DISPOSE OF PAINT DEBRIS IN AN APPROVED LANDFILL. WEAR PROTECTIVE CLOTHING AND SUPPLIED AIR RESPIRATOR IN ACCORDANCE WITH THE PRECAUTIONARY STATEMENTS ABOVE WHEN HANDLING, PAINTING OR REMOVING THIS PAINT.

PHYSICAL OR CHEMICAL HAZARDS

COMBUSTIBLE. DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME.

FIRST AID	
IF IN EYES:	HOLD EYES OPEN AND RINSE SLOWLY AND GENTLY FOR 15-20 MINUTES. REMOVE CONTACT LENSES, IF PRESENT, AFTER THE FIRST 5 MINUTES, AND THEN CONTINUE RINSING. CALL A POISON CONTROL CENTER OR DOCTOR FOR TREATMENT ADVICE.
IF SWALLOWED:	IMMEDIATELY CALL A POISON CONTROL CENTER OR DOCTOR. DO NOT INDUCE VOMITING UNLESS TOLD TO DO SO BY A POISON CONTROL CENTER OR DOCTOR. DO NOT GIVE ANY LIQUID TO THE PERSON. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
IF ON SKIN OR CLOTHING:	TAKE OFF CONTAMINATED CLOTHING. RINSE SKIN IMMEDIATELY WITH PLENTY OF WATER FOR 15-20 MINUTES. CALL A POISON CONTROL CENTER OR DOCTOR FOR TREATMENT ADVICE.
IF INHALED:	MOVE A PERSON TO FRESH AIR. IF PERSON IS NOT BREATHING, CALL 911 OR AN AMBULANCE, THEN GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH-TO-MOUTH IF POSSIBLE. CALL A POISON CONTROL CENTER OR DOCTOR FOR FURTHER TREATMENT ADVICE.
OTHER:	HAVE THE PRODUCT CONTAINER OR LABEL WITH YOU WHEN CALLING A POISON CONTROL CENTER OR DOCTOR, OR GOING FOR TREATMENT.
MEDICAL EMERGENCY NUMBER: 1-800-424-8300	
NOTE TO PHYSICIAN	
Contains petroleum distillate - vomiting may cause aspiration pneumonia.	

Under the Federal Insecticide, Fungicide, and Rodenticide Act, amended for the pesticide registered under: EPA 2562-99

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

ANTIFOULING FOR METAL BOTTOMS

TO CONTROL THE ATTACHMENT OF MARINE FOULING, I.E., BARNACLES, GRASS, ALGAE, TUBE WORMS, MUSSELS, AND SNAILS ON HULLS OF BOATS AND VESSELS IN SALT, BRACKISH AND FRESH WATER WHICH WOULD SUSTAIN SUCH GROWTH. WHEN USED ON ALUMINUM HULLS, A BARRIER COAT OF TWO COATS OF EPOXY COATING ATTAINING AT LEAST 12 MILS DFT MUST BE APPLIED FIRST. CONSULT WITH YOUR REPRESENTATIVE FOR SPECIFIC BARRIER RECOMMENDATIONS. A MINIMUM OF TWO COATS OF THIS PRODUCT IS RECOMMENDED FOR BEST PERFORMANCE. THIS PRODUCT IS NOT FOR USE ON PLEASURE CRAFTS OR USE IN MARINAS.

SURFACE PREPARATION

BEFORE APPLICATION OF ANTIFOULING, ALL SURFACES MUST BE DRY AND CLEANED OF DIRT, DUST, OIL, RUST, LOOSE PAINT, SALT RESIDUES AND OTHER CONTAMINANTS. STEEL MUST BE COATED WITH A SUITABLE PRIMER OR ANTI-CORROSIVE BARRIER COATS.

MIXING

BEFORE USE, POWER MIX OR BOX THE PAINT UNTIL THE PRODUCT IS UNIFORM. STIR THE PAINT AT INTERVALS DURING APPLICATION TO MAINTAIN UNIFORMITY.

APPLICATION

APPLY BY BRUSH, ROLL, OR SPRAY. CONTENTS MAY BE APPLIED BY HOT SPRAY (TEMPERATURES NOT TO EXCEED 95°F) AIRLESS SPRAY OR REGULAR COLD SPRAY. APPLY A FULL WET COAT IN A DOUBLE CROSSHATCH PATTERN. DO NOT PAINT IN COLD OR DAMP WEATHER.

THINNING

NORMALLY NO THINNING REQUIRED. WHERE THINNING IS NECESSARY, USE THINNER NO. 7 XYLENE. **

DRYING TIME

AT 70°F AND 50% R.H. ALLOW AT LEAST 4 HOURS DRY TIME BETWEEN COATS, AND A MINIMUM OF 8 HOURS BEFORE IMMERSION.

REFER TO PRODUCT MATERIAL SAFETY DATA BULLETIN, AVAILABLE UPON REQUEST, FOR FURTHER SAFETY AND HANDLING INFORMATION.

**THE VOC OF THIS PAINT IS
396 GRAMS/LITER (3.3 LBS/GAL).**

** Notified change under "THINNING" - substitute "JOTUN THINNER 7" for "THINNER NO. 7 XYLENE"