

2568-102

12-12-2007

1/4



U.S. ENVIRONMENTAL PROTECTION AGENCY

Office of Pesticide Programs
Antimicrobials Division (7510C)
1200 Pennsylvania Avenue NW
Washington, D.C. 20460

EPA Reg. Number:
2568-102

Date of Issuance:
DEC 12 2007

Term of Issuance:

Name of Pesticide Product: **Antifouling
Seaforce 100 AV Dark Red
3GCDRD**

NOTICE OF PESTICIDE:
 Registration
 Reregistration

(under FIFRA, as amended)

Name and Address of Registrant (include ZIP Code):

Jotun Paints, Inc.
9203 Highway 23
Belle Chasse, LA 70037

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec 3(c)(7)(A) provided that you:

1. Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for re-registration of your product under FIFRA section 4.
2. Make the labeling changes listed below before you release the product for shipment:
 - a. Add the phrase "EPA Registration Number 2568-102."

Signature of Approving Official:

Marshall Swindell
Product Manager-33
Regulatory Management Branch I
Antimicrobials Division (7510P)

Date:
DEC 12 2007


3. The Confidential Statement of Formula dated December 06, 2007, is acceptable.

4. Submit three (3) copies of the final printed label prior to releasing this product for sale.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely,



Marshall Swindell
Product Manager 33
Regulatory Branch I
Antimicrobials Division (7510P)

Enclosure: (Stamped Labeling)

Health	3
Fire hazard	3
Reactivity	1
Protective Equipment	C

D.O.T. SHIPPING NAME: PAINT

D.O.T. HAZARD
CLASS: FLAMMABLE LIQUID

D.O.T. HAZARD
IDENTIFICATION NUMBER: UN1263

3GCDRD

E.P.A. REG. NO.: 2568-
E.P.A. EST. NO.: 002568-LA-001

Jotun Paints, Inc.
9203 Highway 23
Belle Chasse, LA 70037

ACCEPTED
with COMMENTS
in EPA Letter Dated:
DEC 12 2007

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

2568-102

STORAGE AND DISPOSAL

DO NOT CONTAMINATE WATER,
FOOD OR FEED BY STORAGE OR
DISPOSAL. KEEP CONTAINER
CLOSED WHEN NOT IN USE. IN
CASE OF SPILLAGE, ABSORB
WITH INERT MATERIAL AND
DISPOSE OF IN ACCORDANCE
WITH APPLICABLE REGULATIONS

PESTICIDE DISPOSAL

PESTICIDE WASTES ARE TOXIC.
IMPROPER DISPOSAL OF EXCESS
PESTICIDE, SPRAY MIXTURE OR
RINSATE IS A VIOLATION OF
FEDERAL LAW. IF THESE WASTES
CANNOT BE DISPOSED OF BY
USE ACCORDING TO LABEL
INSTRUCTIONS, CONTACT YOUR
STATE PESTICIDE OR
ENVIRONMENTAL CONTROL
AGENCY, OR THE HAZARDOUS
WASTE REPRESENTATIVE AT
THE NEAREST EPA REGIONAL
OFFICE FOR GUIDANCE.

CONTAINER DISPOSAL

TRIPLE RINSE, (OR EQUIVALENT)
THEN OFFER FOR RECYCLING
OR RECONDITIONING, OR
PUNCTURE AND DISPOSE OF IN A
SANITARY LANDFILL, OR BY
OTHER APPROVED STATE AND
LOCAL PROCEDURES.

ANTIFOULING SEAFORCE 100 AV DARK RED 3GCDRD

ACTIVE INGREDIENT: CUPROUS OXIDE.....31.94%*
INERT INGREDIENTS.....68.06%
.....100.00%

*METALLIC COPPER EQUIVALENT: 29.59%

**KEEP OUT OF THE REACH OF CHILDREN
WARNING**

CONTAINS PETROLEUM DISTILLATES
FOR COMMERCIAL USE ONLY. DO NOT USE IN OR
AROUND A HOUSEHOLD OR DWELLING.

NOT SOLD FOR USE IN AIR POLLUTION REGULATION AREAS.
PHOTOCHEMICALLY REACTIVE PER RULE 102

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

Net 20 LITERS (5.28 GALLONS)

ACCEPTED
with COMMENTS
in EPA Letter Dated:

DEC 12 2007

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended for the pesticide,
registered under EPA Reg. No.

2568-102

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS & DOMESTIC ANIMALS

WARNING

CAUSES EYE IRRITATION. HARMFUL IF
ABSORBED THROUGH THE SKIN.

AVOID CONTACT WITH EYES, SKIN AND CLOTHING. WEAR PROTECTIVE CLOTHING SUCH AS GLOVES, LONG-SLEEVED COTTON SHIRT, LONG PANTS, AND A HAT. MAY BE FATAL IF SWALLOWED OR INHALED. DO NOT BREATHE VAPORS OR SPRAY MIST. WHEN USED IN ENCLOSED AREAS, SPRAYING PAINT OR SANDING BOAT SURFACE, WEAR APPROPRIATE PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) DURING AND AFTER APPLICATION UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS ARE BELOW

ENVIRONMENTAL HAZARDS

THIS MATERIAL IS TOXIC TO FISH. DO NOT APPLY DIRECTLY TO WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES. DO NOT ALLOW CHIPS AND DUST GENERATED DURING PAINT REMOVAL TO ENTER WATER. DISPOSE OF PAINT DEBRIS IN AN APPROVED LANDFILL.

PHYSICAL OR CHEMICAL HAZARDS

DO NOT USE OR STORE NEAR
HEAT OR OPEN FLAME.

FIRST AID PESTICIDE CLASS 3	
IF INHALED:	REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. GET MEDICAL ATTENTION.
IF ON SKIN OR CLOTHING:	IMMEDIATELY FLUSH SKIN WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHING AND SHOES. COVER THE IRRITATED SKIN WITH AN EMOLLIENT. WASH CLOTHING BEFORE REUSE. THOROUGHLY CLEAN SHOES BEFORE REUSE. GET MEDICAL ATTENTION.
IF IN EYES:	HOLD EYES OPEN AND RINSE SLOWLY AND GENTLY FOR 15-20 MINUTES. REMOVE CONTACT LENSES, IF PRESENT AFTER THE FIRST 5 MINUTES. CALL A POISON CONTROL CENTER OR DOCTOR FOR PRETREATMENT ADVICE.
IF SWALLOWED:	DO NOT INDUCE VOMITING UNLESS DIRECTED TO DO SO BY MEDICAL PERSONNEL. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. IF LARGE QUANTITIES OF THIS MATERIAL ARE SWALLOWED, CALL A PHYSICIAN IMMEDIATELY. LOOSEN TIGHT CLOTHING SUCH AS A COLLAR, TIE, BELT OR WAISTBAND.
MEDICAL EMERGENCY NUMBER: 1-800-424-9300 PESTICIDE CLASS 3	
NOTE TO PHYSICIAN Contains petroleum distillate - vomiting may cause aspiration pneumonia.	

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

ANTIFOULING FOR METAL BOTTOMS

TO CONTROL THE ATTACHMENT OF MARINE FOULING, IE., BARNACLES, GRASS, ALGAE, ETC. ON STEEL BOTTOMS IN SALT AND BRACKISH WATER WHICH WOULD SUSTAIN SUCH GROWTH. NOT RECOMMENDED FOR USE ON ALUMINUM. A MINIMUM OF TWO COATS IS RECOMMENDED FOR BEST PERFORMANCE.

SURFACE PREPARATION

BEFORE APPLICATION OF ANTI-FOULING, ALL SURFACES MUST BE DRY AND CLEANED OF DIRT, DUST, OIL, RUST, LOOSE PAINT, SALT RESIDUES AND OTHER CONTAMINANTS. STEEL MUST BE COATED WITH A SUITABLE PRIMER OR ANTI-CORROSIVE BARRIER COATS. FOLLOW RESPIRATOR MANUFACTURER'S DIRECTIONS FOR USE. REMOVE CONTAMINATED CLOTHING AND WASH CLOTHING BEFORE RE-USE. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING AND BEFORE EATING, DRINKING, OR USING TOBACCO.

MIXING

BEFORE USE POWER MIX OR BOX THE PAINT UNTIL THE PRODUCT IS UNIFORM. STIR THE PAINT AT INTERVALS DURING APPLICATION TO MAINTAIN UNIFORMITY.

APPLICATION

APPLY BY BRUSH, ROLL OR SPRAY. CONTENTS MAY BE APPLIED BY HOT SPRAY (TEMPERATURES NOT TO EXCEED 95°F, AIRLESS SPRAY OR REGULAR COLD SPRAY. APPLY A FULL WET COAT IN A DOUBLE CROSSHATCH PATTERN. DO NOT PAINT IN COLD OR DAMP WEATHER.

THINNING

NORMALLY NO THINNING REQUIRED. WHERE THINNING IS NECESSARY, USE THINNER 7-T-33, XYLENE.

DRYING TIME

AT 70°F AND 50% R.H. ALLOW AT LEAST 4 HOURS DRY TIME BETWEEN COATS, AND A MINIMUM OF 8 HOURS BEFORE REFLOATING.

REFER TO PRODUCT MATERIAL SAFETY DATA BULLETIN, AVAILABLE UPON REQUEST, FOR FURTHER SAFETY AND HANDLING INFORMATION

THE VOC OF THIS PAINT IS 395
GRAMS/LITER (3.30 LBS./GAL.).