UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, D.C. 20460



EPA United States Environmental Protection Office of Pesticide Programs

Jotun Paints, Inc. 9203 Highway 23 Belle Chasse, LA 70037

FEB 2 4 2009

AGENT: ST Technical Associates, LLC

5 Rogers Avenue

Milford, CT 06460-5230

Attention: Patricia A. Turley, Ph.D.

Subject: Antifouling Seaforce 100 AV Dark Red 3GCDRD

EPA Registration No. 2568-102

Amendments Dated February 11, 2009

The amendment, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, is acceptable.

- Updated First Aid statements

- Container Disposal/Residue Removal Language

A stamped copy of the "accepted" label is enclosed for your records.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely

Marshall Swindell

Product Manager (33)

Regulatory Management Branch 1 Antimorobials Division (7510P)

Enclosure

BATCH 51118419 DOM 12/01/2008

Health	3
Fire hazard	3
Reactivity	1
Protective Equipment	С

D.O.T. SHIPPING NAME: PAINT

D.O.T. HAZARD CLASS: FLAMMABLE LIQUID

D.O.T. HAZARD
IDENTIFICATION NUMBER: UN1263

3GCDRD

E.P.A. REG. NO.: 2568-102 E.P.A. EST. NO.: 002568-LA-001

> Jotun Paints, Inc. 9203 Highway 23 Belle Chasse, LA 70037

ACCEPTED with COMMENTS EPA Letter Dated:

FEB 2 4 2009

der the Federal Insecticide, agicide, and Rodenticide Act as ended, for the pesticide, pistered under EPA Reg. No. 2568-102

STORAGE AND DISPOSAL

DO NOT CONTAMINATE WATER, FOOD OR FEED BY STORAGE OR DISPOSAL. KEEP CONTAINER CLOSED WHEN NOT IN USE. IN CASE OF SPILLAGE, ABSORB WITH INERT MATERIAL AND DISPOSE OF IN ACCORDANCE WITH APPLICABLE REGULATIONS.

PESTICIDE DISPOSAL

PESTICIDE WASTES ARE TOXIC. IMPROPER DISPOSAL OF EXCESS PESTICIDE, SPRAY MIXTURE OR RINSATE IS A VIOLATION OF FEDERAL LAW. IF THESE WASTES CANNOT BE DISPOSED OF BY USE ACCORDING TO LABEL INSTRUCTIONS, CONTACT YOUR STATE PESTICIDE OR ENVIRONMENTAL CONTROL AGENCY, OR THE HAZARDOUS WASTE REPRESENTATIVE AT THE NEAREST EPA REGIONAL OFFICE FOR GUIDANCE.

CONTAINER DISPOSAL NONREFILLABLE CONTAINER

DO NOT REUSE OR REFILL THIS CONTAINER. OFFER FOR RECYCLING IF AVAILABLE. TRIPLE RINSE CONTAINER PROMPTLY AFTER EMPTY-ING. TRIPLE RINSE AS FOLLOWS: EMPTY THE REMAINING CONTENTS INTO APPLICATION EQUIPMENT OR A MIX TANK AND DRAIN FOR 10 SECONDS AFTER THE FLOW BEGINS TO DRIP. FILL THE CONTAINER 1/10TH FULL WITH THINNER AND RECAP. SHAKE FOR 10 SECONDS. POUR RINSATE INTO APPLICATION EQUIPMENT OR A MIX TANK OR STORE RINSATE FOR LATER USE OR RECYCLING, DRAIN FOR 10 SECONDS AFTER THE FLOW BEGINS TO DRIP. REPEAT THIS PROCEDURE TWO MORE TIMES. THEN OFFER THE CONTAINER FOR RECYCLING OR RECONDITIONING, OR PUNCTURE AND DISPOSE OF IN A SANITARY LANDFILL. OR BY OTHER APPROVED STATE AND LOCAL PROCEDURES.

ANTIFOULING SEAFORCE 100 AV DARK RED 3GCDRD

ACTIVE INGREDIENT: CUPROUS OXIDE	31.94%*
INERT INGREDIENTS	68.06%**
	100.00%

- METALLIC COPPER EQUIVALENT: 28.37%
- ** CONTAINS PETROLEUM DISTILLATES, XYLENE, OR XYLENE RANGE AROMATIC SOLVENTS

KEEP OUT OF THE REACH OF CHILDREN.

WARNING

FOR COMMERCIAL USE ONLY. DO NOT USE IN OR AROUND A HOUSEHOLD OR DWELLING.

NOT SOLD FOR USE IN AIR POLLUTION REGULATION AREAS. PHOTOCHEMICALLY REACTIVE PER RULE 102

SEE SIDE PANEL FOR FIRST AID AND ADDITIONAL PRECAUTIONARY STATEMENTS

Net 20 LITERS (5.28 GALLONS)

ACCEPTED with COMMENTS EPA Letter Dated:

FEB 2 4 2009

Under the Federal Insectional To Humans & DOMESTIC ANIMALS

Fungicide, and Rodenticide Act as amended, for the pesticide.

WARNING

registered under EPA Reg. No. 2568-102 CAUSES EYE IRRITATION.
HARMFUL IF ABSORBED THROUGH SKIN.

AVOID CONTACT WITH EYES, SKIN AND CLOTHING. WEAR PROTECTIVE CLOTHING SUCH AS GLOVES, LONG-SLEEVED COTTON SHIRT, LONG PANTS, AND HAT. MAY BE FATAL IF SWALLOWED OR INHALED. DO NOT BREATHE VAPORS OR SPRAY MIST. WHEN USED IN ENCLOSED AREAS, SPRAYING PAINT OR SANDING BOAT SURFACE. WEAR APPROPRIATE PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) DURING AND AFTER APLICATION UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS ARE BELOW APPLICABLE LEVELS.

REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING AND BEFORE EATING, DRINKING, CHEWING GUM, USING TOBACCO OR USING THE WASHROOM.

ENVIRONMENTAL HAZARDS

THIS MATERIAL IS TOXIC TO FISH. DO NOT APPLY DIRECTLY TO WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES. DO NOT ALLOW CHIPS AND DUST GENERATED DURING PAINT REMOVAL TO ENTER WATER, DISPOSE OF PAINT DEBRIS IN AN APPROVED LANDFILL.

PHYSICAL OR CHEMICAL HAZARDS

FLAMMABLE. DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME.

FIRST AID			
	HOLD EYES OPEN AND RINSE SLOWLY AND GENTLY FOR 15-20 MINUTES. REMOVE		
IF IN EYES:	CONTACT LENSES, IF PRESENT, AFTER THE FIRST 5 MINUTES, AND THEN CONTINUE		
L	RINSING. CALL A POISON CONTROL CENTER OR DOCTOR FOR TREATMENT ADVICE.		
	IMMEDIATELY CALL A POISON CONTROL CENTER OR DOCTOR. DO NOT INDUCE VOMITING		
l IF	UNLESS TOLD TO DO SO BY A POISON CONTROL CENTER OR DOCTOR, DO NOT GIVE ANY		
SWALLOWED:	LIQUID TO THE PERSON. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSIOUS PERSON.		
IE ON OKUL OR	TAKE OFF CONTAMINATED CLOTHING. RINSE SKIN IMMEDIATELY WITH PLENTY OF WATER		
IF ON SKIN OR	FOR 15-20 MINUTES. CALL A POISON CONTROL CENTER OR DOCTOR FOR TREATMENT		
CLOTHING:	ADVICE.		
IF INHALED:	MOVE PERSON TO FRESH AIR. IF PERSON IS NOT BREATHING, CALL 911 OR AN AMBULANCE,		
	THEN GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH-TO-MOUTH IF POSSIBLE. CALL A		
	POISON CONTROL CENTER OR DOCTOR FOR FURTHER TREATMENT ADVICE.		
OTHER:	HAVE THE PRODUCT CONTAINER OR LABEL WITH YOU WHEN CALLING A POISON CONTROL		
	CENTER OR DOCTOR, OR GOING FOR TREATMENT.		
	MEDICAL EMERGENCY NUMBER: 1-800-424-9300		
NOTE TO PHYSICIAN			
Contains petroleum distillate – vomiting may cause aspiration pneumonia.			

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

ANTIFOULING FOR METAL BOTTOMS

TO CONTROL THE ATTACHMENT OF MARINE FOULING, IE., BARNACLES, GRASS, ALGAE, TUBE WORMS, MUSSELS, AND SNAILS ON HULLS OF BOATS AND VESSELS IN SALT, BRACKISH AND FRESH WATER WHICH WOULD SUSTAIN SUCH GROWTH. NOT RECOMMENDED FOR USE ON ALUMINUM. A MINIMUM OF TWO COATS OF THIS PRODUCT IS RECOMMENDED FOR BEST PERFORMANCE.

SURFACE PREPARATION

BEFORE APPLICATION OF ANTIFOULING, ALL SURFACES MUST BE DRY AND CLEANED OF DIRT, DUST, OIL, RUST, LOOSE PAINT, SALT RESIDUES AND OTHER CONTAMINANTS. STEEL MUST BE COATED WITH A SUITABLE PRIMER OR ANTI-CORROSIVE BARRIER COATS.

MIXING

BEFORE USE, POWER MIX OR BOX THE PAINT UNTIL THE PRODUCT IS UNIFORM. STIR THE PAINT AT INTERVALS DURING APPLICATION TO MAINTAIN UNIFORMITY.

APPLICATION

APPLY BY BRUSH, ROLL, OR SPRAY. CONTENTS MAY BE APPLIED BY HOT SPRAY (TEMPERATURES NOT TO EXCEED 95°F) AIRLESS SPRAY OR REGULAR COLD SPRAY. APPLY A FULL WET COAT IN A DOUBLE CROSSHATCH PATTERN. DO NOT PAINT IN COLD OR DAMP WEATHER.

THINNING

NORMALLY NO THINNING REQUIRED. WHERE THINNING IS NECESSARY, USE THINNER 7-T-33, XYLENE.

DRYING TIME

AT 70°F AND 50% R.H. ALLOW AT LEAST 4 HOURS DRY TIME BETWEEN COATS, AND A MINIMUM OF 8 HOURS BEFORE IMMERSION.

REFER TO PRODUCT MATERIAL SAFETY DATA BULLETIN, AVAILABLE UPON REQUEST, FOR FURTHER SAFETY AND HANDLING INFORMATION.

THE VOC OF THIS PAINT IS 395 GRAMS/LITER (3.3 LBS/GAL).