

2568-103

7/15/2015

1/3



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY  
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY  
AND POLLUTION PREVENTION

July 15, 2015

Patricia A. Turley  
Regulatory Representative for Jotun Paints, Inc.  
Jotun Paints, Inc.  
Belle Chasse, LA  
70037

Subject: Label Notification per PRN 98-10 – To improve clarification and make  
minor corrections  
Product Name: SEAQUANTUM ULTRA SP Light Red  
EPA Registration Number: 2568-103  
Application Date: June 11, 2015  
Decision Number: 505977

Dear Ms. Turley:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide  
Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division  
has conducted a review of this request for its applicability under PRN 98-10 and finds that the  
action requested falls within the scope of PRN 98-10.

The Label submitted with the application has been stamped "Notification" and will be placed in  
our records

If you have any questions, you may contact Zebora Johnson at (703) 308-7080 or via email at  
Johnson.zebora@epa.gov.

Sincerely,

A handwritten signature in black ink, appearing to read "John Hebert".

John Hebert, Chief  
Regulatory Management Branch I  
Antimicrobials Division (7510P)  
Office of Pesticide Programs

## STORAGE AND DISPOSAL

DO NOT CONTAMINATE WATER, FOOD OR FEED BY STORAGE OR DISPOSAL.

### STORAGE

KEEP THE CONTAINERS IN A DRY, COOL, WELL VENTILATED SPACE AND AWAY FROM SOURCES OF HEAT AND IGNITION. CONTAINERS MUST BE KEPT TIGHTLY CLOSED. HANDLE WITH CARE.

### PESTICIDE DISPOSAL

PESTICIDE WASTES ARE TOXIC. IMPROPER DISPOSAL OF EXCESS PESTICIDE, SPRAY MIXTURE OR RINSATE IS A VIOLATION OF FEDERAL LAW. IF THESE WASTES CANNOT BE DISPOSED OF BY USE ACCORDING TO LABEL INSTRUCTIONS, CONTACT YOUR STATE PESTICIDE OR ENVIRONMENTAL CONTROL AGENCY, OR THE HAZARDOUS WASTE REPRESENTATIVE AT THE NEAREST EPA REGIONAL OFFICE FOR GUIDANCE.

### CONTAINER DISPOSAL

NONREFILLABLE CONTAINER. DO NOT REUSE OR REFILL THIS CONTAINER. PRIOR TO CONTAINER DISPOSAL, ALLOW ANY REMAINING PAINT RESIDUE IN THE CONTAINER TO AIR DRY. DISPOSE OF THE CONTAINER IN ACCORDANCE WITH FEDERAL, STATE OR LOCAL DISPOSAL REGULATIONS.

### FIRST AID

|                         |   |
|-------------------------|---|
| IF IN EYES:             | HOLD EYE OPEN AND RINSE SLOWLY AND GENTLY WITH WATER FOR 15-20 MINUTES. REMOVE CONTACT LENSES, IF PRESENT, AFTER THE FIRST 5 MINUTES, AND THEN CONTINUE RINSING. CALL A POISON CONTROL CENTER OR DOCTOR FOR TREATMENT ADVICE.                                     |
| IF SWALLOWED:           | CALL A POISON CONTROL CENTER OR DOCTOR IMMEDIATELY FOR TREATMENT ADVICE. HAVE PERSON SIP A GLASS OF WATER IF ABLE TO SWALLOW. DO NOT INDUCE VOMITING UNLESS TOLD TO BY A POISON CONTROL CENTER OR DOCTOR. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. |
| IF ON SKIN OR CLOTHING: | TAKE OFF CONTAMINATED CLOTHING. RINSE SKIN IMMEDIATELY WITH PLENTY OF WATER FOR 15-20 MINUTES. CALL A POISON CONTROL CENTER OR DOCTOR FOR TREATMENT ADVICE.   |
| IF INHALED:             | MOVE PERSON TO FRESH AIR. IF PERSON IS NOT BREATHING, CALL 911 OR AN AMBULANCE, THEN GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH-TO-MOUTH IF POSSIBLE. CALL A POISON CONTROL CENTER OR DOCTOR FOR FURTHER TREATMENT ADVICE.                                     |

**NOTE TO PHYSICIAN:** EYE SYMPTOMS CAN INCLUDE CORNEAL OPACITY AND CONJUNCTIVITIS. CONTAINS PETROLEUM DISTILLATES - VOMITING MAY CAUSE ASPIRATION PNEUMONIA. PROBABLE MUCOSAL DAMAGE MAY CONTRAINDICATE THE USE OF GASTRIC LAVAGE.

**GENERAL INFORMATION:** HAVE THE PRODUCT CONTAINER OR LABEL WITH YOU WHEN CALLING A POISON CONTROL CENTER OR DOCTOR OR GOING FOR TREATMENT. FOR NON-EMERGENCY OR GENERAL INFORMATION PERTAINING TO THIS PRODUCT, CALL THE NATIONAL PESTICIDES INFORMATION CENTER AT 1-800-858-7378 (NPIC WEB SITE: WWW.NPIC.ORG.EDU). FOR EMERGENCIES, CALL THE POISON CONTROL CENTER 1-800-222-1222.

## RESTRICTED USE PESTICIDE

Due to hazards to nontarget species and potential dermal and inhalation health risks when proper PPE or application methods are not used. For sale to Certified Applicators or persons under their direct supervision, and only for those uses covered by the Certified Applicator's certification.

# SEAQUANTUM ULTRA SP

## Light Red

### ACTIVE INGREDIENTS:

|                   |          |
|-------------------|----------|
| CUPROUS OXIDE     | 48.20%*  |
| COPPER PYRITHIONE | 2.23%    |
| OTHER INGREDIENTS | 49.57%** |
|                   | 100.00%  |

\*METALLIC COPPER EQUIVALENT: 43.2%

\*\*CONTAINS PETROLEUM DISTILLATES, XYLENE, OR XYLENE RANGE AROMATIC SOLVENTS.

## KEEP OUT OF THE REACH OF CHILDREN.

## WARNING

ONLY FOR USE ON VESSELS GREATER THAN 25 METERS (82 FEET) IN LENGTH.

SEE SIDE PANELS FOR FIRST AID AND ADDITIONAL PRECAUTIONARY STATEMENTS

### Net 20 LITERS (5.28 GALLONS)

E.P.A. REG. NO.: 2568-103  
E.P.A. EST. NO.: 002568-LA-001

Jotun Paints, Inc.  
9203 Highway 23  
Belle Chase, LA 70037

BATCH 51118419 DOM 08/01/2014

# PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS & DOMESTIC ANIMALS WARNING

**WARNING.** CAUSES SUBSTANTIAL BUT TEMPORARY EYE INJURY. HARMFUL IF SWALLOWED, ABSORBED THROUGH SKIN OR INHALED. DO NOT GET IN EYES OR ON CLOTHING. WEAR APPROPRIATE PROTECTIVE EYEWEAR SUCH AS GOGGLES, FACE SHIELD OR SAFETY GLASSES. AVOID CONTACT WITH SKIN. AVOID BREATHING SPRAY MIST. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING AND BEFORE EATING, DRINKING, CHEWING GUM, USING TOBACCO OR USING THE TOILET. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.

**PERSONAL PROTECTIVE EQUIPMENT (PPE)**  
**PPE MUST BE WORN WHEN APPLYING THIS PRODUCT:**

- **SPRAY APPLICATORS** SHALL WEAR NIOSH-APPROVED CONTINUOUS FLOW SUPPLIED AIR OR POWERED AIR PURIFYING RESPIRATORS EQUIPPED WITH A HOOD THAT COVERS THE FACE, NECK, AND SHOULDERS. THE POWERED AIR PURIFYING RESPIRATOR SHALL BE USED WITH AN ORGANIC VAPOR CARTRIDGE AND A HIGH EFFICIENCY (HEPA) PRE-FILTER. THE SPRAY APPLICATORS SHALL WEAR SAFETY GLASSES BENEATH THE HOOD RESPIRATOR.
- **LINE TENDERS AND POT TENDERS** SHALL WEAR NIOSH-APPROVED ELASTOMERIC HALF OR FULL FACE PURIFYING RESPIRATORS WITH ORGANIC VAPOR CARTRIDGES AND P100 PRE-FILTERS. THE LINE TENDERS AND POT TENDERS SHALL WEAR SHIELDED SAFETY GLASSES OR GOGGLES IF THE HALF FACE RESPIRATORS ARE WORN. SAFETY GLASSES OR GOGGLES ARE NOT REQUIRED IF FULL FACE RESPIRATORS ARE WORN.
- **SRAY APPLICATORS, LINE TENDERS AND POT TENDERS** SHALL WEAR DISPOSABLE TYVEK HOODED COVERALLS, OR EXACT EQUIVALENT, COVERALLS OR LONG-SLEEVED SHIRT, LONG PANTS, SOCKS BENEATH THE TYVEK HOODED COVERALL, PROTECTIVE EYEWEAR, CHEMICAL-RESISTANT GLOVES THAT ARE DISPOSABLE, AND CHEMICAL-RESISTANT FOOTWEAR THAT PROTECTS THE LOWER LEG.

**USER SAFETY RECOMMENDATIONS:** WASH THE OUTSIDE OF GLOVES BEFORE REMOVING.

**APPLICATION / ENTRY.** DO NOT APPLY THIS PRODUCT IN A WAY THAT WILL EXPOSE WORKERS OR OTHER PERSONS, EITHER DIRECTLY OR THROUGH DRIFT. ONLY PROTECTED HANDLERS MAY BE IN AREA DURING APPLICATION. DO NOT ENTER OR ALLOW OTHERS TO ENTER UNTIL SPRAYS HAVE DRIED.

### ENVIRONMENTAL HAZARDS

THIS MATERIAL IS TOXIC TO FISH AND AQUATIC INVERTEBRATES. DO NOT APPLY DIRECTLY TO WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES. DO NOT ALLOW CHIPS AND DUST GENERATED DURING PAINT REMOVAL TO ENTER WATER. DISPOSE OF PAINT DEBRIS IN AN APPROVED LANDFILL. DO NOT DISCHARGE EFFLUENT CONTAINING THIS PRODUCT INTO LAKES, STREAMS, PONDS, ESTUARIES, OCEANS OR OTHER WATERS UNLESS IN ACCORDANCE WITH THE REQUIREMENTS OF A NATIONAL POLLUTION DISCHARGE ELIMINATION SYSTEM (NPDES) PERMIT AND THE PERMITTING AUTHORITY HAS BEEN NOTIFIED IN WRITING PRIOR TO DISCHARGE. DO NOT DISCHARGE EFFLUENT INTO SEWER SYSTEMS WITHOUT PREVIOUSLY NOTIFYING THE LOCAL SEWAGE TREATMENT PLANT AUTHORITY. FOR GUIDANCE CONTACT YOU STATE WATER BOARD OR REGIONAL OFFICE OF THE EPA.

### PHYSICAL OR CHEMICAL HAZARDS

**FLAMMABLE.** KEEP AWAY FROM HEAT AND OPEN FLAME.

## DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

**Only For Use On Vessels Greater Than 25 Meters (82 Feet) In Length.**

### ANTIFOULING FOR METAL BOTTOMS

TO CONTROL THE ATTACHMENT OF MARINE FOULING, I.E., BARNACLES, GRASS, ALGAE, TUBE WORMS, MUSSELS, AND SNAILS ON HULLS OF BOATS AND VESSELS IN ALL WATERS WHICH WOULD SUSTAIN SUCH GROWTH WHEN USED ON ALUMINUM HULLS, A BARRIER COAT OF TWO COATS OF EPOXY COATING ATTAINING AT LEAST 10 MILS DFT MUST BE APPLIED FIRST. CONSULT WITH YOUR REPRESENTATIVE FOR SPECIFIC BARRIER RECOMMENDATIONS. A MINIMUM OF TWO COATS OF THIS PRODUCT IS RECOMMENDED FOR BEST PERFORMANCE. THIS PRODUCT IS NOT FOR USE IN MARINAS.

### SURFACE PREPARATION

BEFORE APPLICATION OF ANTI FOULING, ALL SURFACES MUST BE DRY AND CLEANED OF DIRT, DUST, OIL, RUST, LOOSE PAINT, SALT RESIDUES AND OTHER CONTAMINANTS. STEEL MUST BE COATED WITH A SUITABLE PRIMER OR ANTI-CORROSIVE BARRIER COATS.

### MIXING

BEFORE USE, POWER MIX THE PAINT UNTIL THE PRODUCT IS UNIFORM.

### APPLICATION

APPLY BY BRUSH, ROLLER, OR AIRLESS SPRAY. FOR BRUSH AND ROLLER, CARE MUST BE TAKEN TO ACHIEVE THE SPECIFIED DRY FILM THICKNESS. FOR AIRLESS SPRAY, THE FOLLOWING IS SUGGESTED: NOZZLE TIP (INCH/1000) = 17 - 31; PRESSURE AT NOZZLE (MINIMUM) = 150 BAR / 2100 PSI.

### THINNING

NORMALLY NO THINNING REQUIRED. WHERE THINNING IS NECESSARY, USE JOTUN THINNER 7.

### DRYING TIME

AT 70°F AND 50% RH ALLOW AT LEAST 7 HOURS DRY TIME BETWEEN COATS, AND A MINIMUM OF 9 HOURS BEFORE LAUNCHING.

REFER TO THE TECHNICAL DATA SHEET FOR ADDITIONAL APPLICATION DETAILS AND THE MATERIAL SAFETY DATA SHEET FOR FURTHER SAFETY AND HANDLING INFORMATION.

## NOTIFICATION

2568-103

**THE VOC OF THIS PAINT IS  
380 GRAMS/LITER (3.17 LBS/GAL).**

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

07/15/2015