

To treat posts and lumber:  
Have posts and heavy timbers  
free of bark, dry and well-sea-  
soned. Dip or submerge wood  
in PENTA GARD. Allow at  
least five minutes of dipping or  
submerging for every inch thick-  
ness of wood. If posts and  
heavy timbers are to contact  
soil, bury them to 18 inches.

Several applications of PENTA GARD  
may be made with a paint brush if  
dipping or submerging is impractical.  
Posts or lumber which will contact  
the soil should have several free  
flowing applications of PENTA  
GARD attempting to saturate the  
wood as much as possible. The  
effectiveness of PENTA GARD will  
be proportionate to the quantity  
absorbed by the wood. Therefore  
the longer the wood is submerged  
in the vat or the more applications  
made with a brush, the greater the  
effectiveness.

NOTICE: Seller makes no  
warranty, expressed or implied,  
concerning the use of this product  
other than indicated on the label.  
Buyer assumes all risk of use and/or  
handling of this material when such  
use or handling is contrary to label  
instructions.

EPA REG. No. 2666-70

## PENTA GARD 5

**WARNING! Keep Out of Reach of Children.**  
See side panel for additional warnings.

CORNELL PENTA-GARD 5 is a ready-to-use  
material, designed to control wood rotting fungi  
and wood penetrating insects, such as Powder  
Post Beetles, Termites and Carpenter Ants.

**ACTIVE INGREDIENTS:**

Pentachlorophenol  
Other chlorophenols & related  
compounds

Polyphenol Hydrocarbons

**INERT INGREDIENTS:**

TOTAL

ACCEPTED	4.15
NOV 27 1972	
100% T.C.P.	95.00
10% T.C.P.	2.50
10% ATTACHED COTTON	2.50

Meets Federal Specification TT-W-570

**WARNING:**

Harmful or fatal if swallowed or  
absorbed through the skin. Can  
cause skin irritations. Do not  
breathe vapor, fumes or spray  
mist. Do not get in eyes, on skin  
or clothing. In case of contact with  
skin, wash off with plenty of soap  
and water. In case of spillage on  
clothes, change clothes immediately.

Wash thoroughly after handling.

Wear protective clothing and  
rubber gloves when handling the  
freshly treated lumber.

In case of swallowing, induce  
vomiting by administering mustard  
and water or emetic. Call a  
physician immediately.

Do not contaminate or store with  
food and feedstuffs. Keep away  
from fires. Give little heat.

Do not puncture container or  
drum. Return to original condition  
or destroy by cutting or crushing  
and burying in a safe place away from  
water supplies.