

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

WASHINGTON, D.C. 20460

OFFICE OF CHEMICAL SAFETY AND POLLUTION PREVENTION

Hydrite Chemical Company 300 North Patrick Blvd. Brookfield, WI 53045

OCT 14 2011

Attention: Mary Bluemner Registration Specialist

Subject:

Amendment to revise label - Sustain No. 464

EPA Reg. No. 2686-19

Amendment Application Dated September 8, 2011

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, is acceptable. The Agency approves the following changes made to the label:

- 1. Addition of Final Sanitizing Beverage Container Rinse directions
- 2. Revision of the heading, "For Food and Dairy Processing Equipment, Tanks, Vats, Pails, Pipelines, and Closed Systems" to include "/Beverage, Wine"
- 3. In Dilution Instructions, change "Circulate the" to "Expose equipment to"
- 4. In Dilution Instructions, remove the sentence, "The sanitizing solution should have a pH of less than 4 if mineral scale control is desired" as this language is redundant.
- 5. Change placement of the heading "Note:"
- 6. Addition of the sentence "KEEP PRODUCT AWAY FROM HEAT OR DIRECT SUNLIGHT"

A stamped copy of the accepted labeling is enclosed. Submit three copies of your final printed labeling to the Agency before distributing or selling the product bearing the revised labeling. If you have any questions concerning this letter, please contact Abigail Downs at (703) 305-5259.

Sincerely,

Marshall Swindell

Product Manager (33)

Regulatory Management Branch I Antimicrobials Division (7510P)

EPRECAUTIONARY STATEMENTS

B HAZARD TO HUMANS AND DOMESTIC ANIMALS

DANGER CORROSIVE: Do not enter an enclosed area where this product has been applied without proper respiratory protection. Causes irreversible eye damage and skin burns. May be fatal if inhaled or absorbed through skin. Hamful if a sage and skin burns. May be fatal if inhaled or absorbed through skin. Hamful if a swallowed. Do not breathe vapors or spray mist. Do not get in eyes, on skin, or on clothing. Wear face shield, protective clothing and rubber gloves when handling. Wash thoroughly with soap and water after handling and before eating, dinking, chewing gum, using tobacco or using the toilet. Remove contaminated clothing and wash before reuse.

Physical or Chemical Hazards

Strong oxidizing agent. Corrosive. Mix only with water at ambient (room) remperature. Product must be diluted in accordance with label directions prior to use. SUSTAIN, NO. 464 is not combustible; however, at temperatures exceeding 160°F, decomposition occurs releasing oxygen. The oxygen released could

Environmental Hazards

This pesticide is toxic to birds, fish and aquatic invertebrates. Caution should be used when applying indoors because pets may be at risk. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of the National Pollutant Discharge Elimination System (NDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product into sewer systems without previously notifying the local sewage plant authority.

Storage and Disposal

Storage: Never return SUSTAIN, NO. 464 to the original container after it has been removed. Avoid all contaminants, especially dirt, caustic, reducing agents, and iron or yellow metals. Contamination and impurities will reduce shelf life and can induce decomposition. In case of decomposition, isolate container, douse container with cool water and dilute SUSTAIN, NO. 464 with large volumes of water. Sodium carbonate (soda ash) may be broadcast over the affected area to neutralize the spilled product. Avoid damage to containers. Keep container closed at all times when not in use. To maintain product quality, store this product in a cool, dry area, away from direct sunlight and heat.

Procedure for Leak or Spill: Stop leak if this can be done without risk. Shut off ignition sources. To diames, smoking, flares, or spark producing tools. Keep combustible and organic materials sway. Flush spilled material with large quantities of water. Undiluted materials sway. Flush spilled material with large quantities of water. Undiluted materials should not enter confined spaces. If material has been spilled, an acceptable method of disposal is to sprinkle the area with soda ash, then dilute with at least 20 volumes of water followed by discharge into suitable treatment system in accordance with all Local, State and Federal environmental laws, rules, regulations, standards, and other requirements.

Pesticide Disposal: Non refillable container. Do not use this container to hold materials other than pesticides or dilute pesticides (insates). After emptying and cleaning in the pesticides (insates). After emptying and cleaning in the pesticide or dilute pesticides (insates). After emptying and cleaning in the container. related materials in the container. Contact your state regulatory agency to determine allowable practices in your state. SUSTAIN, NO. 464, which is to be discarded, should be disposed of as hazardous waste after contacting the appropriate Local, State or Federal agency to determine proper procedures. Container Disposal: >5 gallon: Clean container promptly after emptying. Triple seconds after the flow beings to drip. Repeat this procedure two more times. Offer for recycling if available. Or puncture and dispose of in a sanitary landfill, or by incineration, or, if allowed by state and local authorities, by burning. If burned, forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times. 5 rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container 1/4 full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete gallons or less: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow beings to drip. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store insate for later use or disposal. Drain for 10 revolution, for 30 seconds. Stand the container on its end and tip it back and stay out of smoke.

> Under the Federal Insecticity Fringicide, and Rodenticide Act as anrended, for the

EPA Reg No. 2686-19 pesticide, registered under

OCT 14 2011

DOT SHIPPING CLASSIFICATION: UN3098, OXIDIZING LIQ-UID, CORROSIVE, N.O.S. (CONTAINS HYDROGEN PEROX-IDE AND NITRIC ACIDS, STABILIZED)

SCH.# RES.# FP046401 LOT# -

SUSTAIN NO. 464

SUSTAIN, NO. 464 is a phosphate-free peracetic acid / nitric acid based low pH (acid) microbiocide developed for use on food, dairy and beverage processing equipment.

ACLIVE	ACTIVE INGREDIENTS:
Perox	Peroxyacetic Acid6.1%
Hydro	Hydrogen Peroxide23.0%
INERT	NERT INGREDIENTS. 70.9%
TOTAL	100.00

EPA Establishment No. 2686-WI-7 EPA Registration No. 2686-19

Before Using This Product, Please Read This Entire Label Carefully. KEEP OUT OF REACH OF CHILDREN

DANGER

FIRST AID

Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove condict lenses if present after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice. IF IN EYES:

Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice. SWALLOWED

person sip glass of water is able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to Call a poison control center or doctor immediately for treatment advice. Have an unconscious person. IF INHALED:

or doctor for treatment advice.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth. Call a poison control center

Have the product container, label, or MSDS with you when calling a poison control center or a doctor, or going for treatment advice of gastric lavage.

24 Hour EMERGENCY NUMBER: 414/277-1311 or CHEMTREC: 800/424-9300

1.00 LBS .45 KGS NET CONTENTS: 10 GALS

DISTRIBUTED BY:



CORPORATE OFFICE 300 N. PATRICK BLVD. BROOKFIELD, WI 53045

Directions For Use

is a violation of Federal Law to use this product in a manner inconsistent with its

This product passes the EPA food contact sanitizer test for previously cleaned, hard, non-porous food-contact surfaces (AOAC Germicidal and Detergent Sanitizing Action of Disinfectants) against Staphylococcus aureus and Escherichia coli when used as recommended

For FoodBeverage, Wine and Dairy Processing Equipment, Tanks, Vats, For FoodBeverage, Wine and Dairy Processing Equipment, Tanks, Vats, Pails, Pipelines and Closed Systems:

Remove gross food particles and soil by a prefluxh or prescrape, and when necessary, a pre-soak treatment. Clean all surfaces with an appropriate cleaning product, followed by a potable water rinse prior to the application of this product. Sanitize CIP or COP equipment by immersion, circulation or coarse spray sanitizing techniques, as appropriate.

Dilution Instructions: Dilute 1.0 ft. oz. of this product in 6 gallons of water. Solutions up to 1.0 ft. oz. per 4 gallons of water may be used. Do not exceed 140° F of the sanitizing solution. Expose equipment to the sanitizing solution for a minimum of 1 minute. Increased circulation firmes will improve microbiological and/or mineral scale removal results. Adequately drain solution from equipment before resuming operations. A water rinse is not necessary. For mechanical operations the prepared use solution may not be re-used for sanitizing, but may be recycled for other uses such as cleaning, flushing or bulk water pH control for other non-sanitizing purposes

Adjusts sanitizer solution to achieve pH values in the preferred range of pH 2.5-4 if milkstone or mineralstone inhibition/removal is required. The regular use of this product at the recommended pH ranges will prevent the formation of milkstone, beerstone, or mineralstone deposits on food contact surfaces. The pH of this product at 1.0 fl. oz. per 6 gallons (v/v) of 200 ppm (11 grain) hard water will be approximately 3.3-3.6.

Final Sanitizing Beverage Container Rinse: This product may be used as a final sanitizing abeverage container Rinse is a final sanitizing after the sanitizing rinse. Use this product at 1 fl. oz. per 4-6

gallons of water

Combination Cleaning/Descaling and Sanitization For Reveres Osmosis and Other Filtration Systems: This product may be used for all types of industrial and potable water RO. UF and other similar membrane filtration systems for the dual purpose of simultaneously descaling and sanitizing objectives for off-line use. This product is not for use on kidney dialysis equipment. Fror to treatment with this product alkaline clean membranes by the following manufacturer or service companys instructions. Isolate incompatible equipment including all soft metals, charge system with raw water, and add this product to the desired (acid) pH level according to the ranges recommended by the manufacturer or service companys instructions. Isolate incompatible equipment including all soft metals, charge system with raw water, and add this product to the desired (acid) pH level according to the ranges recommended by the manufacture/service company. Be sure to open and close remote manded by the manufacture/service company. Be sure to open and close remote valves during treatment process to assure all surfaces are confacted with the treatment soution. When this treatment is completed, drain or air-purge the system and then resume normal operations. If using dilutions stronger than 11. oz. per 4 process.

Under the Federal Insecticus Fungicide, and

OCT 14 2011

Rodaminade Act as amended, for the

pesticide, registered under EPA Reg. No. 36 8-6-19

This product degrades with age depending on the storage conditions and temperature. KEEP PRODUCT AWAY FROM HEAT OR DIRECT SUNLIGHT. Use a peroxyacetic acid test kit and increase dosage as necessary to obtain the required level of active ingredients. As a reference, a fresh solution should contain about 90 ppm or more peroxyacetic acid at 1.0 ft. oz. per 6 gal. of process water. ucts. SUSTAIN NO. 464 is safe to use on stainless steel and most plastics. Do not use this product in systems that contain copper, brass, aluminum, cast iron or mild steel, as a severe corrosion or acute product decomposition will occur. This product is highly acidic, so do not use with or around chlorinated prod-Note:

FLAMMABILITY REACTIVITY HEALTH

3