

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND
DOMESTIC ANIMALS**

WARNING

KEEP OUT OF REACH OF CHILDREN

Harmful if swallowed. Use with adequate ventilation. Avoid contact with skin and breathing of vapor or spray mist. Causes eye and skin irritation. **FIRST AID:** In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. If inhaled, remove to fresh air, breathe and wash contaminated clothing before reuse. Wash thoroughly with soap and water after handling and before eating and smoking. If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, if these are not available, drink large quantities of water. Never give anything by mouth to an unconscious person. Avoid alcohol. Call a physician immediately.

ENVIRONMENTAL HAZARD

Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL OR CHEMICAL HAZARD

FLAMMABLE! Keep away from heat or open flame

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

NOTE: Wear protective clothing when product is used in confined areas or applied by spraying; wear a respirator jointly approved by the Mining Enforcement and Safety Administration (formerly the U. S. Bureau of Mines) and by the National Institute for Occupational Safety and Health under the provisions of 30 CFR 11.

GENERAL DESCRIPTION

Bottommate is an anti-fouling protective coating resistant to algae, barnacles and other marine fouling.

STORAGE & DISPOSAL

Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

Pesticide spray mixture or rinseate that cannot be used or chemically re-processed should be disposed of according to procedures approved by Federal, State, or local disposal authorities.

Containers (Triple Rinse or equivalent) and dispose of in an approved landfill or bring to a safe place. Consult Federal, State, or local disposal authorities for approved alternative procedures.

BOTTOMKOTE® ANTIFOULING BOTTOM PAINT

PRODUCT DESCRIPTION: The proven standard, all purpose antifouling bottom paint ideally suited for power boats that desire very good, dependable protection. It has universal application over all types of bottom paints and surfaces (except aluminum). Dries to a semi-hard finish, enabling easy clean-up. Ideal for commercial fishing vessels operating in warm waters.

SURFACE PREPARATION: Surface must always be clean, dry and properly prepared prior to application. Failure to do so will lead to eventual blistering and/or peeling. All sanded surfaces must be wiped clean with INTERLUX SPECIAL THINNER 216 to remove sanding residue.

GENERAL APPLICATION: For use on boats below the true waterline. Can be brushed or rolled on smooth and previously painted surfaces per application systems below. Do not use on aluminum unless recommended for best performance.

MIXING & THINNING: Shake or mix thoroughly and stir continuously while using. When applying to bare wood, use not thin bottom paints — except for the first coat on bare wood with INTERLUX SPECIAL THINNER 216.

THEORETICAL COVERAGE: Depending on surface and conditions, one gallon of bottom paint will cover approximately 350 square feet of surface when brushed or rolled.

CLEAN UP: Use INTERLUX SPECIAL THINNER 216 for cleaning equipment. Use INTERLUX LIQUID CLEANER for cleaning paint brushes, however, never use it as a paint additive.

ESTIMATED DRY TIMES: INTERLUX bottom paints are designed for overcoating after a minimum of 24 hours. After launching, allow a minimum dry of overnight and maximum of 48 hours. If drying conditions are poor, longer periods of drying will be required. Fresh coats of paint must be applied overcoating.

APPLICATION SYSTEMS

PREVIOUSLY PAINTED SURFACES - Good Condition: Remove all traces of loose paint and clean the entire surface well with 80-120 grit sandpaper; wipe surface clean. Apply 2 coats of bottom paint. **Poor Condition:** Completely remove all old paint with INTERLUX PINTOFF 299 for fiberglass.