

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND
DOMESTIC ANIMALS**

WARNING

KEEP OUT OF REACH OF CHILDREN

Harmful if swallowed. Use with adequate ventilation. Avoid contact with skin and breathing of vapor or spray mist. Causes eye and skin irritation. **FIRST AID:** In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. If inhaled remove to fresh air. Remove and wash contaminated clothing before reuse. Wash thoroughly with soap and water after handling and before eating and smoking. If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Never give anything by mouth to an unconscious person. Avoid alcohol. Call a physician immediately.

ENVIRONMENTAL HAZARD

Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL OR CHEMICAL HAZARD

**FLAMMABLE! Keep away from heat or
open flame**

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

NOTE—Wear protective clothing when product is used in confined areas or applied by spraying. wear a respirator jointly approved by the Mining Enforcement and Safety Administration (formerly the U. S. Bureau of Mines) and by the National Institute for Occupational Safety and Health under the provisions of 30 CFR 11.

GENERAL DESCRIPTION

Viny-Lux is an anti-fouling protective coating resistant to algae, barnacles and other marine fouling.

STORAGE & DISPOSAL

Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State, or local disposal authorities.

Container—Triple rinse (or equivalent) and dispose of in an approved landfill or bury in a safe place. Consult Federal, State, or local disposal authorities for approved alternative procedures.

(Asiatic Jasmine)
Trachelospermum japonicum
 (Star Jasmine)
Viburnum japonicum
 (Japanese Viburnum)
Viburnum lantago
 (Nannyberry)
Viburnum suspensum
 (Sandankwa Viburnum)
Viburnum trilobum
 (American Cranberry)

Ornamentals, Bedding Plants

Listed by common name

Alyssum
 (*Alyssum* sp.)
 Asparagus, Myers (var: *Meyeri*)
 (*Asparagus densiflorus*)
 Asparagus, Sprenger (var: *Sprengeri*)
 (*Asparagus densiflorus*)
 Begonia
 (*Begonia semperflorens*)
 Bittersweet, American
 (*Calceolaria scandens*)
 Bleeding Heart
 (*Dicentra spectabilis*)
 Cactae, Barrel
 (*Cactus* sp.)
 Candytuff
 (*Iberis sempervirens*)
 Canna
 (*Canna* sp.)
 Cassia, Feathery
 (*Cassia artemisioides*)
 Chrysanthemum frutescens
 (*Chrysanthemum*, Marguerite)
 Chrysanthemum
 (*Chrysanthemum indicum*)
 Cockscomb
 (*Celosia argentea*)
 Coleus
 (*Coleus* sp.)
 Coralbells
 (*Heuchera sanguinea*)
 Coral Beauty
 (*Cotoneaster Dammeri*)
 Dahlia
 (*Dahlia pinnata*)

Listed by scientific name

Acorus gramineus
 (Sweet Grass)
Agapanthus africanus
 (Peter Pan Lily of Africa)
Alyssum sp.
 (Alyssum)
Antirrhinum majus
 (Snapdragon)
Arenaria verna
 (Moss Sandwort)
Arisaema pusillum
 (Jack-in-the-Pulpit)
Armeria maritima
 (Sea Pinks)
Asparagus densiflorus
 (Sprenger Asparagus)
Asparagus densiflorus
 (Myers Asparagus)
Begonia semperflorens
 (Begonia)
Bignonia cherokeeana
 (Blood Red Trumpet)
Bignonia Tweediana
 (Yellow Trumpet)
Bignonia violacea
 (Lavender Trumpet)
Bougainvillea sp.
 (Raspberry Ice)
Cactus sp.
 (Cactae, Barrel)
Canna sp.
 (Canna)
Capsicum sp.
 (Pepper, Ornamental)

VINY-LUX

PRODUCT DESCRIPTION: VINY-LUX is a vinyl resin coating which contains cuprous oxide as its antifouling toxicant. Renders very good, effective protection and a hard, durable finish.

SURFACE PREPARATION: Surfaces must always be clean, dry and properly prepared prior to painting. Failure to do so will lead to blistering and/or peeling. All sanded surfaces must be wiped clean with INTERLUX SPECIAL THINNER 216 to remove sanding residue.

GENERAL APPLICATION: For use on fiberglass, wood and steel boats below the true waterline. Apply two coats with pure bristle brush or short nap roller. Do NOT apply to aluminum and over non-vinyl based bottom paints (vinyls will lift non-vinyls).

MIXING & THINNING INSTRUCTIONS: Shake or mix well and stir continuously while using. When brushing or rolling, do not thin—EXCEPT for the first coat on bare wood with VINY-LUX SOLVENT 355.

DRY TIME BEFORE: OVERCOATING—Minimum 5 hours.
LAUNCHING—Minimum overnight; Maximum 60 days

THEORETICAL COVERAGE: 250 - 300 square feet per gallon when brushed or rolled.

CLEAN UP: Use VINY-LUX SOLVENT 355 for cleaning paint brushes and equipment.

APPLICATION SYSTEMS

PREVIOUSLY PAINTED FIBERGLASS & WOOD: Remove all traces of loose paint and surface contamination by sanding thoroughly with 80-120 Grit Production Paper; wipe surface clean. Apply two coats of VINY-LUX.

BARE FIBERGLASS—No Sand System: Wash entire surface thoroughly with INTERLUX FIBERGLASS SOLVENT WASH 202 to remove wax and dirt, changing rags frequently. Before liquid dries, wipe clean with a dry cloth. Apply with brush or roller one thin continuous coat of INTERLUX FIBERGLASS PRIMER 200. Do not spray. Allow to cure overnight. Do not sand. Apply two coats of VINY-LUX.

Sanding System: Wash entire surface thoroughly with INTERLUX FIBERGLASS SOLVENT WASH 202 to remove wax and dirt, changing rags frequently. Before liquid dries, wipe clean with a dry cloth. Sand entire surface with 80-120 Grit Production Paper until a flat, matte finish is obtained; wipe surface clean. Apply two coats of VINY-LUX.

BARE WOOD: Sand well with 80-120 Grit Production Paper; wipe surface clean. Apply first coat of VINY-LUX reduced 10% with VINY-LUX SOLVENT 355 to penetrate the grain of wood. Fair seams with PUTTY BUG TOXIC SEAM COMPOUND 35 for use in tropical waters or SEAM COMPOUND 30 for use in other waters. Apply second and third coats of VINY-LUX unreduced.

PREVIOUSLY PAINTED STEEL: Remove all loose paint, rust and surface contamination by sanding or using a wire brush; wipe surface clean. Touch up bare spots by roughening with 80 Grit Production Paper then spot priming with at least 4 coats of VINY-LUX UNDERCOATER 352; allow to dry 5 hours between coats. Apply two coats of VINY-LUX.

BARE STEEL: Sandblast to a near white metal; remove blast residue with a broom and air hose. Immediately apply one thin coat of VINY-LUX PRIMEWASH 353/354; allow to dry to a minimum of one hour, maximum of 24. Do not sand. Fill in all imperfections with RED HAND FILLER 4498/4499; sand repaired areas smooth; wipe clean. Apply at least 4 coats of VINY-LUX UNDERCOATER 352; allow to dry minimum of 5 hours between each coat. Apply two coats of VINY-LUX.

**This is a simple system for small areas. For a more advanced, professional system, please consult the INTERLUX Technical Department: INTERNATIONAL PAINT COMPANY, INC. P.O. Box 386, Union, N. J. 07083 — or — 220 South Linden Avenue, South San Francisco, CA 94080.*

BEST AVAILABLE COPY