

VINY-LUX ANTIFOULING PAINT

DIRECTIONS

For protection from fouling on the bottoms of **WOOD**, **FIBERGLASS** and **STEEL** boats. Made with a Vinyl resin base, to a durable, hard and smooth finish containing a high percentage of antifouling toxic properties. It is highly resistant to water friction for an indefinite period.

For best results **VINY-LUX** should be applied over bare wood.

Always see that the surface is dry and clean before painting. To mix this paint, pour from one can to another several times, stirring well between each pouring and during application.

Do not reduce this paint with any thinner other than 355 VINY-LUX SOLVENT.

WOOD BOTTOMS—New Work

1. On bare wood, add about 10% **355 VINY-LUX SOLVENT** to the antifouling for the priming coat. Allow at least three hours for drying before coating over.

2. Apply two coats **VINY-LUX ANTIFOULING** without thinning, allowing three hours for drying between coats and before launching.

WOOD BOTTOMS—Old Work

When the surface is dry and clean, sand well and apply two coats **VINY-LUX ANTIFOULING**, thinning the first coat about 10% with **355 VINY-LUX SOLVENT**. Do not thin the final coat. Allow three hours for drying between coats and before launching.

FIBERGLASS BOTTOMS

Wipe surface clean with **202 "INTERLUX" FIBERGLASS SOLVENT WASH**. Apply one coat of **200 "INTERLUX" FIBERGLASS PRIMER**. (Sanding of fiberglass not required.) Allow five to six hours dry time, then apply two coats of **VINY-LUX** — red, green or blue.

STEEL BOTTOMS (excluding ALUMINUM)

Prepare surface to clean bright metal. (sandblasting, rotary grinding, etc.) Next apply one coat of **353/54 VINY-LUX PRIMEWASH** followed by three coats of **352 VINY-LUX UNDERCOATER**. Allow three hours drying time between coats and before coating over.

The surface is then ready for the application of two coats of **VINY-LUX ANTIFOULING**.



ONE U.S. GALLON

WARNING!

KEEP OUT OF REACH OF CHILDREN

See other warnings on back panel

Viny-lux
VINYL-BASE PAINT


340 ANTIFOULING BLUE

Oct-13-1970

2693-18

ACTIVE INGREDIENTS	PER CENT
Cuprous Oxide	35.0%
INERT INGREDIENTS	65.0%
	100.0%

ELEMENTAL COPPER 31.0%



International Paint Company, Inc.

NEW YORK, N. Y. 10006 • SAN FRANCISCO, CAL. 94080 • NEW ORLEANS, LA. 70126

Oct-13-1970

FACTORIES

2693-18

U.S.A.	UNION, N. J.	HOLLAND	RIJSWIJK
U.S.A.	SAN FRANCISCO	ITALY	GENOA
U.S.A.	NEW ORLEANS	ITALY	TRIESTE
AUSTRALIA	SYDNEY	MEXICO	MEXICO CITY
BRAZIL	RIO DE JANEIRO	NEW ZEALAND	AUCKLAND
CANADA	MONTREAL	NEW ZEALAND	WELLINGTON
CANADA	REGINA	NIGERIA	IKEJA
CANADA	VANCOUVER	NORWAY	BERGEN
DENMARK	COPENHAGEN	PORTUGAL	SETUBAL
	FELTING-ON-TYNE	SCOTLAND	GLASGOW
	ROUEN	SPAIN	BILBAO
	HAMBURG	SWEDEN	GOTHENBURG
		VENEZUELA	MARACAIBO

WARNING

Harmful if swallowed. Do not use or store near heat or open flame.

Use with adequate ventilation.

Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use.

U.S.D.A. Reg. No. 2693-18

