

ACCEPTED
FEB 18 1993
 Under the Federal Insecticide,
 Fungicide, and Rodenticide Act,
 as amended, for the pesticide
 registered under EPA Reg. No. 2693-19

Inter

**PRECAUTIONARY STATEMENTS
 HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

WARNING

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long sleeved shirt, long pants and hat. Wash thoroughly with soap and water after handling and before eating and smoking. May be fatal if swallowed or inhaled. Do not breathe dust, vapor or spray mist. When product is used in confined areas or applied by spraying, wear a respirator (only approved by the Mining Enforcement and Safety Administration formerly the U.S. Bureau of Mines) and by the National Institute for Occupational Safety and Health.

Statement of Practical Treatment: If in eyes, immediately flush with plenty of water for at least 15 minutes. Get medical attention. If on skin, immediately remove contaminated clothing, wash with plenty of soap and water. Get medical attention. If skin contaminated, change before reuse if inhaled. Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention. If swallowed, drink promptly a large quantity of water. Avoid alcohol. Get medical attention.

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning equipment or disposal of wastes. Do not allow fumes and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS

FLAMMABLE: Keep away from heat, sparks or open flame.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. **NOTE:** Protective clothing and respirators should be used as described under Precautionary Statements.

GENERAL DESCRIPTION

This product is an anti-rusting protective coating resistant to alkaline detergents and other marine fouling. For use in fresh, salt and brackish waters.

STORAGE & DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Paint that cannot be used according to label instructions must be disposed of according to Federal, State or local procedures under the Resource Conservation and Recovery Act.

CONTAINER DISPOSAL: Dispose of container by triple rinse and recycling or puncturing and disposing in a sanitary landfill or by other approved State and local procedures. If burned, stay out of smoke.

VINY-L

VINYL ANTI-RUST COATING

350 RED

**KEEP OUT OF REACH OF CHILDREN
 WARNING!**

See Side Panel for additional precautionary information.
ONE OF GARDNER'S

BEST AVAILABLE COPY

sterlux®



VINYLUX

ANTIFOULING PAINT

350 RED

KEEP OUT OF REACH OF CHILDREN
WARNING!
Contains Cuprous Oxide
(1 GALLON / 3.78 LITERS)

ACTIVE INGREDIENTS	PERCENT
Cuprous Oxide	42.7%
INERT INGREDIENTS	57.3%
ELEMENTAL COPPER	37.0%

REG. NO. 5880-10
EST. 2003-NJ-1

DIRECTIONS FOR USE (CONTINUED) VINYLUX ANTIFOULING PAINT 350 R

PRODUCT DESCRIPTION: VINYLUX ANTIFOULING PAINT 350 RED is a urethane coating which is an antifouling paint. Renders very good, effective protection and a hard, durable finish.

SURFACE PREPARATION: Surfaces must always be clean, dry and properly prepared prior to p... will lead to blistering and/or peeling. All sanded surfaces must be wiped clean with INTERLUX 355 remove sanding residue.

GENERAL APPLICATION: For use on fiberglass, wood and steel boats below the true waterline. Apply with brush or short nap roller. Do not apply to aluminum and over gun and base of bottom for vinyls.

MIXING & THINNING INSTRUCTIONS: Shake or stir well and stir continuously while using. Use not thin... EXCEPT for the first coat which is applied with VINYLUX SOLVENT 355.

DRY TIME BEFORE OVERCOATING:—Minimum 5 hours
LAUNCHING:—Maximum overnight, Maximum 60 days

THEORETICAL COVERAGE: 250 - 300 square feet per gallon when brushed or rolled
CLEAN-UP: Use VINYLUX SOLVENT 355 for cleaning paint brushes and equipment.

APPLICATION SYSTEMS

PREVIOUSLY PAINTED FIBERGLASS & WOOD: Remove all traces of loose paint and surface clean thoroughly with 80/120 grit production paper, wipe surface clean. Apply two coats of VINYLUX RED.

BARE FIBERGLASS - No Sand System: Wash entire surface thoroughly with INTERLUX FIBERGLASS to remove wax and dirt, changing rags frequently. Before liquid dries, wipe clean with a dry cloth, roller one thin, continuous coat of INTERLUX FIBERGLASS PRIMER 200. Do not spray. Allow 1 sand. Apply two coats of VINYLUX ANTIFOULING PAINT 350 RED.

Sanding System: Wash entire surface thoroughly with INTERLUX FIBERGLASS SOLVENT WASH dirt, changing rags frequently. Before liquid dries, wipe clean with a dry cloth. Sand entire surface with 80/120 grit production paper until a flat, matte finish is obtained, wipe surface clean. Apply two coats of VINYLUX 350 RED.

BARE WOOD: Sand well with 80/120 grit production paper, wipe surface clean. Apply first coat PAINT 350 RED reduced 10% with VINYLUX SOLVENT 355 to penetrate the grain of wood. For PRIMER 30. Apply second and third coats of VINYLUX ANTIFOULING PAINT 350 RED unreduc

PREVIOUSLY PAINTED STEEL: Remove all loose paint, rust and surface contamination by sanding, wipe surface clean. Touch up bare spots by roughening with 80 grit production paper then sand coats of VINYLUX UNDERCOATER 352, allow to dry 5 hours between coats. Apply two coats PAINT 350 RED.

BARE STEEL: Sandblast to a near white metal, remove blast residue with a broom and air hose. Apply coat of VINYLUX PRIMEWASH 353/354, allow to dry minimum of 1 hour, maximum of 24 hours. Apply at least 4 coats of VINYLUX UNDERCOATER 352, allow to dry minimum of 5 hours between coats. Apply two coats of VINYLUX ANTIFOULING PAINT 350 RED.

*This is a simple system for small areas. For a more advanced, professional system, please contact our Technical Department, Courtaulds Coatings Inc., P.O. Box 386, Union, NJ 07087.

Courtaulds Coatings Inc.
2270 Morris Avenue, Union, NJ 07083
(908) 686-1000

BEST AVAILABLE COPY

DIRECTIONS FOR USE (CONTINUED)
V-LUX ANTIFOULING PAINT 350 RED

V-LUX ANTIFOULING PAINT 350 RED is a vinyl resin coating which renders very good, effective protection and a hard, durable finish. Surfaces must always be clean, dry and properly prepared prior to painting. Failure to do so will result in poor adhesion. All sanded surfaces must be wiped clean with INTERLUX SOLVENT 355 before painting. For use on fiberglass, wood and steel parts below the true waterline. Do not apply to aluminum and other non-ferrous metals. Coats with pure water will kill non-toxic organisms. Mixing or rolling do not affect the product. The first coat should be applied with V-LUX SOLVENT 355. Recoating - Minimum 5 hours. Drying - Minimum overnight. Maximum 60 days. Coverage: 250 - 300 square feet per gallon when brushed or rolled. Use V-LUX SOLVENT 355 for cleaning paint brushes and equipment.

APPLICATION SYSTEMS

FIBERGLASS & WOOD: Remove all traces of loose paint and surface contamination by sanding with 80 grit production paper, wipe surface clean. Apply two coats of V-LUX ANTIFOULING PAINT 350 RED. **Sand System:** Wash entire surface thoroughly with INTERLUX FIBERGLASS SOLVENT WASH 202, changing rags frequently. Before liquid dries, wipe clean with a dry cloth. Apply with brush or roller coat of INTERLUX FIBERGLASS PRIMER 200. Do not spray. Allow to cure overnight. Do not sand until surface is thoroughly clean. Sand entire surface with 80 grit production paper, wipe surface clean. Apply two coats of V-LUX ANTIFOULING PAINT 350 RED. **WOOD:** Wash entire surface thoroughly with INTERLUX FIBERGLASS SOLVENT WASH 202 to remove wax and grease. Before liquid dries, wipe clean with a dry cloth. Sand entire surface with 80 grit production paper, wipe surface clean. Apply two coats of V-LUX ANTIFOULING PAINT 350 RED. **STEEL:** Remove all loose paint, rust and surface contamination by sanding or using a wire brush. Roughen bare spots by roughening with 80 grit production paper then spot priming with at least 4 coats of INTERLUX UNDERCOATER 352, allow to dry 5 hours between coats. Apply two coats of V-LUX ANTIFOULING PAINT 350 RED. **WOOD & STEEL:** Blast to a near white metal, remove blast residue with a broom and air hose. Immediately apply one coat of INTERLUX PRIMER WASH 353-354, allow to dry minimum of 1 hour, maximum of 24. Do not sand. Fill in all imperfections with INTERLUX SURFACING & TAMPING COMPOUND 417/418, sand repaired areas smooth and wipe clean. Apply one coat of INTERLUX UNDERCOATER 352, allow to dry minimum of 5 hours between each coat. Apply two coats of V-LUX ANTIFOULING PAINT 350 RED. **WOOD & STEEL:** For small areas for a more advanced, professional system, please consult the INTERLUX Technical Department, Courtaulds Coatings Inc., P.O. Box 386, Union, NJ 07083.

Rev. 1/69

Courtaulds Coatings Inc.
2270 Morris Avenue, Union, NJ 07083
(908) 686-7300

DIRECTIONS FOR USE (CONTINUED)

This product is an antifouling protective coating resistant to algae, barnacles and other marine fouling. **SURFACE PREPARATION AND COMPATIBILITY:** Surface preparation directions must be followed exactly in order to ensure adhesion. Surface must always be clean and dry prior to painting. **GENERAL APPLICATION PROCEDURES:** Airless spray is recommended; tip size 21-26 thou. inch, pump ratio of 30:1 or greater. For small areas brush or roller may be used but multiple coats may be required to achieve the required dry film thickness. It is recommended to apply by airless spray one (1) or two (2) full coats of this product. **MIXING AND THINNING INSTRUCTIONS:** Mix thoroughly with power mixer prior to application. This coating is designed to be applied without thinning. Should thinning be necessary, consult your International representative prior to altering this coating. **CLEAN-UP:** For tools, equipment, etc., use INTERNATIONAL GTA007. **MINIMUM DRY AND LAUNCHING TIMES:** Minimum drying time between coats is 6 hours, and before launching is 12 hours at a temperature of 73°F. **THEORETICAL COVERAGE:** 290 square feet per gallon, per coat at 2.0 mils D.F.T. Consult your International representative for practical application coverages. Practical square foot coverage per gallon, per coat is directly proportional to surface, application techniques and climatic conditions.

APPLICATION SYSTEMS

EXISTING ANTIFOULING SYSTEMS - GOOD CONDITION: High pressure fresh water wash with a minimum of 2500 psi and/or scrape to remove all marine growth, slime, salts, etc. Spot blast all areas of corrosion to a Near White Metal Standard of SSPC-SP 10-85. Blow down with clean and dry high pressure air to remove all spent abrasives. Apply an approved underwater anticorrosive system. **POOR CONDITION:** For "optimum" results, blast entire area to a Near White Metal Standard SSPC-SP 10-85. Apply an approved underwater anticorrosive system. **NEW SHIP CONSTRUCTION:** Blast entire area to a Near White Metal Standard SSPC-SP 10-85. Blow down with clean and dry high pressure air to remove all spent abrasives. Apply an approved underwater anticorrosive system. **WOOD AND NON-FERROUS SURFACES:** Use surface preparation and primers as specified by the Navy.

BEST AVAILABLE COP